

Mfrs. List Nos:	T3P26MC1LX=118-6768	T3P26FC1LX=118-6774
	T3P24MC1LX=118-6769	T3P24FC1LX=118-6775
	T3P22MC1LX=118-6770	T3P22FC1LX=118-6776
	T3P20MC1LX=118-6771	T3P20FC1LX=118-6777
	T3P16MC1LX=118-6773	T3P16FC1LX=118-6778

Wire Size	Colour	Order Code	10+	50+	100+	500+	+
<b>Pins</b>							
26AWG	Black	118-6768	24.00	21.00	18.00	15.00	--
24AWG	Blue	118-6769	24.00	21.00	18.00	15.00	--
22AWG	Red	118-6770	24.00	21.00	18.00	15.00	--
20AWG	Green	118-6771	24.00	21.00	18.00	15.00	--
AWG16	Black	118-6773	24.00	21.00	18.00	15.00	--
<b>Sockets</b>							
26AWG	Black	118-6774	24.00	21.00	18.00	15.00	--
24AWG	Blue	118-6775	24.00	21.00	18.00	15.00	--
22AWG	Red	118-6776	24.00	21.00	18.00	15.00	--
20AWG	Green	118-6777	24.00	21.00	18.00	15.00	--
16AWG	Black	118-6778	24.00	21.00	18.00	15.00	--

**Metalok Bantam EMC Shielded System**  
Crimp 4 to 48 Way, 13A



- Immediate EMC solution for new designs
- Instant retrofit for existing Metalok Bantam users, to meet EMC requirements
- 360 degrees electrical continuity for grounding
- Ease of assembly
- IP65 rating when O ring fitted

Contact rating	See contact specs
Operating voltage	750 Vrms
Insulation resistance	5000 mΩ min.
Operating temperature	-25°C to +125°C
Housing	(Body) Glass filled polyester UL94V-0 (Plating) Nickel plating to the outside of connector body and bayonet ring

**Free Housing**

No. of Ways	Shell Size	Mfrs. List No.	Order Code	1+	25+	50+	100+	+
<b>Pin Housing - Accepts Pin Contacts</b>								
4	10	UTGS6PG104PN	748-456	2,037.00	1,853.00	1,667.00	1,347.00	--
8	12	UTGS6PG128PN	748-468	2,074.00	1,884.00	1,696.00	1,371.00	--
12	14	UTGS6PG1412PN	748-470	2,145.00	1,950.00	1,753.00	1,418.00	--
19	16	UTGS6PG1619PN	748-481	2,263.00	2,057.00	1,850.00	1,496.00	--
23	18	UTGS6PG1823PN	748-493	2,379.00	2,162.00	1,946.00	1,681.00	--
28	20	UTGS6PG2028PN	748-500	2,645.00	2,402.00	2,162.00	1,749.00	--
<b>Socket Housing - Accepts Socket Contacts</b>								
4	10	UTGS6PG104SN	748-535	2,037.00	1,853.00	1,667.00	1,347.00	--
8	12	UTGS6PG128SN	748-547	2,074.00	1,884.00	1,696.00	1,371.00	--
12	14	UTGS6PG1412SN	748-559	2,145.00	1,950.00	1,753.00	1,418.00	--
19	16	UTGS6PG1619SN	748-560	2,263.00	2,057.00	1,850.00	1,496.00	--
23	18	UTGS6PG1823SN	748-572	2,379.00	2,162.00	1,946.00	1,681.00	--
28	20	UTGS6PG2028SN	748-584	2,645.00	2,402.00	2,162.00	1,869.00	--
48	24	UTGS6PG2448SN	748-602	3,077.00	2,797.00	2,517.00	2,206.00	--

**Panel Housing**

ORDER CONTACTS SEPARATELY SEE WEBSITE

No. of Ways	Shell Size	Mfrs. List No.	Order Code	1+	25+	50+	100+	+
<b>Pin Housing - Accepts Pin Contacts</b>								
4	10	UTGS0104PN	748-614	640.00	580.00	523.00	422.00	--
8	12	UTGS0128PN	748-626	670.00	609.00	547.00	442.00	--
12	14	UTGS01412PN	748-638	686.00	623.00	561.00	454.00	--
19	16	UTGS01619PN	748-640	732.00	663.00	598.00	484.00	--
23	18	UTGS01823PN	748-651	749.00	680.00	613.00	495.00	--
28	20	UTGS02028PN	748-663	1,050.00	953.00	856.00	694.00	--
48	24	UTGS02448PN	748-687	1,132.00	1,029.00	926.00	800.00	--

No. of Ways	Shell Size	Mfrs. List No.	Order Code	1+	25+	50+	100+	+
<b>Socket Housing - Accepts Socket Contacts</b>								
4	10	UTGS0104SN	748-699	640.00	580.00	523.00	422.00	--
8	12	UTGS0128SN	748-705	670.00	617.00	--	--	--
12	14	UTGS01412SN	748-717	686.00	623.00	561.00	454.00	--
19	16	UTGS01619SN	748-729	732.00	663.00	598.00	484.00	--
23	18	UTGS01823SN	748-730	770.00	680.00	613.00	495.00	--
28	20	UTGS02028SN	748-742	1,050.00	953.00	856.00	694.00	--
48	24	UTGS02448SN	748-766	1,132.00	1,029.00	926.00	800.00	--

**'Metalok Bantam' Crimp 3 to 48 Way, 13A**

**IP65 Sealed**

Circular plastic connector shells with 5 polarising keyways and a snap-locking bayonet ring. The housings can accept either machined, two-piece or coaxial contacts as a pin or socket insert. IP65 sealing can be achieved with the environmental hood and 'O' ring panel seal. The range is UL Recognised and the 3 and 7 way also have VDE approval

**Note:** The 3 & 4 and 7 & 23 way options within this range occupy the same shell size, therefore when ordering accessories such as 'O' ring seals, dust caps and cable strain reliefs the shell size is common to both, i.e, 10 and 18 respectively.

Contact rating	See contact specs	Housing	BlackGlass filled polyester, UL94V-0
Operating voltage	750V rms	Bayonet ring	Brass, nickel plated
Insulation resistance	5000 MΩ min.		500 mating cycles
Temperature range	-55°C to +125°C	Dust cap	Copper alloy, Nickel plated

**Free Housings, UTG Series**



Mfrs. List No. UTG-6/yy/xxzN, UTG-6/yy/xxzNVDE for 3 and 7 ways, where xx= No Of Ways, yy=Shell size and z=P Pin, S Socket

No. of Ways	Shell Size	Order Code	1+	25+	100+	250+	+
<b>Pin Housing - Accepts Pin Contacts</b>							
3	10	150-619	654.00	603.00	493.00	418.00	--
4	10	105-317	540.00	511.00	406.00	345.00	--
7	18	105-318	710.00	623.00	587.00	370.00	--
8	12	105-319	594.00	535.00	443.00	375.00	--
12	14	105-320	566.00	510.00	505.00	465.00	--
19	16	105-321	631.00	540.00	476.00	406.00	--
23	18	105-322	704.00	648.00	635.00	504.00	--
28	20	105-323	873.00	774.00	757.00	694.00	--
35	22	105-324	1,018.00	910.00	785.00	672.00	--
48	24	105-325	994.00	885.00	840.00	719.00	--
<b>Socket Housing - Accepts Socket Contacts</b>							
3	10	150-621	654.00	603.00	466.00	400.00	--
4	10	105-335	525.00	471.00	462.00	392.00	--
7	18	105-336	702.00	639.00	627.00	470.00	--
8	12	105-337	547.00	479.00	475.00	447.00	--
12	14	105-338	786.00	709.00	670.00	537.00	--
19	16	105-339	631.00	562.00	477.00	408.00	--
23	18	105-340	652.00	580.00	550.00	504.00	--
28	20	105-341	873.00	774.00	757.00	694.00	--
35	22	105-342	1,017.00	910.00	840.00	648.00	--
48	24	105-343	969.00	885.00	840.00	696.00	--

**Hoods, UTG Series**



Both hoods have cable strain relief and the environmental hood also has multiple knockout rubber seals giving protection to IP65.

Mfrs. List No. UTGxx/AC or PG, where xx=Shell size

No. of Ways	Shell Size	Order Code	1+	25+	100+	+	+
<b>AC Basic</b>							
3&4	10	105-579	254.00	228.00	217.00	--	--
8	12	105-581	254.00	239.00	222.00	--	--
12	14	105-582	270.00	240.00	223.00	--	--
19	16	105-583	277.00	247.00	229.00	--	--
7&23	18	105-580	271.00	252.00	236.00	--	--
28	20	105-585	286.00	272.00	259.00	--	--
35	22	105-586	322.00	290.00	261.00	--	--
48	24	105-587	305.00	285.00	266.00	--	--

5

Connectors - Multipole

Compliant Non-compliant + Limited stock - RoHS replacement available