

Grommet Strip - continued

Rayrim™ Adhesive Panel Edging - continued

A (max)	B (min)	C (min)	D (min)	E (typical)	Mfrs. List No.	Order Code
0.6	0.5	3.5	0.8	1.25	RAYRIM-NR6-0-769-174	1.2m 769-174 5m 134-727
1.0	0.9	4.8	1.6	1.25	RAYRIM-NR7-0-769-186	769-186 134-739
2.0	0.9	6.6	2.5	2.25	RAYRIM-NR8-0-769-198	769-198 134-740
4.2	0.9	13.5	4.5	2.20	RAYRIM-NR9-0-769-204	769-204 134-752

Panel Thickness (max)	Order Code	1+	25+	100+	250+
1.2m Length	769-174	155.00	140.00	120.00	104.00
	769-186	201.00	179.00	154.00	135.00
	769-198	288.00	251.00	217.00	188.00
	769-204	493.00	440.00	388.00	381.00
5m Length	134-727	634.00	573.00	491.00	425.00
	134-739	821.00	731.00	630.00	552.00
	134-740	1,153.00	1,026.00	887.00	769.00
	134-752	2,015.00	1,798.00	1,586.00	1,385.00

Panel Edging



A versatile method of protection from raw metal edges of panels, racks and cabinets, grommet strip may be used along straight or formed curved edges. It may also be used to form internal protection for cut-outs, either round or rectangular.

Material Polyethylene Operating temperature -50°C to +50°C 224117

25m Lengths Panel Thickness	Order Code	1+	5+	10+	25+	+
1.0 — 1.10mm	141-550	861.00	791.00	746.00	612.00	--
1.5 — 2.0mm	141-551	949.00	846.00	801.00	616.00	--
2.5 — 3.30mm	141-552	1,021.00	931.00	881.00	681.00	--

Cable Glands

IP66 - Nylon



A range of Nylon 66 compression glands complete with lock nut and soft Nylon washer. Designed for use with circular PVC and rubber cable the gland provides a waterproof entry and strain relief to **IP66**. Available in Black or White.

Cable Dia.	Mounting Thread Size	Mounting Thread Length	Front Panel Projection	Black Order Code	White Order Code
5-7	M13x1.0	8	21	143-607	218-285
4-7	M20x1.5	8	21	151-831	218-297
7-10.5	M16x1.5	10	25	143-608	218-303
7-10.5	M20x1.5	10	25	151-832	218-315
8-13	M20x1.5	11	31	143-609	218-327

Black Cable Dia.	Order Code	5+	50+	100+	500+	+
5-7	143-607	43.00	40.00	38.00	34.00	--
4-7	151-831	41.00	36.00	34.00	32.00	--
7-10.5	143-608	41.00	35.00	33.00	31.00	--
7-10.5	151-832	40.00	35.00	34.00	31.00	--
8-13	143-609	53.00	48.00	45.00	42.00	--
White 5-7	218-285	43.00	39.00	38.00	34.00	--
4-7	218-297	41.00	36.00	34.00	31.00	--
7-10.5	218-303	41.00	37.00	35.00	32.00	--
7-10.5	218-315	40.00	36.00	34.00	31.00	--
8-13	218-327	51.00	44.00	42.00	39.00	--

Cord Grip Bushes



- Moulded in Black Nylon 66
- Reversible clamping bar for wide cable diameter range
- Compatible with IP66 Nylon glands above
- Optional locknuts available separately
- Flame retardant to **UL94V-2**

Operating temperature -10 °C to 90 °C

Mounting Thread Size	Cable Diameter	Mounting Thread Length	Overall Length	A/F Size	Order Code Bush	Order Code Locknut
M16x1.5	3.5-11	9	23.5	19	303-0740	303-0775
M20x1.5	4-14.5	12	29.5	23	303-0751	303-0787
M25x1.5	8-18	12	29.5	27	303-0763	303-0799

Thread Size	Order Code	10+	50+	100+	500+
Cord Grip Bushes M16x1.5	303-0740	23.00	21.00	22.00	21.00
M20x1.5	303-0751	24.00	23.00	22.00	21.00
M25x1.5	303-0763	50.00	49.00	47.00	46.00
Locknuts M16x1.5	303-0775	8.00	7.00	6.00	6.00
M20x1.5	303-0787	7.00	7.00	6.00	6.00
M25x1.5	303-0799	18.00	17.00	15.00	14.00

IP68 - Nylon



- A range of **IP68** sealed compression cable glands
- Available in Metric and PG thread
- Metric supplied complete with lock nut and washer, PG only with lock nut
- Manufactured from UL recognised (**UL94V-2**) NYLON 66



Mounting Thread Size	Cable Diameter	Mounting Thread Length	Colour	Order Code Bush
PG7	3-6.5	8	Grey	927-648
PG9	4-8	8.1	Grey	927-650
PG11	5-10	8.2	Grey	927-661
PG13.5	6-12	8.9	Grey	927-673
PG16	10-14	8.9	Grey	927-685
PG21	13-18	10.8	Grey	927-697
PG29	18-25	10.9	Grey	927-703
M12	3-6.5	7.9	Black	927-715
M16	5-10	14.4	Black	927-727
M20	10-14	12.8	Black	927-739
M25	13-18	13.9	Black	927-740
M32	18-25	14.6	Black	927-752
M40	22-32	17.7	Black	317-7233
M50	30-38	17.3	Black	317-7245
M63	34-44	18.6	Black	317-7257

Thread Size	Order Code	5+	50+	100+	250+	+	+
Grey							
PG7	927-648	54.00	51.00	47.00	42.00	--	--
PG9	927-650	56.00	53.00	49.00	44.00	--	--
PG11	927-661	61.00	58.00	55.00	49.00	--	--
PG13.5	927-673	74.00	69.00	66.00	63.00	--	--
PG16	927-685	85.00	80.00	76.00	68.00	--	--
PG21	927-697	155.00	145.00	135.00	120.00	--	--
PG29	927-703	255.00	227.00	204.00	196.00	--	--
Black							
M12	927-715	58.00	49.00	44.00	40.00	--	--
M16	927-727	60.00	52.00	47.00	42.00	--	--
M20	927-739	62.00	54.00	49.00	44.00	--	--
M25	927-740	79.00	68.00	63.00	58.00	--	--
M32	927-752	156.00	154.00	150.00	138.00	--	--
M40	317-7233	199.00	168.00	157.00	143.00	--	--
M50	317-7245	248.00	227.00	212.00	193.00	--	--
M63	317-7257	320.00	297.00	286.00	264.00	--	--

IP68 - Nylon - 'Perfect' Dome Top - with Locknut



A range of **VDE** approved compression type polyamide cable glands, available in Grey with PG thread or Black with Metric thread. Designed for use with circular PVC or rubber cables and provides protection to **IP68** when spanner tightened.

- Supplied complete with locknut
- Wide clamping range available