

Rating	Order Code	Price Each			
		10+	100+	500+	1K+
1A	117-5102	102.00	89.00	73.00	70.00
1.6A	117-5112	92.00	84.00	73.00	69.00
2A	117-5103	85.00	76.00	66.00	63.00
2.5A	117-5113	92.00	84.00	73.00	69.00
3.15A	117-5104	85.00	76.00	66.00	63.00
4A	117-5114	92.00	84.00	73.00	69.00
5A	117-5106	85.00	76.00	66.00	63.00
6.3A	117-5107	85.00	76.00	70.00	--
8A	117-5108	85.00	76.00	70.00	--
10A	117-5109	85.00	76.00	70.00	--
12.5A	117-5110	85.00	76.00	70.00	--
16A	117-5111	85.00	76.00	70.00	--

**Quick Blow (F) Ceramic**  
MCF07C Series



- Manufactured to meet UL and CSA time/current characteristics
- CSA approved up to 15A


Voltage rating 250V ac Breaking capacity @ 250V ac  
Up to 500mA = 35A 750mA to 3A = 100A  
4A to 7A = 200A 8A to 15A = 750A  
20A = 1000A

Mfrs. List No. MCF07C + Rating

204513

Rating	Order Code	Price Each				
		10+	100+	500+	1K+	+
125mA	119-0663	28.00	26.00	23.00	18.00	--
500mA	119-0664	24.00	23.00	21.00	16.00	--
1A	119-0665	24.00	23.00	21.00	16.00	--
2A	119-0666	24.00	23.00	21.00	16.00	--
3A	119-0667	24.00	23.00	21.00	16.00	--
5A	119-0668	24.00	23.00	21.00	16.00	--
6A	119-0669	24.00	23.00	21.00	16.00	--
8A	119-0670	24.00	23.00	21.00	16.00	--
10A	119-0671	24.00	23.00	21.00	16.00	--
12A	119-0673	24.00	23.00	21.00	16.00	--
15A	119-0674	24.00	23.00	21.00	16.00	--
20A	119-0675	28.00	26.00	23.00	19.00	--

**Quick Blow (F) HRC Ceramic**  
70-065-63 Series



UL Recognised (up to 6.3A)

Voltage Rating (Vn) 500V ac  
Breaking capacity 1500A @ Vn  
Mfrs. List No. 70-065-63 + rating

204388

Rating	Order Code	Price Each			
		10+	100+	500+	1K+
500mA	117-5115	22.00	20.00	18.00	18.00
1A	117-5116	22.00	20.00	18.00	18.00
2A	117-5118	22.00	20.00	18.00	18.00
3A	117-5119	22.00	20.00	18.00	18.00
5A	117-5120	22.00	20.00	18.00	18.00
6.3A	117-5124	21.00	19.00	18.00	17.00
7A	117-5121	22.00	20.00	18.00	18.00
10A	117-5122	22.00	20.00	18.00	18.00
16A	117-5123	25.00	22.00	18.00	17.00

**Quick Blow (F) Glass**  
MCF01G Series



- CSA approved


Voltage rating 250V Breaking capacity 250mA to 1A 35A @ 250V ac  
1.25 to 3A 100A @ 250V ac  
4A to 10A 200A @ 250V ac

Mfrs. List No. MCF01G + Rating

204486

Rating	Order Code	Price Each				
		10+	100+	500+	1K+	+
500mA	119-0653	10.00	9.00	8.00	7.00	--
1A	119-0654	10.00	9.00	8.00	7.00	--
2A	119-0655	10.00	9.00	8.00	7.00	--
3A	119-0656	10.00	9.00	8.00	7.00	--
4A	119-0657	10.00	9.00	8.00	7.00	--
5A	119-0658	10.00	9.00	8.00	7.00	--
6A	119-0661	10.00	9.00	8.00	7.00	--
10A	119-0662	10.00	9.00	8.00	7.00	--

**Quick Blow (F) Glass**  
TDC10 Series



Complies with BS2950A

Voltage rating (Vn): 60mA - 250mA 1000V ac 1.5A - 5A 250V ac  
500mA 750V ac 7.5A 150V ac  
750mA 500V ac 10A 100V ac  
1A - 1.25A 350V ac 12A - 25A 32V ac  
Breaking capacity 10 x In @ Vn Mfrs. List No. TDC10 + Rating

204395

Rating	Order Code	Price Each			
		10+	100+	500+	1K+
60mA	534-869	37.00	33.00	30.00	30.00
100mA	534-870	48.00	42.00	39.00	37.00
150mA	534-882	37.00	33.00	30.00	30.00
250mA	534-894	11.00	10.00	9.00	9.00
500mA	534-900	11.00	10.00	10.00	9.00
750mA	534-912	11.00	10.00	9.00	9.00
1A	534-924	9.00	8.00	7.00	7.00
1.25A	534-936	9.00	8.00	7.00	8.00
1.5A	534-948	9.00	8.00	7.00	7.00
2A	534-950	9.00	8.00	7.00	7.00
2.5A	534-961	9.00	8.00	7.00	7.00
3A	534-973	9.00	8.00	7.00	7.00
5A	534-985	9.00	8.00	7.00	7.00
7.5A	534-997	9.00	8.00	7.00	7.00
10A	535-000	9.00	9.00	8.00	7.00
12A	535-011	12.00	10.00	9.00	8.00
15A	535-023	9.00	9.00	8.00	7.00
20A	535-035	12.00	10.00	9.00	8.00
25A	535-047	12.00	10.00	9.00	8.00

**Antisurge (T), Ceramic**  
70-065-65 Series



- UL Recognised up to 16A

Voltage Rating (V) 500V ac (up to 10A)  
440V ac (12.5A-25A)  
250V ac (32A)  
Breaking capacity 1500A @ V (up to 25A)  
1000A @ V (32A)  
Maximum voltage drop 800-150mV

Please note that when using 8A or over, consideration should be given to heat dissipation

Mfrs. List No. 70-065-65 + Rating

204524

Rating	Order Code	Price Each				
		10+	100+	500+	1K+	+
500mA	117-5139	30.00	26.00	24.00	21.00	--
1A	117-5140	30.00	26.00	24.00	21.00	--
2A	117-5141	30.00	26.00	24.00	21.00	--
2.5A	117-5143	30.00	26.00	24.00	21.00	--
3.15A	117-5144	30.00	26.00	24.00	21.00	--
4A	117-5145	30.00	26.00	24.00	21.00	--
5A	117-5146	30.00	26.00	24.00	21.00	--
6.3A	117-5147	30.00	26.00	24.00	21.00	--
8A	117-5148	30.00	26.00	24.00	21.00	--
10A	117-5149	30.00	26.00	24.00	21.00	--
12.5A	117-5150	28.00	26.00	23.00	22.00	--
16A	117-5151	28.00	26.00	23.00	22.00	--
20A	117-5152	52.00	46.00	42.00	40.00	--
25A	117-5153	64.00	58.00	53.00	47.00	--
32A	117-5155	92.00	78.00	71.00	64.00	--

**Antisurge (T) Glass**  
MCF02G Series



- CSA Approved (up to 6.5A)

Voltage Rating 250V to >6.25A = 32V  
Breaking capacity 125mA to 500mA 35A @ 250V  
750mA to 3A 100A @ 250V  
4A to 6.25A 200A @ 250V  
8A to 10A 300A @ 32V

Mfrs. List No. MCF02G + Rating

204489

Rating	Order Code	Price Each			
		10+	100+	500+	1K+
125mA	119-0642	93.00	84.00	76.00	58.00
500mA	119-0643	18.00	16.00	14.00	12.00
1A	119-0644	18.00	16.00	14.00	12.00
2A	119-0645	18.00	16.00	14.00	12.00
3A	119-0646	18.00	16.00	14.00	12.00
4A	119-0648	18.00	16.00	14.00	11.00
5A	119-0649	18.00	16.00	14.00	11.00
6.25A	119-0650	18.00	16.00	14.00	11.00
8A	119-0651	18.00	16.00	14.00	11.00
10A	119-0652	18.00	17.00	16.00	15.00

Fuses, Circuit Breakers & Consumer Units

19

Compliant Non-compliant Limited stock - RoHS replacement available

RoHS