

Building & Maintenance Tapes — continued

Polycloth Laminate



- Laminated polythene cloth tape
- Very aggressive pressure-sensitive adhesive
- Ideal for sealing and bundling



adh60

50 Metre Reel

Width	Mftrs List.No.	Order Code	1+	6+	12+	24+
Black	AT169	705-4970				
White	AT169	705-4981				
Silver	AT169	705-4993				

Polycloth Duct Tape



- Thermosetting polycloth duct tape
- Polythene coated fabric
- Temperature resistant, pressure sensitive adhesive
- Extremely flexible
- Operating temperature -50°C to 110°C




Applications: Joint sealing on metal or plastic ducting, suitable for hot air duct sealing

adh57

50 Metre Reel

Width	Mftrs List.No.	Order Code	1+	6+	12+	24+
50mm	AT163	705-2698				

Aluminium Foil Tape



- 30 micron aluminium foil
 - Acrylic pressure sensitive adhesive
 - Excellent shear strength at high temperatures
- Tape Thickness 0.07mm
 Application temperature 0°C to 40°C (Dry surface)
 Operating temperature -20°C to +110°C


Th = 0.07mm, W = 50mm, L = 45 Metres

H149X

45 Metre Reel

Order Code	1+	10+	50+	100+
627-434				

Closure Plate Tape



- Polythene coated fabric tape
- Heat and cold resisting adhesive
- Flexible
- Conforms to British Gas specification PRS10

Application temperature 5°C to 45°C
 Operating temperature -50°C to +110°C


Th = 0.3mm, Width = 50mm

H148X

Price Per Reel

Length	Order Code	1+	10+	50+	100+
10m	627-410				
25m	627-422				

PTFE Threadseal Tape



- Pure polytetrafluoroethylene (PTFE) tape
- Clean and economical method of sealing threaded joints
- Suitable for aggressive environments eg. acids, gases, solvents, steam, water
- Natural water council approved
- Conforms to BS4375



W = 12, L = 12 Metres

Operating temperature -190°C to +250°C

H252

12 Metre Reel
 Order Code
 711-4898

Price Per Reel	1+	10+	100+	500+	1000+	1500+

Double Sided Adhesive Tapes

Thin Film, 50 Metre Reel

Double Sided Rubber Based Adhesive



- Lightweight thin translucent flexible polypropylene film
- High tack rubber based adhesive
- Adhesive gives an immediate bond suitable for a variety of smooth, flexible materials

Operating temperature -20°C to +100°C

Th = 0.08, W = 25.0, L = 50 metres

H78X

50 Metre Reel
 Order Code
 106-869

Price Per Reel	1+	12+	24+	48+	144+

Polypropylene Carrier – 51968

Double Sided Acrylic Adhesive



- White polypropylene film with paper release liner
- Very strong permanent bond even on low energy plastic surfaces
- Suitable for use on rough surfaces
- Ideal for mounting mouldings and decorative parts

Operating temp. range -40°C to +70°C (long term)
 120°C (Short term)

Thickness 0.3mm
 Adhesion 65N/25mm

H311

50 Metre Reel

Width	Order Code	1+	12+	24+	48+	144+
12	.306-9412					
19	.306-9424					
25	.306-9436					
38	.306-9448					

Polyester Carrier – 4965

Double Sided Acrylic Adhesive



- Transparent polyester film with red polypropylene release liner
- High adhesion for permanent fixings
- Secure bond at elevated temperature
- Resistant to plasticisers
- Ideal for mounting ABS/Rubber/EPDM profiles

Operating temp. range -40°C to +80°C (long term)
 +200°C (short term)

Thickness 0.21mm
 Adhesion 25N/25mm

H278

50 Metre Reel

Width	Order Code	1+	12+	24+	48+	144+
12	306-9370					
19	306-9382					
25	306-9394					
38	306-9400					

PVC Carrier – 4970

Double Sided Acrylic Adhesive



- White PVC carrier with paper release liner
- High level of adhesion
- Resistant to plasticisers
- Suitable for rough surfaces
- Ideal for mounting heavy decorative items, plastic and wooden trim

Operating temp. range -40°C to +60°C (long term)
 70°C (Short term)

Thickness 0.23mm
 Adhesion 29N/25mm