

Multicore Cable — Continued

Sub-Miniature – Screened 7/0.1mm (0.055mm²)

Voltage rating 250V (RMS) Maximum current per core **0.25A**
 Conductor area 0.055mm² per core Max. operating temperature 70°C
 Sheath colour Grey

No. of Cores	Nom. Dia. (mm)	Length (m)	Order Code	Price Per Coil/Reel		
				1+	5+	10+
4	2.9	25	.711-342			
		100	.711-354			
6	3.3	25	.711-366			
		100	.711-378			
9	4.0	25	.711-380			
		100	.711-391			
15	5.0	25	.711-408			
		100	.711-410			
25	6.0	25	.711-421			
		100	.711-433			
36	6.6	25	.711-445			
		100	.711-457			

Miniature – Screened 7/0.2mm (0.22mm²)

Voltage rating 440V (RMS) Maximum current per core **1A**
 Conductor area 0.22mm² per core Max. operating temperature 70°C
 Sheath colour Grey



No. of Cores	Nom. Dia. (mm)	Length (m)	Order Code	Price Each		
				1+	5+	10+
4	4.3	25	.715-440			
		100	.715-451			
8	6.1	25	.715-463			
		100	.715-475			
12	6.8	25	.715-487			
		100	.715-499			
20	8.6	25	.715-505			
		100	.715-517			
36	10.7	25	.715-529			
		100	.715-530			

Standard – Screened 16/0.2mm (0.5mm²)

Voltage rating 440V (RMS) Maximum current per core **2.5A**
 Conductor area 0.5mm² per core Max. operating temperature 70°C
 Sheath colour Grey

No. of Cores	Nom. Dia. (mm)	Reel Length	Order Code	Price Per Reel		
				1+	5+	10+
4	7.3	25m	.715-980			
		100m	.715-992			
6	8.3	25m	.716-005			
		100m	.716-017			
12	10.5	25m	.716-029			
		100m	.716-030			
18	12.0	25m	.716-042			
		100m	.716-054			

Heavy item, special delivery conditions apply

DEF STAN 61-12 Part 4 – Unscreened 7/0.1mm (0.055m²) 7-1-A Type

Voltage rating 250V (RMS) Maximum current per core **0.25A**
 Conductor area 0.055mm² per core Max. operating temperature 70°C
 Sheath colour Black

Cable Ref.	No. of Cores	Nom. Dia. (mm)	Reel Length	Order Code	Price Per Reel		
					1+	5+	10+
7-1-2A	2	2.5	25m	.711-482			
7-1-3A	3	2.6	25m	.711-500			
			100m	.711-512			
7-1-4A	4	2.8	25m	.711-524			
			100m	.711-536			
7-1-6A	6	3.3	25m	.711-548			
			100m	.711-550			
7-1-9A	9	3.9	25m	.711-561			
			100m	.711-573			
7-1-12A	12	4.1	25m	.711-585			
			100m	.711-597			
7-1-15A	15	4.5	25m	.711-603			
			100m	.711-615			
7-1-18A	18	4.7	25m	.711-627			
			100m	.711-639			
7-1-25A	25	5.8	25m	.711-640			
			100m	.711-652			
7-1-36A	36	6.4	25m	.711-664			
			100m	.711-676			
7-1-50A	50	7.3	25m	.711-688			

DEF STAN 61-12 Part 4 – Unscreened 7/0.2mm (0.22m²) 7-2-A Type

Voltage rating 440V (RMS) Max. current per core **1A**
 Conductor area 0.22mm² per core Max. operating temperature 70°C
 Sheath colour Black

Cable Ref.	No. of Cores	Nom. Dia. (mm)	Reel Length	Order Code	Price Per Reel		
					1+	5+	10+
7-2-2A	2	3.4	25m	.714-963			
			100m	.714-975			
7-2-3A	3	3.5	25m	.714-987			
			100m	.714-999			
7-2-4A	4	3.9	25m	.715-001			
			100m	.715-013			
7-2-6A	6	4.6	25m	.715-025			
			100m	.715-037			
7-2-8A	8	5.5	25m	.715-049			
			100m	.715-050			
7-2-12A	12	6.1	25m	.715-062			
			100m	.715-074			
7-2-18A	18	7.4	25m	.715-086			
			100m	.715-098			
7-2-20A	20	7.8	25m	.715-104			
			100m	.715-116			
7-2-25A	25	8.7	25m	.715-128			
			100m	.715-130			
7-2-36A	36	9.8	25m	.715-141			
			100m	.715-153			

DEF STAN 61-12 Part 4 – Screened 7/0.1mm (0.055m²) 7-1-C Type

Voltage rating 250V (RMS) Maximum current per core **0.25A**
 Conductor area 0.055mm² per core Max. operating temperature 70°C
 Sheath colour Black

Cable Ref.	No. of Cores	Nom. Dia. (mm)	Reel Length	Order Code	Price Per Reel		
					1+	5+	10+
7-1-2C	2	3.0	25m	.714-768			
			100m	.714-770			
7-1-3C	3	3.2	25m	.714-781			
			100m	.714-793			
7-1-4C	4	3.4	25m	.714-800			
			100m	.714-811			
7-1-6C	6	3.8	25m	.714-823			
			100m	.714-835			
7-1-9C	9	4.4	25m	.714-847			
			100m	.714-859			
7-1-12C	12	4.6	25m	.714-860			
			100m	.714-872			
7-1-15C	15	5.4	25m	.714-884			
			100m	.714-896			
7-1-18C	18	5.8	100m	.714-914†			
			25m	.714-926			
7-1-25C	25	6.6	100m	.714-938			
			25m	.714-940			
7-1-36C	36	7.2	25m	.714-951†			
			100m	.714-951†			

†Available until stocks are exhausted

DEF STAN 61-12 Part 4 – Screened 7/0.2mm² (0.22mm²) 7-2-C Type

Voltage rating 440V (RMS) Maximum current per core **1A**
 Conductor area 0.22mm² per core Max. operating temperature 70°C
 Sheath colour Black

Cable Ref.	No. of Cores	Nom. Dia. (mm)	Reel Length	Order Code	Price Per Reel		
					1+	5+	10+
7-2-2C	2	3.8	25m	.715-189			
			100m	.715-190			
7-2-3C	3	4.0	25m	.715-207			
			100m	.715-219			
7-2-4C	4	4.3	25m	.715-220			
			100m	.715-232			
7-2-6C	6	5.5	25m	.715-244			
			100m	.715-256			
7-2-8C	8	6.1	25m	.715-268			
			100m	.715-270			
7-2-10C	10	6.6	25m	.715-281			
			100m	.715-293			
7-2-12C	12	6.8	25m	.715-300			
			100m	.715-311			
7-2-15C	15	7.7	25m	.715-323			
			100m	.715-335			
7-2-18C	18	8.1	25m	.715-347			
			100m	.715-359			
7-2-20C	20	8.6	25m	.715-360			
			100m	.715-372			
7-2-25C	25	9.5	25m	.715-384			
			100m	.715-396			
7-2-36C	36	10.7	25m	.715-402			
			100m	.715-414			