


Ribbon Cable Clamps — Self-Adhesive



- Flat ribbon cable clamps in Grey PVC, self-adhesive backed



346

100 Per Pack

Dimensions			Order Code	Price Each				
W	D	H		1+	5+	10+	25+	50+
15	25	10	.581-975					
20	25	10	.581-987					
25	25	10	.581-999					
28	25	10	.582-001					

Ribbon Cable Clamps — Self-Adhesive



- One-piece releasable ribbon cable clamps in Natural Nylon 66
- Self-adhesive foam pad
- Flame retardant to UL94V-2


No. of Ribbon Conductors	Max. Cable Width	Overall Length	Overall Width	Overall Height	Order Code
25	32.0	45.8	19.4	18.0	303-0520
30	39.5	53.3	19.4	18.0	303-0532
50	63.5	76.2	19.4	18.0	303-0544

612

Order Multiple=10

No. of Ribbon Conductors	Max. Cable Width	Order Code	Price Each				
			10+	50+	100+	500+	1000+
25	32.0	303-0520					
30	39.5	303-0532					
50	63.5	303-0544					

Ribbon Cable Clamps — Self-Adhesive



- A range of moulded nylon clamps for ribbon cable up to 64 way
- Unique method of clamping allows several layers of cable to be clamped
- 6BA countersunk screw fixing

No. of Ribbon Conductors	Length	Maximum Cable Width	Height	Fixing Centres	Order Code
26	51	33	17	42	145-426
40	76	54	17	67	145-427
64	107	85	17	98	145-428

104

Order Multiple=5

No. of Ribbon Conductors	Order Code	Price Each				
		5+	25+	100+	250+	500+
26	.145-426					
40	.145-427					
64	.145-428					

Flat Cable Clamps



- A two-piece nylon cable clamp for bundling flat cable, which may be released and reused. Available in two versions, screw mounting or adhesive mounting

Note: Full strength on adhesive mounting types achieved after 24 hours.

No. of Ribbon Conductors	Cable Capacity Width	Height	Order Codes	
			Screw Mounting	Adhesive Mounting
20	25.4	12.7	302-843	302-879
40	50.8	25.4	302-855	302-880
60	76.2	25.4	302-867	302-892

105

Order Multiple=5

No. of Ribbon Conductors	Mfrs. List No.	Order Code	Price Each		
			5+	50+	100+
Screw Mounting					
20	FCC-1	302-843			
40	FCC-2	302-855			
60	FCC-3	302-867			
Adhesive Mounting					
20	FCC-1A	302-879			
40	FCC-2A	302-880			
60	FCC-3A	302-892			

P-Clips, Nylon



- UL approved P-clips manufactured in UL94V-2 flame retardant Natural Nylon 66
- Suitable for fixing cables, looms etc up to 25.4mm diameter.

Operating temperature -40°C to +85°C
Fixing hole diameter 4.6

307

100 Per Pack

Nominal Bundle Dia.	Clip Width	Order Code	Price Per Pack			
			1+	5+	10+	50+
3.2	9.6	434-097				
4.8	9.6	434-103				
6.35	10.0	434-115				
7.9	10.0	434-127				
9.5	12.0	434-139				
12.7	12.0	434-140				
15.8	12.0	434-152				
19.4	12.0	434-164				
25.4	12.0	434-176				

P-Clips, Nylon



A range of UL approved Natural nylon P-clips for the positive fixing of cables, looms and pipes up to 16mm diameter.

Operating temperature -20°C to +85°C
Nominal fixing hole diameter 5.0
Clip width 9.5
12.7 (146-179)

118

Pack Qty.	Nom. Cable Dia.	Order Code	Price Per Pack				
			1+	3+	5+	10+	25+
100	3.0	146-173					
100	6.0	146-174					
100	7.5	146-175					
100	9.0	146-176					
100	11.0	146-177					
100	12.5	146-178					
50	16.0	146-179					

P-Clips, Nylon Black



- A range of Black flexible Nylon 6 P-Clips
- Suitable for fixing cables and pipes up to 25.4mm diameter

Operating temperature -50°C to +80°C

Mfrs. List No. NX0 = 330-8625, NX1 = 330-8637, NX2 = 330-8649, NX2A = 330-8650, NX3 = 330-8662, NX4 = 330-8674, NX5 = 330-8686, NX6 = 330-8698, NX8 = 330-8704, NX11 = 330-8716, NX14 = 330-8728

CAB669

100 Per Pack

Nominal Bundle Dia.	Clip Width	Fixing Hole Dia.	Order Code	Price Per Pack				
				1+	5+	10+	25+	50+
3.4	6.2	3.5	330-8625					
5.0	6.2	3.5	330-8637					
6.4	6.2	3.5	330-8649					
7.6	9.4	3.9	330-8650					
8.0	9.4	3.9	330-8662					
10.0	9.4	3.9	330-8674					
12.0	9.4	3.9	330-8686					
13.6	9.4	3.9	330-8698					
14.3-15.8	12.6	4.0	330-8704					
17.4-20.0	12.6	4.0	330-8716					
22.2-25.4	16.0	4.3	330-8728					

Continued