

## Insulated Crimp Terminals – Metric — Continued

### Butt Splice & Female Push-On (Miniature Conductor)



CS385X

100 Per Pack	Order Code	1+	5+	10+	50+	100+
Butt Splice						
Yellow - 15 Amp	658-327					
Female Push-On						
Tab Size						
2.8 0.5	658-339					
2.8 0.8	658-340					

### Ratchet Crimp Tool (Miniature Conductor)



Ratchet tool, fully calibrated for miniature yellow insulated terminals.

CS386X

Mftrs. List No.	Order Code	1+	5+	10+	25+
DHCR10	658-352				

### 'Plasti Grip' Metric Insulated Terminals



- Funnel entry wire barrels allow easier wire insertion
- Inner serrations improve overall tensile strength for a reliable connection
- Crimp locating ribs are moulded into the insulation for perfect crimp tool positioning
- Vinyl sleeve for improved wire protection

Temperature range	-25°C to 90°C	PVC
	-55°C to 105°C	Nylon
Terminal	Tin plated copper	
Insulation	Spades, ring, blades, butt splices, wire pins	PVC
	Receptacles (including shrouded)	Nylon 6.6

Wire Details	Insulation Colour		
	Red	Blue	Yellow
Wire size in mm <sup>2</sup>	0.25—1.65	1.04—2.63	2.63—6.64
Single Stranded Wire Size Dia in mm	0.57—1.44	1.14—1.82	1.82—2.89
Equivalent A.W.G.	22—18	16—14	12—10
Equivalent S.W.G.	29—17	17—13	11—6
	Suitable Metric Cables		
Stranded	19/0.15	19/0.3	19/0.45
	13/0.2	7/0.5	44/0.3
	16/0.2	21/0.3	7/0.85
	19/0.2	30/0.25	56/0.3
	14/0.25	19/0.335	65/0.3
	24/0.2	63/0.2	37/0.4
	19/0.25	28/0.3	159/0.2
	32/0.2	35/0.3	84/0.3
	40/0.2	51/0.25	7/1.04
	19/0.3		
Single	1/0.9	1/1.38	1/2.25
	1/1.13	1/1.78	

AWG = American Wire Gauge SWG = Standard Wire Gauge  
Conductor Make up Metric cables i.e. 19/0.15 = 19 Strands of 0.15mm diameter.

CS387

### Spade – 'Plasti Grip'



CS388

### Order Multiple=100

Stud Size	Mftrs. List No.	Order Code	100+	500+	3000+
<b>Red</b>					
M3/3.5	342117	. 586-961			
M4	342118	. 586-973			
M5	342119	. 586-985			
<b>Blue</b>					
M3/3.5	342157	. 586-997			
M4	342158	. 587-000			
M5	342159	. 587-011			
M6	130568	308-5296			
<b>Yellow</b>					
M3/3.5	342197	. 587-023			
M4	342198	. 587-035			
M5	342199	. 587-047			
M6	165019	308-5302			

### Ring – 'Plasti Grip'



CS389

### Order Multiple=100

Stud Size	Mftrs. List No.	Order Code	100+	500+	3000+
<b>Red</b>					
M2.5	342101-1	. 587-059			
M3/3.5	342102-1	. 587-060			
M4	342103-1	. 587-072			
M5	342104-1	. 587-084			
M6	342105-1	308-5272			
M8	342106-1	. 587-096			
<b>Blue</b>					
M2.5	342141-1	. 587-102			
M3/3.5	342142-1	. 587-114			
M4	342143-1	. 587-126			
M5	342144-1	. 587-138			
M6	342145-1	. 587-140			
M8	342146-1	. 587-151			
<b>Yellow</b>					
M3/3.5	342182-1	. 587-163			
M4	342183-1	. 587-175			
M5	342184-1	. 587-187			
M6	342185-1	. 587-199			
M8	342186-1	. 587-205			
M10	160300	308-5284			

### Blade – 'Plasti Grip'



CS390

### Order Multiple=100

Blade Size	Mftrs. List No.	Order Code	100+	500+	3000+
<b>Red</b>					
0.25 inch	140896-2	. 587-217			
<b>Blue</b>					
0.25 inch	140971-2	. 587-229			
<b>Yellow</b>					
0.25 inch	141085-2	. 587-230			

### Receptacle – 'Plasti Grip'



CS391