


Order Code	Price Each			
	1+	5+	10+	25+
540-500				
540-511				

### In-line IP65 Sealed



A heavy duty 16A in-line RCD unit providing double pole protection, for use in wet or dirty environments where rough handling is expected. Sealed to IP65, the unit is supplied with 0.3m of 1.5mm<sup>2</sup> cable on the input and 0.6m of 1.5mm<sup>2</sup> cable on the output. Plugs, sockets or connectors of the same IP rating must be used to maintain IP65 integrity.



For IP67 in-line connector see Order Code 179-555, page 388

Voltage rating	240V ac	Trip current	30mA
Maximum load	16A	Operating temperature	-5°C to +40°C
Trip time	40ms	Mftrs. List No.	J62

FUS200X

Order Code	Price Each		
	1+	5+	10+
287-155			

### International Mains Plugs

#### France and Belgium 2 Pin + Earth Unfused



- Rewireable straight or side entry
- Suitable for Class 1 appliances
- Flame retardant to IEC695-2-1 and NF-USE approval

Pitch = 19

Current rating	16A @ 250V ac	Max cable dia	11.0
Housing	Polypropylene	Box qty.	20, 200
Contacts	Brass		

Mftrs. List No. 50215 = 299-881, 50235 = 299-893, 50216 = 299-900, 50239 = 299-911

CM261X

Colour	Order Code	Price Each			
		1+	20+	100+	200+
<b>Straight Entry</b>					
White	299-881				
Black	299-893				
<b>Side Entry</b>					
White	299-900				
Black	299-911				

#### Europe, 'Schuko' Plug Unfused



- Rewireable 'Schuko' with dual earthing system
- Extensive use across the majority of Europe
- Complies with DIN49441 and CEE 7 sheet VII, VDE approved

Current rating	16A @ 250V ac	Terminations	3 1.5mm <sup>2</sup> screw
Housing	Polyamide, UL94V-0	Box qty	50,400
Contacts	Brass, nickel plated		

Mftrs. List No. 2029WS = 285-456, 2029SW = 285-468

FOR SCHUKO MAINS LEAD 210-699, SEE PAGE 30

CM278

Colour	Order Code	Price Each		
		1+	50+	200+
White	285-456			
Black	285-468			

#### Italy, 2 Pin + Earth Plug Unfused



- Rewireable straight, one piece moulding
- Approved, IMO
- Integral cable clamp
- Meets the CE123-16 standard

Current rating 10A @ 220V

Mftrs. List No. 51530 Black = 535-242, 51532 White = 535-254

CM313X

Colour	Order Code	Price Each			
		1+	20+	100+	200+
White	535-254				

#### Denmark, 2 Pin + Earth Plug Unfused



- Rewireable, white moulded cover houses terminations
- Approval DEMKO

Current rating 10A @ 250V ac

CM308X

Order Code	Price Each			
	1+	20+	100+	200+
535-278				

#### America, 2 Pin



Socket panel cut-out = 20.5 11 Fixing centres = 27 2.5 dia. Pin dimensions L = 18, W = 6.3, Th = 1.4 Pitch = 12.7

Contact rating	Plug 15A @ 150V ac	Body	Black bakelite
	Socket 15A @ 125V ac	Contacts	Brass

**Warning:** Only suitable for use with correct mating socket. Equipment Safety Regulations 1975.

CM226X

	Order Code	Price Each				
		1+	25+	50+	100+	250+
Free plug	240-540					
Panel socket	240-552					

### Adaptors

#### 2 and 3 Way

MARBO



2 way  
H = 50, W = 50,  
D = 50 (excl. pins)

3 way  
H = 58, W = 51,  
D = 55.5 (excl. pins)

- Unfused 2 way adaptor
- 3 way fitted with ASTA approved 13A fuse
- Fuse holder facilitates fuse changing without dismantling adaptor
- Spring shuttered pin apertures. Approved to BS5733:1979

Housing White urea formaldehyde Box qty. 10

Mftrs. List No. 7954 = 108-085, 7957 = 108-086

CM9X

No. of Ways	Order Code	Price Each				
		1+	5+	10+	25+	50+
2	108-085					
3	108-086					

continued

## Total Customer Care

Our aim is to ensure you are 100% satisfied. If you ever have a query with your order, call us on (65) 788 0200