



Ferric Chloride (FCC)

- Sealed packet of ferric chloride hexahydrate for etching copper clad boards
- Dissolve the packet (250g) in warm de-mineralised water
- Makes up to 500ml
- Solution may be heated to lengthen life

Photoresist Developer (PDN)

- An alkaline, aqueous developer for positive photoresists particularly PRP200
- Dilute 1 to 4 with de-mineralised water and use at above 20°C

Photoresist (PRP)

- Fast drying positive photoresist aerosol
- Use for one to one reproduction of circuits etc., on metal from transparent positive masters
- Intended for PCB prototyping but may be used for areas of technical or artistic reproduction

CHM322

	Size	Order Code	1+	5+	10+	20+	50+
Ferric Chloride	250g	130-539					
Developer	250ml	130-540					
Photoresist	200ml	130-552					

Conformal Coating Removal Pen



Conformal Coating Removal Pen

- Removes most types of coatings in seconds
- Spot clean tight tolerance areas on circuit boards
- Marker dispenser provides controlled and exact application
- Evaporates quickly
- Provides low surface tension for superior wetting
- Conveniently sized repair/prototype dispenser
- Multilingual instructions and regulatory information



CHM326

Mfrs. List No.	Size	Order Code	1+	6+	12+	24+	72+
CW3500	9g	130-667					

Flux Removal/Dispensing



Dispensing Pens

Chisel tip marker provides exact delivery of flux to surface
Easily removes with appropriate Flux Remover Pen or Flux-Off flux remover

No clean Flux Dispensing Pen

- Applies a patented non-corrosive, halide free, organic no-clean flux
- Flux meets Bellcore TR-NWT-000078 and IPC SF-818 for Surface Insulation Resistance

Rosin Flux Dispensing Pen

- Applies a non-corrosive Type R flux
- Flux meets MIL-14256 E+F Type R and RMA

Remover Pen

Completely removes flux in seconds
Spot cleans tight tolerance areas on circuit boards
Marker dispenser provides controlled and exact application
Dries fast

CHM329

Description	Mfrs. List No.	Size/ Qty	Order Code	1+	6+	12+	24+	72+
Dispensing Pens								
No clean Flux	CW8100	9g	130-692					
Rosin Flux	CW8200	9g	130-709					
Remover Pen								
No Clean Flux	CW9100	9g	128-727					

Lubricants

Speciality Lubricants



HTG – High Temperature Grease

- Temperature range -20°C to +200°C
- Does not harden at high temperature
- Low evaporation weight loss
- Fortified with anti-wear and anti-oxidant additives
- Water resistant

MPG – Multipurpose Grease

- Wide temperature range
- Good lubricating and thermal properties
- Safe on most thermoplastics
- Non-melting

SPG – Special Plastics Grease

- Superb plastic compatibility
- Excellent mechanical lubricant
- Will not adversely affect electrical performance
- Use for plastic gears, cogs, slides etc.

EPE – Permargard 40

- De-watering fluid
- Loosens seized metal parts
- Protects against rust and corrosion
- 100% Ozone Friendly

Warning: Flammable contents, do not use on live equipment or near any source of ignition, use in a well ventilated area.

- Please check with Sales Office for availability

MPO – Multipurpose Oil

- Light, general purpose oil for all mechanical lubrication applications
- Reduces wear and friction
- Prevents rust and corrosion
- Excellent lubrication characteristics
- Tenacious film

CHM30X

Mfrs. List No.	Order Code	1+	10+	20+	50+
50ml Tube HTG50T	891-290				
50ml Tube MPG50T	317-846				
35ml Syringe SPG35SL	725-626				
		1+	12+	36+	144+
200ml Aerosol EPE200H	298-244				
400ml Aerosol EPE400H	298-256				
		1+	5+	20+	100+
250ml Tin MPO250ML	317-834				

Silicone Oil – OSL400



- High quality silicone spray
- Multi-purpose lubricant with good adhesion
- Excellent water repellency
- Good electrical insulating compound and sealant
- 100% Ozone Friendly



Warning: Product contains flammable solvent, do not use on live equipment or near any source of ignition, use in a well ventilated area.

- Please check with Sales Office for availability

CHM348

Mfrs. List No.	Order Code	1+	6+	12+
400ml Aerosol OSL400	302-6875			

Continued