

Floor Paint

Single-Pack Floor Paint

JOHNSTONE'S



- Mid-sheen, quick-drying polyurethane finish
- Single pack
- Ideal for use on stone & concrete
- Brush, roller or spray application
- Dust retardant
- Resistant to mild chemical attack
- Suitable for surfaces subjected to repeated/regular washing
- Conforms to **BS4310**

Touch Dry 5 hours
 Dry Film Thickness not less than 43 microns
 Coverage 60 m² typically

pnt45

5 litres Colour	Mftrs. List No.	Order Code	Price Each					
			1+	5+	10+	25+	50+	100+
Red	DJCAR5	714-5070						
Green	DJSHE5	714-5081						
Dark Grey	DJDAG5	714-5093						
Light Grey	DJPRG5	714-5100						
Black	DJBLA5	714-5111						
Whit	DJBRI5	714-5123						

750ml Aerosol

Colour	Order Code	Price Each					
		1+	6+	12+	18+	30+	48+
White	721-2902						
Yellow	721-2914						
Red	721-2926						
Green	721-2938						

Layout Blue Ink



- Allows clear, sharp definitions
- Will not chip or flake
- Resists wash off
- Easy to apply & remove

ROCOL

pnt4

400ml Mftrs. List No.	Order Code	Price Each			
		1+	12+	36+	72+
57034	707-2028				

Concrete Repair Motar



- Fast setting, open to light traffic within 6 hours
- Durable hardwearing epoxy resin with excellent abrasion resistance
- Chemically resistant to most industrial chemicals
- Non-shrinking, reduces potential failure
- Permanent repair giving high compressive strength after full cure (80N/mm²)
- Multi-purpose as it can be used internally and externally, on both old and new concrete

Patchfast is an easy to apply 3-component kit which can be used with confidence by maintenance staff. Bonds and sets down to a feather edge which gives a hygienic impervious finish that is easily cleaned. Patchfast can be used in aggressive environments such as chemical process areas, steelworks, food and drink manufacturing areas, dairies, breweries, plating shops, abattoirs, engineering shops, production lines, workshop and warehousing areas.

Coverage rate: 1.14m² per 12kg @ 5mm deep

Material Properties

Specific Gravity	2.1
Pot Life	30 minutes
Initial Hardness	6 hours
Full Cure	7 days
Below 20°C these times will be increased	

Physical Properties

Compressive Strgth	80N/mm ²
Flexural Strength	30N/mm ²
Tensile Strength	12N/mm ²
Bond to Steel (Blasted to S.A 2.5)	12N/mm ²
Bond to Concrete	Concrete Fails

PNT58

12kg Tub	Order Code	Price Each					
		1+	4+	8+	12+	20+	30+
	721-3323						

Road Paint

Marking Paint.

plasti-kote




- One coat coverage
- Tight spray pattern, minimises over-spray
- Not affected or washed-away by poor weather conditions
- Non-clogging nozzle
- Formulated for heavy-traffic areas
- Suitable for concrete, grass, asphalt and gravel
- Typically applied to car parks, warehouses, loading areas and factory floors
- Touch dry in 2 to 5 minutes

PNT57

Strippers and Thinners

Paint & Varnish Remover

Leyland



- Fast-acting
- Non-drip
- Water-washable
- Does not discolour or change the substrate
- Softens paints & varnishes

pnt53

500ml	Mftrs. List No.	Order Code	Price Each		
			1+	12+	24+
	S81599	720-6999			
2.5 litre	S81600	720-7001			

Corrosion Control

Heavy-Duty Rust Shield

ROCOL



- Effective outdoor corrosion protection
- Thin flexible film – will not crack or chip
- Dry film – does not attract dirt & dust
- Easily handled – resists finger-print corrosion

The mild dewatering action means that the parts do not need to be completely dry before application. Use for the protection of metal parts stored for extended periods out of doors, in transit or indoors under severe corrosion conditions. Ideal for the protection of machines and equipment shipped overseas. Protective film also provides residual lubrication for assembly etc.

Colour	fugitive red dye
Film Type	hard waxy film when fully cured
Film Thickness	approx. 5 to 10 microns
Curing Time	fully cured in approx. 48 hours
Protection Period	outdoors: up to 12 months indoors: typically in excess of 3 years

pnt2

300ml aerosol	Mftrs. List No.	Order Code	Price Each			
			1+	12+	36+	72+
	69100	707-1784				