

## 20 x 5mm Fuses — continued

### Quick Blow (F) HRC Ceramic S501 Series



- Complies with IEC127: Standard Sheet I
- Approved to SEMKO (500mA to 5A)
- Available in bulk pack of 1000 fuses

Voltage rating (Vn) 250V ac  
 Breaking capacity 1500A @ Vn, Cos φ = 0.7 to 0.8

Mfrs. List No. Single: S501 + Rating  
 Bulk: BK/S501 + Rating

**Bussmann**

**Bulk Pack Available**

FUS5X

#### Order Multiple=10

Rating	Order Code	10+	100+	500+	1000+
100mA	.532-848				
250mA	.532-850				
500mA	.532-861				
630mA	.532-873				
800mA	.532-885				
1A	.532-897				
2A	.532-903				
3.15A	.532-915				
4A	.532-927				
5A	.532-939				
6.3A	.532-940				
8A	.532-952				
10A	.532-964				

#### Bulk Packs

Rating	Order Code	1+	2+	3+
100mA	348-2157			
250mA	348-2169			
500mA	348-2170			
630mA	348-2182			
800mA	348-2194			
1A	348-2200			
2A	348-2212			
3.15A	348-2224			
4A	348-2236			
5A	348-2248			
6.3A	348-2250			
8A	348-2261			
10A	348-2273			

FUS3X

#### Order Multiple=10

Rating	Order Code	10+	100+	500+	1000+
50mA	.533-051				
63mA	.533-063				
80mA	.533-075				
100mA	.533-087				
125mA	.533-099				
160mA	.533-105				
200mA	.533-117				
250mA	.533-129				
315mA	.533-130				
400mA	.533-142				
500mA	.533-154				
630mA	.533-166				
800mA	.533-178				
1A	.533-180				
1.25A	.533-191				
1.6A	.533-208				
2A	.533-210				
2.5A	.533-221				
3.15A	.533-233				
5A	.533-245				
6.3A	.533-257				
8A	.533-269				
10A	.533-270				

#### Bulk Packs

Rating	Order Code	1+	2+	3+
50mA	348-1712			
63mA	348-1724			
80mA	348-1736			
100mA	348-1748			
125mA	348-1750			
160mA	348-1761			
200mA	348-1773			
250mA	348-1785			
315mA	348-1797			
400mA	348-1803			
500mA	348-1815			
630mA	348-1827			
800mA	348-1839			
1A	348-1840			
1.25A	348-1852			
1.6A	348-1864			
2A	348-1876			
2.5A	348-1888			
3.15A	348-1890			
5A	348-1906			
6.3A	348-1918			
8A	348-1920			
10A	348-1931			

#### Price Per Pack

### Quick Blow (F) Glass 19193 Series



- Complies with BS4265, IEC127 Sheet II
- Approved to BEAB, VDE, SEMKO
- UL recognised

Voltage rating (Vn) 250V ac  
 Breaking capacity 35A @ Vn

Mfrs. List No. 19193 + Rating

**WICKMANN**

**Littelfuse**

### Quick Blow (F) Glass 217 Series



- Complies with IEC127, BS4265, Standard Sheet II
- Approved to SEMKO and VDE

Voltage rating (Vn) 250V ac  
 Breaking capacity 50mA to 3.15A 35A @ Vn 4A to 6.3A 10 In @ Vn

Mfrs. List No. 217 + Rating

FUS246X

#### Order Multiple=10

Rating	Order Code	10+	100+	500+	1000+
315mA	533-336†				
3.15A	533-439†				


†Available until stocks are exhausted

FUS7X

#### Order Multiple=10

Rating	Order Code	10+	100+	500+	1000+
50mA	533-464				
100mA	533-476				
250mA	533-488				
500mA	533-490				
1A	533-506				
2A	533-518				
3.15A	533-520				
4A	533-531				
5A	533-543				
6.3A	533-555				

### Quick Blow (T) Glass S500 Series\*



- Complies with IEC127, BS4265, Standard Sheet II
- Approved to SEMKO, BSI, VDE, IMQ
- UL recognised\* except 8A and 10A which are not approved
- Available in bulk pack of 1000 fuses

Voltage rating (Vn) 250V ac  
 Breaking capacity 35A @ Vn

Mfrs. List No.  
 Single: 50mA to 6.3A S500 + Rating,  
 8A, 10A\* TDC641 + Rating  
 Bulk: 50mA to 6.3A BK/S500 + Rating,  
 8A, 10A BK/TDC641 + Rating

**Bussmann**

**Bulk Pack Available**

### Medium Blow (T) Glass TDC 210 Series



- Conforms to DIN 41.75 T2

Voltage rating 250V ac  
 Construction 1A - glass tube  
 1.6A and above - glass tube with extinguishing agent

Breaking capacity @ 250V 1A = 80A  
 1.6A to 6.3A = 1000A  
 8A to 10A = 300A

Mfrs. List No. 210 + Rating

FUS312