


multicomp

Best value

Order Multiple=10

Rating	Order Code	10+	50+	100+	250+	500+	1000+
1A	926-760						
1.6A	926-772						
2A	926-784						
2.5A	926-796						
3.15A	926-802						
4A	926-814						
5A	926-826						
6.3A	926-838						
8A	926-863						
10A	926-840						

Antisurge (T) HRC Ceramic S505 Series



- Complies with IEC127, Standard Sheet V
- Approved to VDE (2A to 5A), SEMKO (1.6A to 4A)
- Available in bulk pack of 1000 fuses

Voltage rating (Vn) 250V ac
Breaking capacity 1500A @ Vn

Mfrs List No. Single: S505 + Rating
Bulk: BK/S505 + Rating

Bussmann

Bulk Pack Available

FUS8

Order Multiple=10

Rating	Order Code	10+	100+	500+	1000+
500mA	.533-683				
800mA	.533-701				
1A	.533-713				
1.25A	.533-725				
1.6A	.533-737				
2A	.533-749				
2.5A	.533-750				
3.15A	.533-762				
4A	.533-774				
5A	.533-786				
6.3A	.533-798				
8A	.533-804				
10A	.533-816				

Bulk Packs

Rating	Order Code	1+	2+	3+
500mA	348-2285			
800mA	348-2297			
1A	348-2303			
1.25A	348-2315			
1.6A	348-2327			
2A	348-2339			
2.5A	348-2340			
3.15A	348-2352			
4A	348-2364			
5A	348-2376			
6.3A	348-2388			
8A	348-2390			
10A	348-2406			

Antisurge (T) HRC Ceramic MCF03C Series



- Complies with IEC127, DIN41662 and BS4265
- UL recognised

Voltage Rating 250V Breaking Capacity 1500A @ 250V
Mfrs. List No. MCF03C + Rating

multicomp

Best value

FUS290

Order Multiple=10

Current Rating	Order Code	10+	100+	500+	1000+	3000+
500MA	799-051					
630MA	799-063					
800MA	799-075					
1A	799-087					
1.25A	799-099					
1.6A	799-105					
2A	799-117					
2.5A	799-129					
3.15A	799-130					
4A	799-142					
5A	799-154					
6.3A	799-166					
8A	799-178					
10A	899-306					

Antisurge (T) Glass MCF06G Series



- Complies with IEC127, DIN41662 and BS4265
- UL recognised

Voltage Rating 250V
Breaking Capacity 32MA to 3.15A, 35A @ 250V, 4A to 6.3A 10 x IN @ 250V

Mfrs. List No. MCF06G + rating

FUS291

Order Multiple=10

Current Rating	Order Code	10+	100+	500+	1000+	3000+
32mA	898-776					
40mA	898-788					
50mA	898-790					
63mA	898-806					
80mA	898-818					
100mA	898-820					
125mA	898-831					
160mA	898-843					
200mA	898-855					
250mA	898-867					
315mA	898-879					
400mA	898-880					
500mA	898-892					
630mA	898-909					
800mA	898-910					
1A	898-922					
1.25A	898-934					
1.6A	899-331					
2A	898-946					
2.5A	898-958					
3.15A	898-960					
4A	898-971					
5A	898-983					
6.3A	898-995					
10A	899-343					

Antisurge (T) Glass Enhanced Breaking Capacity



Designed to meet the new IEC 127 Part 2, sheet 6 requirements for enhanced breaking capacity glass fuses. A cost effective alternative to ceramic fuses in applications that require a fuse with a breaking capacity of 150A

Voltage rating (Vn) 250V ac Breaking capacity 150A @ 250V ac

Mfrs. List No. 219 + Rating

FUS268X

Rating	Order Code	10+	100+	500+	1000+
1A	665-060				
1.25A	665-071				
1.6A	665-083				
2A	665-095				
2.5A	665-101				
3.15A	665-113				
4A	665-125				
5A	665-137				
6.3A	665-149				

Antisurge (T) Glass - Spiral Element3 213 Series



- Complies with IEC127, BS4265, Standard Sheet III
- Approved to VDE, SEMKO and BSI

Voltage rating (Vn) 250V ac
Breaking capacity 250mA to 3.15A 35A@ Vn, 4A 40A@ Vn

Mfrs. List No. 213 + Rating

FUS245

Order Multiple=10

Rating	Order Code	10+	100+	500+	1000+
250mA	533-932				
315mA	533-944				
500mA	533-956				
1A	533-968				
1.25A	533-970				
1.6A	533-981				
2A	533-993				
2.5A	534-006				
3.15A	534-018				
4A	534-020				

Continued

24

727

Fuses Circuit Breakers & Consumer Units