

31.75 x 6.35mm Fuses (1 1/4" x 1/4"), Size '0'

Quick Blow (F) Ceramic MCF07C Series



- Manufactured to meet UL and CSA time/current characteristics
- UL listed and CSA approved up to 15A

multicomp



Voltage rating 250V ac
 Breaking capacity @ 250V ac
 Upto 500mA = 35A 750mA to 3A = 100A
 4A to 7A = 200A 8A to 15A = 750A
 20A = 1000A

Mftrs. List No. MCF07C + Rating

FUS14

Order Multiple=10		Price Each				
Rating	Order Code	10+	100+	500+	1K+	3K+
125mA	975-461					
250mA	975-473					
375mA	975-485					
500mA	975-497					
750mA	975-503					
1A	975-515					
2A	975-527					
3A	975-539					
4A	975-540					
5A	975-552					
6A	975-564					
7A	975-576					
8A	975-588					
10A	975-590					
12A	975-606					
15A	975-618					
20A	975-620					

Quick Blow (F) HRC Ceramic



UL Recognised
(up to 6.3A)

Voltage rating (Vn) 500Vac
 Breaking capacity 1500A @ Vn
 Mftrs. List No. 70-065-63+ rating



FUS16X

Order Multiple=10		Price Each			
Rating	Order Code	10+	100+	500+	1000+
500mA	534-705				
1A	534-717				
2A	534-729				
3A	534-730				
4A	760-882				
5A	534-742				
6.3A	760-894				
7A	534-754				
10A	534-766				
16A	534-778				

Quick Blow (F) Ceramic L693 Series



Complies with DEF-59-96.



Voltage rating (Vn) 440V ac, 230V dc
 Breaking capacity 33,000A @ Vn cos φ = 0.3
 Mftrs. List No. L693 + Rating

FUS17X

Order Multiple=10		Price Each 2.60			
Rating	Order Code	10+	100+	500+	1000+
250mA	534-780				
500mA	534-791				
1A	534-808				
2A	534-810				
3A	534-821				
5A	534-833				
7A	534-845				
10A	534-857				

Quick Blow (F) Glass MCF01G Series



- UL and CSA approved

multicomp



Voltage rating 250V
 Breaking capacity 250mA to 1A 35A @ 250Vac
 1.25 to 3A 100A @ 250Vac
 4A to 10A/200A @ 250Vac

Mftrs. List No. MCF01G+Rating

FUS289

Order Multiple=10

Current Rating	Order Code	10+	100+	500+	1000+	3000+
250mA	799-671					
300mA	799-683					
375mA	799-695					
500mA	799-701					
750mA	799-713					
1A	799-725					
1.25A	799-737					
1.6A	799-749					
2A	799-750					
2.5A	799-762					
3A	799-774					
4A	799-786					
5A	799-798					
6A	799-804					
8A	799-816					
10A	799-828					

Quick Blow (F) Glass TDC10 Series



Complies with BS2950A

Voltage rating (Vn): up to 2A 250V ac Breaking capacity 10 In @ Vn
 3A 150V ac Mftrs. List No. TDC10 + Rating
 5A - 12A 60V ac
 15A - 25A 32V ac

FUS18X

Order Multiple=10

Rating	Order Code	10+	100+	500+	1000+
60mA	534-869				
100mA	534-870				
150mA	534-882				
250mA	534-894				
500mA	534-900				
750mA	534-912				
1A	534-924				
1.25A	534-936				
1.5A	534-948				
2A	534-950				
2.5A	534-961				
3A	534-973				
5A	534-985				
7.5A	534-997				
10A	535-000				
12A	535-011				
15A	535-023				
20A	535-035				
25A	535-047				

Medium Time-Lag (M) Ceramic



Approved to UL and CSA



Voltage Rating 250(Vn)

Rating	Breaking Capacity @ Vn, cos φ = 0.7-0.8 (A)	Power Dissipation @ 1.1 I rat	Order Code
12A	750	3.4	760-857
15A	200	3.6	760-869
20A	1500	4.0	760-870

Mftrs List No. 19341 + Rating

FUS277X

Order Multiple=10

Rating	Order Code	1+	100+	500+	1000+
12A	760-857†				
15A	760-869†				
20A	760-870†				

† Available until stocks are exhausted

Antisurge (T), Ceramic 70-065-65 Series



- Approved to UL up to 16A

Voltage rating (V) 500V ac (up to 10A)
 440V ac (12.5A-25A)
 250V ac (32A)
 Breaking capacity 1500A @ V (up to 25A)
 1000A @ V (32A)
 Maximum voltage drop 800-150mV

Please note that when using 8A or over, consideration should be given to heat dissipation

Mftrs. List No. 70-065-65 + rating

FUS325