Health & Safety Farnell



Limited Life Clothing

TYPE 6

Limited splash

protection

work etc

B Kimberly-Clark

TYPE 5

Particle

protection

HS214

500+

Ideal for cleaning & maintenance tasks, working with dusts & powders, inspection

Price Each

100+

250+

50+

Fall Arrest Kits - 2 Man

all Allest Kits - 2	IVICIII	E Contraction of the second seco	INTERNA	
1		 Basic fall arrest kit for 2 operators Must be used with at lea 6m free space below anchor point 		
		Contents of Kit Harness Shock-absorbing lanyard Mobile anchor point Carrying bag	Mftrs. AB AE: AJ: AK	
Order Code 708-7731	1+ 969.84	Price Each 5+ 10+	20+	

PROTECTA 🌰 rrest kit for 2

		s absorbing lanyard anchor point	Mftrs. List No. AB101 AE522 AJ302 AK066	Qty 2 2 1 HS396	
4.	Price 5+	Each	00.		

Fall Arrest Kits - 2 Man

Order

708-7



0		JRG 10	s bsorbing lanyar m fall arrest bloc anchor point		Qty 2 1 1 2 1 HS397
		Price	Each		
Code 7792	1+	5+	10+	20+	



						101003
	Mftrs.		Price Each			
	List No.	Order Code	1+	5+	10+	
Polycoupe	701000	326-9528				J

Estev



25 Health & Safety 790

ē

Size

Μ

1

XL XXL

Collared

Individually poly-bagged CE95 0120 Type 5 and 6

Mftrs.

List No.

9861

9862

9863

9864

Fall Arrest Equipment

25 +

Protects against water-based splash & spray, dirt & low toxicity chemicals

Protective value of garment enhanced by triple-stitch overlock seams

1 +

Protecta Harnesses

Kleenguard® GP Coveralls

Particular protection for single-use tasks

Order Code

705-1440

705-1451 705-1463

705-1475

Over one million Protecta harnesses have been supplied worldwide. Protecta harnesses are colour-coded in two tones to make it easier to distinguish the lower and upper parts of the harness. All stitching is in contrasting Polyamide thread. All products comply with relavent European standards and therefore carry the CE mark. WHS451

Protecta Sanchocs

Sanchoc is a textile energy-absorbing system designed to arrest the fall of an individual in free-fall by the impact to a level below that of the current European Standard EN 355. Sanchoc allows the anchor point to be below the user. The system comprises two polyamide straps woven together in a single weave, which tear apart gradually until the fall is arrested. This tear strap is sewn to a second polyamide safety strap forming a loop on each side of the Sanchoc.

The minimum clearance below the anchor point must be a minimum of 6 metres. The unit must be connected to the Dorsal D-ring of the Protecta harness.

By design the Sanchoc unit is designed for one fall arrest only. WHS452

Protecta Fall Arrest Blocks

Fall arrest blocks are anchored to a point above the user and to the rear dorsal D-ring of the Protecta harness. They are designed for use whilst working on vertical, horizontal or inclined planes.

Their robust design allows them to continue the safety of the user even after a fall. It is essential that the stength of the anchor point as well as the risks of pendulum effects are considered before using a self-retracting fall arrest system.

WHS453