

## TS Floodlights — continued

### Floodlight 'Dominator'

TRAC LIGHTING



- British made, vandal resistant floodlight
- Body and lens are manufactured in anti-corrosive high impact polycarbonate IP65
- Typical uses: building facades, car parks, etc
- Photocell version available
- 70W SON(I) lamp inc
- Replacement lamp order code = 3353783

**New**

	Mfrs List No.	Height	Length	Width	Order Code
Dominator	PRF70S	320	260	115	353-7857
Dominator with photocell	PRF70S/PC	320	260	115	353-7869

SEC535

Order Code	1+	5+	10+
353-7857			
353-7869			

### Telescopic Combination Floodlight



- Dual use telescopic or portable floodlight
- Complete with easy 'twist-lock' height adjustable telescopic pole and floor stand (tripod)
- Steel construction finished in safety yellow colour
- Wire storage brackets on pole
- Weatherproof IP44
- Supplied with 2 metres of cable, fitted plug and 500W, 240V halogen lamp

**Best value**

Extended: H = 2500, W = 1000  
Closed: H = 1000, W = 180

SEC281X

Order Code	1+	5+	10+	20+
719-559				

### Tungsten Halogen Lamps



L = 189 (750, 1000W), 254 (1500W)

A range of tungsten halogen lamps suitable for the open face and enclosed floodlights.

SEC54X

Lamp Rating	Order Code	1+	5+	10+	20+	40+
240V						
200W	105-807					
300W	105-808					
500W	105-809					
750W	719-500					
1000W	719-511					
1500W	719-523					
110V						
300W	474-198					
500W	474-204					

## Outdoor Security Lighting

### Industrial Security 'Custodian'

WHITECROFT LIGHTING



- General purpose exterior fitting for car parks, building perimeters, etc
- Vandal resistant polycarbonate frame
- IP65 dust and jet wash proof
- Integral photocell option
- Supplied complete with SON lamp
- Replacement lamp 70W SON = 3353722

**New**

	Mfrs List No.	Height	Length	Width	Order Code
Standard	C70S	306mm	280mm	180mm	353-3761
With photocell	C70SP	306mm	280mm	180mm	353-3773

SEC525

Order Code	1+	5+	10+
353-3761			
353-3773			

### Floodlight

WHITECROFT LIGHTING

#### Euroflood Mini & Midi



- Typical uses: building facades, sports facilities, etc
- Precise asymmetric optics for pollution free lighting
- Delivers peak intensity at 50 degrees, allowing the front glass to be parallel to be lit
- Precision die cast aluminium body
- Finished grey to RAL 7035
- Toughened glass cover
- Low profile design for low windage
- Mini = medium beam angle, Midi = wide
- Supplied without lamps, accepts both HQI and SON

**New**


- Metal halide lamps (HQI) for Mini 70W = 341-5867, 150W = 341-5880
- Metal halide lamps (HQI) for Midi 250W = 341-5946, 400W = 341-5958
- High pressure sodium (SON) for Midi 250W = 335-3849, 400W = 335-3850

	Mfrs List No.	Height	Length	Width	Order Code
Euroflood Mini 70W	SC70	83mm	381mm	230mm	353-3724
Euroflood Mini 150W	SC150	83mm	381mm	230mm	353-3736
Euroflood Midi 250W	SC250TW	150mm	660mm	420mm	353-3748
Euroflood Midi 400W	SC400TW	150mm	660mm	420mm	353-3750

SEC528

Order Code	1+	5+	10+
353-3724			
353-3736			
353-3748			
353-3750			

### Passive Infra-Red Controlled Floodlight



- Unique intelligent PIR tracking system actively reduces false triggering caused by high wind, rain, moving trees and small animals
- 12 metre range with 140° detection angle
- "Time on" variable from 5 secs to 5 minutes
- Variable lux control
- Weatherproof to IP44
- Supplied with 500W halogen lamp, fixing bracket and cable gland

**Best value**

H = 240, W = 185, D = 135

Power requirements 230V ac 50Hz

SEC291X

Order Code	1+	5+	10+
719-584			