

Product	Viscosity			
Vactra 2	ISO VG 68			
Alternative Guide				
Mobil	Shell	Esso	Castrol	B.P.
Vactra 2	Tonna TX 68	Febis K 68	Magna BD 68	Maccurat 68

lub36

Mfrs.	Order Code	1+	4+	Price Each	72+	144+
List No.						
20 Litre Vactra 2	700-5155					

### Mobil DTE Named Oil Airline Oil

Mobil



- Manufactured from carefully selected base stocks
- Naturally high quality, chemically and thermally stable
- Stability further enhanced by UNIQUE additive package which promotes long life and inhibits corrosion in systems subject to water/moisture contamination

#### Typical uses of these products are:

##### DTE Light

Precision machine tools, airline lubricators, steam and gas turbine circulation systems.

##### DTE Medium

As above but where slightly heavier viscosity is required.

#### DTE Heavy Medium

Machine tool lubrication, hydraulic systems, air compressor crankcases, water turbines and ring oiled bearings.

Product	Viscosity					
DTE Light	ISO VG 32					

lub39

25 Litre Drum	Order Code	1+	4+	Price Each	12+	36+	72+
DTE Light	701-5203						

### Mould Release Products

#### Rocol PR Spray

ROCOL™



- Effective release of plastics and rubber moulded parts
- Heat-resistant wet film - up to 200°C
- Gives improved gloss finish
- Particularly suited to delicate or intricate parts
- Ideal for all types of blow, injection, flow and compression moulding
- Ideal for temperatures up to +200°C

lub29

Mfrs.	Order Code	1+	12+	Price Each	36+	72+	144+
List No.							
400ml 72015	706-9765						

### Grease

#### 'Handi' Bearing Grease

ROCOL™



- Bearing grease in easy to use precision applicator
- Convenient tool box sized pack, 150ml
- Suitable for a wide variety of industrial applications
- Sealed container – stops contamination
- Available in multi-purpose, hi-speed and foodlube

lub124

	Order Code	1+	6+	Price Each	12+	24+
Multi-purpose	725-4751					
Hi-speed	725-4763					
Foodlube	725-4775					

### Mobil Grease HP222

Mobil



- Provides excellent corrosion resistance
- Demonstrably superior water wash-off characteristics
- Inherent adhesion allows longer re-lubrication intervals
- NLGI No: 2 consistency, with ISO VG 220 superior base oil

Lithium complex grease, manufactured to meet the most demanding requirements for multi-purpose industrial, automotive and marine applications.

Approved by: Timken UNIPAC Bearings, Caterpillar Equipment Applications 1 E 0325, Komatsu, HD785-3 and HD1400B-3 bearings, Komatsu Dresser Multipurpose Spec LW 008-27.

lub49

	Order Code	1+	24+	Price Each	48+	96+	192+	384+
400g Cartridge	706-7744							

### Mobil Grease MP

Mobil



- Lithium hydroxystearate, general-purpose grease
- Suitable for most moderate applications in automotive or industrial applications
- Formulated to provide added protection against corrosion
- Recommended for lubrication of bearings, universal joints and other moving parts
- Recommended operating temperature range -20°C to +120°C
- NLGI No. 2 consistency, with an ISO VG 150 superior oil

lub51

	Order Code	1+	24+	Price Each	48+	96+	192+
400g Cartridge	706-8281						

### Sapphire 2

ROCOL™



- Revolutionary multi-complex soap technology
- Greatly extends lubrication intervals
- Excellent load-carrying properties
- Good corrosion resistance

Rocol Sapphire 2 is a long-life, general-purpose bearing grease designed for the effective lubrication and protection of all types of ball, roller and plain bearings. Sapphire 2 is compatible with other soap-thickened greases; however for best results bearings should be cleaned or purged of the previous lubricant.

Appearance  
NLGI No. (IP 50) (ASTM D217)  
Base fluid type  
Thickener  
Temperature range (ASTM D128)  
4 Ball Test (IP 326) (ASTM D2596)  
Weld Load  
Load Wear Index  
Timken 'OK' Load (IP 326) (ASTM D30)  
Copper corrosion test (IP 112) (ASTM D130)  
Corrosion test – Emcor (IP 220)  
Water washout test

Smooth, blue grease  
NLGI No. 2  
Mineral oil  
Multi-complex soap  
-30°C to +150°C

>800kg  
130kg  
60lb  
1a  
0:0  
2%

lub15

Mfrs.	Order Code	1+	10+	Price Each	20+	50+	100+
List No.							
400g 12171	706-5243						