

Mfrs. List No.	Order Code	1+	12+	36+	144+
300ml 15710	451-022				

Food Lubricant Foaming Chain Spray



- Non drip, food quality chain and drive lubricant
- Non toxic
- Foaming action aids application and ensures economic use
- Free from mineral hydrocarbons
- Uses FDA listed ingredients
- Meets USDA category H1 requirements
- Designed to lubricate rollers, drives and conveyor chains where contact with foodstuffs is possible
- Supplied with extension tube

Contains: CO₂ Operating Temperature: -20°C to +110°C
300ml Aerosol

Mfrs. List No.	Order Code	1+	12+	36+	144+
15730	451-034				

Food Lubricant Dismantling Spray



- Mineral hydrocarbon & solvent-free
- Excellent penetration of rust, scale & general grime
- Quick effective release of seized & corroded threaded fasteners
- Protective film provides short-term corrosion prevention
- FDA listed ingredients, **USDA H1 approved**
- Working temperature range -20°C to +110°C

Fast-acting penetrating spray specifically designed for applications where a clean, non-toxic product is preferred.

Mfrs. List No.	Order Code	1+	12+	36+	72+	144+
300ml Aerosol 15720	706-2035					

Automotive

Mobil 1 0W-40



- Quite simply the worlds most advanced engine oil
- Low pour point
- Excellent wear protection
- Outstanding detergency and discrepancy
- Improved fuel mileage
- Superior protection for turbo-charged engines
- Fully compatible with conventional engine oils

A fully synthetic lubricant with a truly unique formulation offering a level of engine protection that no other oil can match. Suitable for use in all types of cars and light vans. Mobil 1 has been tested on a BMW for 1,000,000 miles whose engine was found to have virtually no wear after laboratory analysis. Protect your vehicle with the best in the world.

Mfrs. List No.	Order Code	1+	4+	12+	36+
4 Litre Mobil 1 0W-40	710-9866				

Mobil Super 10W-40



- High quality engine oil suitable for almost all engines in current use, including passenger car and light vans (petrol and diesel, turbo and non-turbo)
- Meets/exceeds **API SG** and **CCMC G5/PD-2**

Mfrs. List No.	Order Code	1+	4+	12+	36+
4.5 Litre Mobil Super 10W-40	312-1574				

Machine Shop Lubricants - Reaming Tapping & Drilling

RTD Compound



- Extends tool life
- Improves surface finish
- Allows increased removal rates
- Reduces production costs
- Suitable for all metals including hardened steels, nimonics & titaniums

Rocol RTD compound is a soft paste for use in reaming, tapping, drilling and other cutting operations. Containing extreme pressure additives, this compound significantly reduces friction, giving superb cutting performance. Apply directly to the tool or workpiece.

Mfrs. List No.	Order Code	1+	12+	36+	72+	144+
500g Tin 53023	706-3453					

RTD Foamcut



- Extends tool life
- Improves surface finish
- Increases removal rate
- Reduces production costs
- Suitable for both ferrous & non-ferrous metals

The foaming action ensures rapid penetration to the cutting edges without running off the tool or workpiece, allowing economical application, even in deep holes.

Mfrs. List No.	Order Code	1+	12+	36+	72+	144+
400ml aerosol 53041	706-3696					

RTD Liquid



- Extends tool life
- Improves surface finish
- Increases removal rate
- Suitable for all metals including hardened steels, nimonics & titaniums

Rocol RTD liquid is a viscous fluid containing extreme pressure additives for use in reaming, tapping, drilling and other metal-cutting operations. Suitable for use as reinforcement for ordinary mineral cutting oil for the most severe operations, such as broaching and gear cutting on the toughest materials. Apply direct to tool or workpiece.

Mfrs. List No.	Order Code	1+	12+	36+	72+	144+
400ml bottle 53072	706-3714					

Continued

Call for Latest Pricing

Products on this page may be subject to price changes in line with market trends. Call us for an update on (65) 788 0200.