

Olympian Plus 64 Series — continued

Olympian Plus Lubricator



- Micro-Fog plug-in lubricators for most general purpose pneumatic applications
- Constant density output with varying flow
- Standard options include high capacity metal reservoirs
- Easy fill with quick-release bayonet bowls
- High visibility prismatic sight glass
- Oil fog



Micro fog lubricators inject a fine mist of oil into the air stream and are suitable for most pneumatic multivalve and cylinder circuits. For mounting bracket and yoke connector kit see Order Code 701-2123.

Medium Pressure Temperature	Compressed air only
Max. flow at 6.3 bar with a pressure drop of 0.5 bar	0 to 17 bar
Bowl Capacity	-20°C to +80°C
Bowl	72dm ³ s
	0.2
	Aluminium

Series	Size	Drain	A	B	C	F	G	H
L64M	G ¹ / ₄ , G ³ / ₈ , G ¹ / ₂	Auto	209	225	63	105	74	37

pne86

Port	Mfrs. List No.	Order Code	1+	4+	10+	20+
1/2"	L64M-NNP-EDN	701-2056				
1/2"	L64C-NNP-EDN	327-5863				

NOT supplied with a Yoke: Order separately

Gauges



- Dual calibrated dials, available for direct or panel mounting
- Choice of pressure ranges
- Conform to **BS 1780: Part 2, Industrial Class 2**
- Ideal for use with Olympian 64 series air preparation units
- G³/₈" ports

pne393

Gauges 1/2"	Mfrs. List No.	Order Code	1+	4+	10+	20+	50+
Direct Mounting							
0 to 6 bar	18-013-012	711-8041					
0 to 10 bar	18-013-013	711-8030					
Panel Mounting							
0 to 1.6 bar	18-013-991	711-8065					
0 to 10 bar	18-013-993	711-8053					

Olympian Plus Shut-Off Valve



- Isolates the air supply to an Olympian 64 series air preparation unit
- Lockable design
- 3/2 exhausting action
- Supplied with a connector kit
- Threaded exhaust port (1/8" bsp)
- Maximum pressure 17 bar

Olympian Plus Shut-Off Valve

pne88

Port	Mfrs. List No.	Order Code	1+	4+	10+	20+	50+
G ¹ / ₄	T64T-2GB-P1N	701-2093					
G ³ / ₈	T64T-3GB-P1N	701-2100					
G ¹ / ₂	T64T-4GB-P1N	701-2111					

Olympian Plus Yokes



- Single, double and triple units
- Use as spares for Olympian 64 series air preparation units

Olympian Plus Yokes

pne89

Port (BSP)	Type	Mfrs. List No.	Order Code	1+	4+	10+	20+
G ¹ / ₄	Single	Y64A-2GA-N1N	701-2123				
G ¹ / ₄	Double	Y64A-2GA-N2N	701-2135				
G ³ / ₈	Single	Y64A-3GA-N1N	701-2147				
G ³ / ₈	Double	Y64A-3GA-N2N	701-2159				
G ¹ / ₂	Single	Y64A-4GA-N1N	701-2160				
G ¹ / ₂	Double	Y64A-4GA-N2N	701-2172				
G ¹ / ₂	Triple	Y64A-4GA-N3N	721-3438				

Olympian Plus Accessories



- Easy and secure mounting of Olympian 64 series air preparation units
- Simple connection of yokes for the Olympian 64 units
- Both units sold including O rings and mounting screws

One size fits all units, the yoke connector kit is used by positioning two yokes together end to end, positioning the yoke connector over the joint, and tightening the connector kit screws down. A secure joint is produced.

The mounting bracket attaches to any yoke unit in the Olympian range.

pne90

Type	Mfrs. List No.	Order Code	1+	4+	10+	20+	50+
Bracket	74504-50	701-2214					
Connector Kit	74503-51	701-2226					

Additional Equipment

Pressure Gauges Bottom Entry



- Low cost ABS housing
- Ø 40mm, 1/8" BSP connection
- Ø 50mm, 1/4" BSP connection, dual scale (bar and psi)
- Accuracy class 2.5 to **DIN 16005**
- Brass movement and wetted parts

pne535

Pressure Range	Ø 40mm	Mfrs. List No.	Order Code	1+	5+	10+	25+
-1 to 0		1410016001	679-100				
0 to 2.5		1410072001	679-112				
0 to 10		1410075001	679-124				
0 to 25		1410098001	679-136				
0 to 100		1410081901	679-148				
Ø 50mm							
-1 to 0		1420016025	721-8345				
0 to 2.5		1420072024	721-8357				
0 to 10		1420075040	721-8369				
0 to 25		1420078022	721-8370				
0 to 100		1420081016	721-8382				

Pressure Gauges Rear Entry



- Low cost ABS housing
- Ø 40mm, 1/8" BSP connection
- Ø 50mm, 1/4" BSP connection, dual scale (bar and psi)
- Accuracy class 2.5 to **DIN 16005**
- Brass movement and wetted parts

pne536