


**CCTV Camera Accessories — continued**

**Low Voltage Camera Power Supplies**



- Single supply can power up to 3 cameras
- Protected by thermal cut-out
- Sealed unit in black ABS case with wall mount lugs

	<b>773-049</b>	<b>773-050</b>
Supply input	240V ac	240V ac
Supply output	12V dc, 1A	24V ac, 750mA
Weight	562g	542g

L = 115,  
W = 64, D = 45

SSW200X

Output Voltage	Order Code	1+	4+	8+
12V dc	<b>773-049</b>			
24V ac	<b>773-050</b>			

**Camera Housings/Mounting Equipment**

**Vandal Resistant Ceiling Mount Camera Housing**



The compact vandal resistant, ceiling mount camera housing overall size will accommodate most popular camera and lens combinations. The hinge-down top section is a significant advantage when installing and servicing. The housing is constructed from 1.2mm mild steel sheet, and exposed joints are seam welded and machine finished.

**Recent Addition**

- White, textured powder coat finish
- 20mm conduit knock-outs in the base and at either end of the base section
- Secured by a seven pin, radial camlock with 2 keys provided
- Impact resistant 6mm polycarbonate window
- Adaptor plate supplied for fitting to acoustic tiles in a suspended ceiling

SSW625

Order Code	1+	5+
<b>354-3948</b>		

**Vandal Resistant Camera Housing**



The type 508 housing is a stylish, weatherproof, fixed attitude, vandal resistant enclosure, designed to accommodate a wide range of CCD cameras. The housing design incorporates its own universal hidden cable bracket with built-in locking teeth. All fixings are stainless steel button head socket screws and the window is polycarbonate which adds up to total protection.

**DENNARD**

**Recent Addition**


- Constructed from aluminium alloy extrusions, powder coated & stoved
- Vandal resistant
- Slide and hang operation for ease of installation & maintenance
- Horizontal insulated camera platform adjustment
- Window heater & thermostat
- Weatherproof to IP65

Internal dimensions (L x W x H)	260 x 84 x 84mm
Weight	4.5kg
Heater power	9 watts

SSW655

Order Code	1+	4+
<b>354-2531</b>		

**Aluminium Extruded Housing**



This type of 500-130 housing is suitable for internal or external use, constructed from hollow aluminium extrusion with a die cast end plate and scratch resistant polycarbonate window offering strength, reliability and environmental protection to IP65.

**DENNARD**

**Recent Addition**

Supplied with a PCB camera platform, to which a thermostatically controlled heater and terminal blocks are fitted, standard fitments also include three cable glands, a full sunshield and tamper-proof fixings.

- Constructed from die cast & extruded aluminium alloy, powder coated & stoved
- Polycarbonate window
- Weatherproof to IP65
- Tamper-proof fixings
- Robust construction

Internal dimensions (L x W x H)	350 x 110 x 102mm
Weight	3.2kg
Heater power	12W

SSW673

Order Code	1+	4+
<b>354-2543</b>		
<b>354-2555</b>		
<b>354-2567</b>		
<b>354-2579</b>		

**Large External Camera Housing**



The type 515 camera housing is designed to accommodate a wide range of camera/lens combinations and to provide protection to IP65 (no water ingress). Insulated camera platforms with longitudinal adjustment are supplied as standard, plus window heater, thermostat, three cable glands and full sunshield. The housing is constructed from aluminium alloy, powder coated and stoved with stainless steel fittings.

**Recent Addition**

- Powder coated and stoved
- Weatherproof to IP65
- Window heater and thermostat
- Three latch cover retention

Internal dimensions (L x W x H)	440 x 135 x 97mm
Weight	3.6kg

SSW666

Order Code	1+	4+
<b>354-4321</b>		
<b>354-4333</b>		
<b>354-4345</b>		
<b>354-4357</b>		

**Housing Washer Units**



The Dennard washer unit is designed to accompany the type /W (354-4369) wiper unit. Together they provide a complete window wash/wipe system for the Dennard range of outdoor housings. Constructed from mild steel, zinc plated and powder coated and stoved with stainless steel fittings, the units offer environmental protection to IP65. The washer units are supplied with 10 metres of tubing to allow direct connection to the washer jet on the wiper unit.

**Recent Addition**

- Available in 5 litre or 25 litre versions
- Built-in fuse protection
- Supplied with 10 metres of tubing
- Maximum pumping height 10 metres
- Weatherproof to IP65

SSW668

Order Code	1+	4+
<b>354-4370</b>		
<b>354-4382</b>		

**Camera Housing Wiper**



The wiper unit is designed to accompany the 5 and 25 litre washer units. Together they provide a complete window wash/wipe system for the Dennard range of camera housings. Constructed from pressure die-cast aluminium alloy, powder coated and stoved with stainless steel wiper arms and fittings. The units offer protection to IP65. The self-parking arm is fitted with a washer jet as standard.

**Recent Addition**

- Self-parking wiper arm
- Washer nozzle
- Stainless steel wiper arm and blade
- Weatherproof to IP65
- Built-in fuse protection
- PCB plug-in connections
- Suitable for the following housings 500/130WP, 506 and 515

Wipe angle	45°	Power consumption	6VA
Weight	0.9kg		

SSW667

Order Code	1+	4+
<b>354-4369</b>		