

Length including cap = 172

- High quality miniature version of the
- pyropen
 Offers the same functions, soldering, blow torch and hot air torch, on a smaller scale
- Aluminium protective cap with pocket
- Temperature adjustable
- Operates on standard butane gas Supplied fitted with 0.5mm tapered
- needle soldering tip WPT-15, and 4.9mm hot blow nozzle WHC-55

CIIP						S0L092	
	Mftrs. List No.	Order Code	1+	Price 5+	Each 10+	48+	
Pyropen Junior	WSTA-2	.418-778.					
Soldering Tips 0.5mm Tapered needle 2.5mm Screwdriver style 2.0mm Sloped round	WPT-15 WPT-16 WPT-17	.418-780. .418-791. .418-808.	1+	25+	100+	200+	
Hot Blow Nozzles 1.5mm 4.9mm		.418-810. .418-821.					

Gas Soldering Iron Pyropen Junior, Self Igniting

Weller




- Self igniting butane gas operated soldering iron
- Adjustable gas flow gives equivalent 15W to 60W output
- Approximately 1 hours operation on full reservoir
- Heat up time is 30 seconds
- Can be fitted with hot blow nozzles
- Not supplied with gas

						S0L022
	Mftrs.		Price Each			
	List No.	Order Code	1+	3+	6+	12+
Pyropen	WSTA6	559-799				
Tips						
1.0mm Needle*	WPT01	559-805				
2.4mm Chisel	WPT02	559-817				
2.0mm Spade	WPT03	559-829				
5.0mm Spade	WPT04	559-830				
Hot Blow Nozzles						
1.5mm Dia.	WPT0150	559-842				
4.7mm Dia.	WPT0152	559-854				
*Fitted as standa	rd					

Gas Soldering Iron — 'Pyropen'

Weller



WSTA-3 Case H = 50, W = 60, L = 280

- Sophisticated gas powered soldering iron, inert gas/hot air blower and brazing
- Soldering tip temperature adjustable between 200°C and 500°C
- Tip is heated without a burning flame
- Use of a blow nozzle allows unit to be used for heat shrink tubing and soldering and desoldering of surface mount components
- Use of torch ejector produces an open burning flame for hard soldering and light brazing (not available in self-igniting model)
- Reservoir in handle holds sufficient butane gas for up to 3/4 hours soldering
- Not supplied with gas

1420 & Soldering

Available in three versions:

Economy (WSTA-1)

Supplied with one WPT-2 tip and protective cap

- Self Igniting (WSTA-4)

 As economy model but with integral piezo-electric ignitor

 Functions as soldering iron and hot air tool, but, not as a blow-torch

Heavy Duty Self Igniting (WSTA-5)

- 10mm soldering tip
- 6mm hot blow nozzle
- Heat shrink diffuser attachment
- Equivalent to 100-150W

Standard Model (WSTA-3)

- As economy model but supplied as a kit in a metal box
- Kit contains Hot blow tip (4.9mm ID); tool support clip, torch ejector, cleaning sponge and operating manual

	ŭ					SOL07
	Mftrs. List No.	Order Code	1+	Price 5+	Each 10+	48+
Pyropens Economy model	WSTA-1.	.418-833				
Self igniting model Heavy duty	WSTA-4.	.418-845				
self igniting Pyropen kit	WSTA-5 WSTA 3.					
Soldering Tips			1+	25+	100+	200+
Tapered needle	WPT-1.	.418-869				
3mm chisel	WPT-2.					
2mm spade	WPT-3. WPT-4.					
3mm 35° spade Offset tapered needle						
Offset tapered fieldie	WI I 10.	.410-300	1+	5+	10+	48
Chical tin	WPT-20	889-143	1+	3+	10+	40
Chisel tip	WP1-20	009-143	4.			
			1+			
Hot Blow Nozzles 1.59mm I.D.	WHC-50.	.418-912				
4.9mm I.D.	WHC-50.					
Torch Ejector	WP71T.	418-936				
Soldering Ejector	WP70S.					
• •	WF703.	410-940				
Spares Barrel assembly not						
self igniting model	WP72M.	418-950				
Gas refill (75ml)	PGR1.	418-961				
Piezo igniter	8038U	971-613				

Portasol Portable Gas Soldering Irons

Gas Soldering Iron 'Fixed Temperature 'Hobby'



- Portable low cost soldering iron Fixed operating temperature for ease of
- Nominal tip temperature of 350°C
- 35W power output
- Powered by standard butane lighter
- Gives upto 30 minutes continuous use
- from full reservoir
- Rectangular body to prevent rolling Safety gas cut off cap incorporating a
- flint lighter

Note: For safety reasons the iron is supplied discharged of gas.

FOR SUITABLE	GAS SEE ORDER	CODE	200-001	PAGE	1422	S0L174
Hobby iron	Order Code 493-600	1+		Each i+	20+	
Replacement Tips Screwdriver tip* Hot knife tip Point tip *Fitted as standard	493-612 493-624 493-636					