

## Rocker Switches — continued

### Miniature – 8600 Series


6(1)A @ 250V ac (SPST Momentary, SPDT, DPST Illuminated, DPST)  
10(4)A @ 250V ac (SPST, DPST)



Best value



Single pole



Double pole

Single pole Bezel = 21 15, Depth = 19, Panel cut-out = 19.3 13, Tab = 4.8 0.8  
Double pole Bezel = 24 21, Depth = 19, Panel cut-out = 19.3 21.9, Tab = 4.8 0.8

- Approved to **BEAB, VDE, SEV, DEMKO, SEMKO, NEMKO, SEMKO, KEMA, SETI, UTE, OVE, UL and CSA**
- Momentary type has push-to-make spring return action
- Illuminated type available with coloured illuminated rocker


Electrical life 10000ops      Insulation resistance >20MΩ  
Mechanical life 50000ops      Contact resistance <10mΩ  
Operating temperature 0°C to +90°C

Mfrs. List No. H8600VB = 151-133, H8601VB = 480-393, H8610VB = 151-134,  
H8620VB = 733-878, H8650VB = 151-135, H8660VB = 151-136,  
H8653VB Red = 152-266, H8653VB Green = 149-286

SW27

Non-Illuminated	Order Code	Price Each				
		1+	25+	100+	250+	500+
SPST	.151-133					
SPST, momentary	.480-393					
SPDT	.151-134					
SPDT, centre-off	.733-878					
DPST	.151-135					
DPDT	.151-136					
Illuminated						
DPST, Red	.152-266					
DPST, Green	.149-286					

### Miniature - Coloured Rocker



Bezel = 21 15  
Depth = 22.7  
Tabs = 4.8 0.8  
Cut out: 1mm panel (min) 19.3 13  
3mm panel (max) 19.5 13

- Compact rocker switches with coloured section visible in the ON position
- SPST and DPST fits standard panel cut out
- **UL, CSA, VDE and SEMKO** approved

Rating SPST 4A @ 250Vac      Contact resistance 20 x 10<sup>-3</sup> Ω  
6A @ 28Vdc      Insulation resistance > 50 x 10<sup>6</sup> Ω  
Rating DPST 10(6) A @ 250Vac      Dielectric strength Up to 3.5kV ac  
16A @ 12Vdc      Mechanical Life > 100,000 operations

SW162

	Order Code	Price Each				
		1+	25+	100+	250+	500+
SPST, Red	312-1677					
SPST, Green	312-1689					
SPST, Blue	312-1690					
SPST, Yellow	312-1707					
DPST, Red	312-1719					
DPST, Green	312-1720					
DPST, Blue	312-1732					
DPST, Yellow	312-1744					

### Miniature – 'Mini Visirocker'



6(4)A @ 250V ac



- Matt black switches with coloured section (red or green) on rocker that becomes visible in 'ON' position
- I/O markings on rocker for status indication
- Approved to **VDE, SEV, SEMKO, BEAB, DEMKO, NEMKO, SETI, UL and CSA**

Mfrs. List No. 6211691909V = 273-168, 6211691909G = 273-170,  
6211591909V = 273-181, 6211591909G = 273-193  
Bezel = 21.0 15.0, Depth = 27, Panel cut-out = 19.2 12.9, Tab = 4.7

SW204

	Order Code	Price Each			
		1+	25+	100+	250+
SPST, red	.273-168				
SPST, green	.273-170				
DPST, red	.273-181				
DPST, green	.273-193				

### Miniature – 8800 Series

10(6)A @ 250V ac



- Slimline body
- High rating 10(6)A @ 250V ac
- Approved to **BEAB, VDE, SEMKO, DEMKO, NEMKO, SETI, KEMA, OVE, SEV, NF-USE, IMQ, UL and CSA**
- Available with or without I/O status marking

Bezel = 21 9.5, Depth = 24,  
Panel cut-out = 19.3 6.8, Tab = 4.8 0.8

Electrical life 10000 ops.      Contact gap >3.0mm  
Contact resistance <10mΩ      Insulation resistance >1000MΩ  
Breakdown voltage >2kV

Mfrs. List No. H8800VA BLK = 678-120, H8800VA BLK 0/I = 678-132

SW252

	Order Code	Price Each				
		1+	100+	250+	500+	1K+
SPST	.678-120					
SPST, I/O	.678-132					

### Miniature – 8500 Series

10(6)A @ 250V ac, 85A Inrush (EN61058-1)



Bezel = 21 15, Body = 16.9 12.1, Depth = 23,  
Panel cut-out = 19.3 13, Tab = 4.8 0.8

- DPST switches that fit into standard SPST panel cut-out
- Approved to **BEAB, VDE, SEV, DEMKO, SEMKO, NEMKO, KEMA, SETI, UTE, IMQ, UL and CSA**
- Non-illuminated type available with or without I/O marking for status indication
- Illuminated type available with coloured illuminated rocker

Electrical life 10000ops      Insulation resistance >20MΩ  
Mechanical life 50000ops      Contact resistance <10mΩ  
Operating temperature 0°C to +125°C

Mfrs. List No. H8550VB = 149-905, H8550VB0/I = 273-200, H8553VB Red = 149-863,  
H8553VB Green = 149-864, H8553VB Amber = 150-388

SW134

Non-Illuminated	Rocker/Marking	Order Code	Price Each				
			1+	25+	100+	250+	500+
SPST	Black with I/O red	389-997					
	Black with I/O green	390-010					
DPST	Black	149-905					
DPST,	Black with I/O white	273-200					
DPST	Black/Red with I/O	390-021					
	Black/Green with I/O	566-147					
Illuminated							
DPST	red	.149-863					
DPST	green	.149-864					
DPST	amber	150-388					

### Splash Proof Covers



- Clear silicone rubber
- Cover simply clips over the switch mounted on the panel
- Seals to **IP64** and **DIN40050**, switch operation is unaffected
- Single pole size is suitable for Arcoelectric subminiature rocker switches 8600 series (single pole size) and 8500 series
- Double pole size is suitable for Arcoelectric subminiature rocker switches 8600 series (double pole size)


Single pole cut-out 19.3 13  
Double pole cut-out 19.3 21.9

Mfrs. List No. L167 = 149-287, F0180L0 = 151-575

SW127

	Order Code	Price Each			
		10+	100+	250+	500+
Single pole cut-out	149-287				
Double pole cut-out	151-575				

### Standard - 40 Series Single pole, 50 Series Double pole 10(4)A @250V ac



Single pole bezel = 30 x 13.9  
Depth = 29.6 Tabs = 6.3  
Cut-out: 1mm panel (min.) 27.3 x 12.2  
3mm panel (max) 27.5 x 13.2  
Double pole bezel = 21 x 15 Depth = 22.7 Tabs = 6.3  
Cut-out: 1mm panel (min) 27.2 x 22.1 3mm panel (max) 27.2 x 22.3

Best value