


Ultra Flush Mount IP67 – 84 Series

Illuminated and Non-illuminated Push Buttons and Indicators – 100mA @ 42V ac/dc, 2W


Push buttons/Indicators
Bezel = 25 dia. Panel cut-out = 22.5

- Ultra flush mounting – height above panel 2mm only
- Illuminated and non-illuminated switches available
- Integrated multi-chip LED (illuminated versions, 24V dc operating voltage)
- Flying lead or solder/plug-in terminations
- Detachable switch unit for easy wiring
- Gold plated normally open, momentary contacts
- Sealing to IP67



SW231

	Mfrs. List No.	Order Code	1+	10+	100+
Push Button Illuminated – Solder Terminal					
Red	K84-603.2105	618-901			
Yellow	K84-603.2909	618-913			
Green	K84-603.3311	618-925			
Push Button Non-Illuminated – Solder Terminal					
Red	K84-603.1705	618-937			
Yellow	K84-603.1709	618-949			
Green	K84-603.1711	618-950			
Indicator – Solder Terminal					
Red	K84-601.0305	618-962			
Yellow	K84-601.1109	618-974			
Green	K84-601.1511	618-986			
Push Button Illuminated – Flying Lead					
Red	K84-603.2205	618-998			
Yellow	K84-603.3009	619-000			
Green	K84-603.3411	619-012			
Push Button Non-Illuminated – Flying Lead					
Red	K84-603.1805	619-024			
Yellow	K84-603.1809	619-036			
Green	K84-603.1811	619-048			
Indicator – Flying Lead					
Red	K84-601.0405	619-050			
Yellow	K84-601.1209	619-061			
Green	K84-601.1611	619-073			
Accessories					
Mounting tool	84-997	619-085			
Lens remover	61-9730-0	619-097			
Dismantling tool for switch unit	84-998	619-103			

Industrial – A3PJ Series
3A @ 250Vac, 5A @ 125VacBezel: 32 25, Panel cut out 30.5 23.5,
Depth behind panel = 52.6

- 32 25mm bezel
- Single or split screen options available
- High quality silver contacts
- Back projected LED/lamp facility offers longer life
- Uses standard T 1-3/4 LED and Filament lamps
- Button lockable
- Complete switch = Switch Unit + Screen unit + LED
- Screen Unit consists of lens, legend plate, plunger, lamp holder, 5 coloured lenses (white, red, green, blue and yellow) and light baffle

OMRON

New

Switch Units	Mfrs. List No.	Order Code	1+	10+	50+	100+	250+
Price Each							
Momentary, SPCO	A3PJ-7010-1	328-1243					
Latching, SPCO	A3J-7020-1	328-1255					
Momentary, DPCO	A3PJ-7030-1	328-1267					
Latching, DPCO	A3PJ-7040-1	328-1279					
Switch Screen Units							
Single	A3PJ-5011	328-1280					
2-Split, Horizontal	A3PJ-5012	328-1292					
2-Split, Vertical	A3PJ-5013	328-1309					
Indicator Units							
Body	M2PJ-7010-1	328-1310					
Indicator Screen Units							
Single	M2PJ-5011	328-1322					
2-Split, Horizontal	M2PJ-5012	328-1334					
2-Split, Vertical	M2PJ-5013	328-1346					

Vandal Resistant IP65

0.5A @ 20V dc

L = 22.1, Bezel = 27.0 dia.,
Panel cut-out = 24

LED	Red 1.8V, 20mA Green 1.8V, 25mA	Contact resistance Operating temperature	50mΩ (typ) -30°C to +70°C
Mfrs. List Nos:	VR01S1A1G0 = 103-731 VR01S2A2R01 = 103-779 922400713 = 103-81	VR01S1A1R01 = 103-755 VR01S3A3R01 = 103-780	VR01S2A2G01 = 103-767 923600000 = 103-792

SW268

Body Colour	LED Colour	Order Code	1+	10+	50+	100+
Switch						
Silver	Green	103-731				
Silver	Red	103-755				
Black	Green	103-767				
Black	Red	103-779				
Red	Red	103-780				
Flying Lead Connector (200mm)		103-792				
Spare Locking Ring		103-810				

'Vandal Resistant' – IP65

Illuminated and Non-Illuminated – 50mA @ 24V dc

L = 23.8, Dia. = 22.0, Depth behind panel = 21.6
Max. panel thickness = 10.5,
Panel cut-out = 19.2
Connections : Switch = 1,2, LED = +,
– (illuminated types)

- Vandal resistant, low profile
- Robust stainless steel bushing and plunger, sealed to IP65
- Available LED illuminated red or green, or non-illuminated
- Gold plated contacts for low level switching

Switch rating	50mA max. (resistive), 24V dc
LED (illuminated types)	1.6V (2V max.) 2mA, red or green
Contact resistance	100mΩ max.
Insulation resistance	1000MΩ min./500V dc
Temperature range	-30°C to +70°C

Mfrs. List No.	AV09C703D240E = 607-538, AV09C7L3D2403E = 607-551	AV09C7L3D2406E = 607-540,
----------------	--	---------------------------

SW239

	Order Code	1+	10+	50+	100+
Price Each					
Non-illuminated	607-538				
Illuminated					
Red	607-540				
Green	607-551				

continued