

Spares and Accessories

AVO/Megger Instruments



Model	Walk & Work Carrying Case Order Code	Test Leads Order Code	Probes Hard Point
1000, 1001	423-786	423-889	
Model 8MK7		423-853 676-421	252-840
2001			
M2000 Series		423-889	
WM5500			
BM100 Series	423-786	423-889	
LT5		282-935	
BM200 Series		252-402	

For suitable safety test leads which comply with the **Health and Safety Executive GS38**, see order code 252-402 above

T142

	Mfrs. List No.	Order Code	1+	5+	10+
Walk and Work Case	6420 030	<b>423-786</b>			
Test Leads MK1	6120452	<b>423-853</b>			
Hard Point Probes MK2A	6220499	<b>252-840</b>			
	6120302	<b>676-421</b>			
	6220 434	<b>423-889</b>			
MK2	6280 294	<b>282-935</b>			
Fused Test Lead Set	6110 920	<b>252-402</b>			

TL80 Electronic Test Lead Set



- One meter long test leads with a safety shrouded, right angle banana at one end a stainless steel probe on the other
- Rated to 10A, silicone insulated leads
- Insulated alligator clips rated to 5A
- Insulated probe tip rated up to 3A
- Zipped vinyl soft case
- **Cat III 300V, IEC1010-1**

T474

	Order Code	1+	2+	5+	10+
TL80 Test Lead Set	<b>493-314</b>				

Fluke Instruments



423-981      424-006      201-285      467-194

Model	Holster Case Order Code	Soft Vinyl Case Order Code	TL75 Test Lead Set Order Code	Test Clips Order Code	630mA Fuse Order Code	1A Fuse Order Code	2A Fuse Order Code	3A Fuse Order Code	15A Fuse Order Code
10, 11, 12, 12B	227-018	227-020	201-285	467-194	105-559	106-667	105-558	147-615	105-999
70, 73, 75, 77, 79	423-981 or 227-031	424-006 or 424-018							
83, 85, 87		424-020							
23	423-981	424-006 or 424-018							
27		424-020							
8060A	—	424-018							
45, 45-01	—	—							
51, 52	423-981	424-006 or 424-018							

Note

C10 holder fits 7-300, 7-600 series  
C90 case required for instruments fitted in a C70 holster

T140

	Mfrs. List No.	Order Code	1+	2+	5+	10+
Holster case	C10	<b>227-018</b>				
Grey	C70	<b>423-981</b>				
Yellow	C70Y	<b>227-031</b>				
Soft vinyl case	C12	<b>227-020</b>				
	C50	<b>424-006</b>				
	C90	<b>424-018</b>				
	C25	<b>424-020</b>				
TL75 Test lead set	TL75	<b>201-285</b>				
Test clips (2 pack)	AC70A	<b>467-194</b>				
630mA fuse	740670	<b>105-559</b>				
1A Fuse	830828	<b>106-667</b>				
2A Fuse	376582	<b>105-558</b>				
3A Fuse	475004	<b>147-615</b>				
15A Fuse	820829	<b>105-999</b>				

High Voltage Probe  
To BS EN61010 40kV

TESTEC



- Suitable for measuring EHT rails
- Maximum input voltage 40kVdc or pk ac at 1000:1 division ratio
- Suitable for most multimeters (input resistance 10M)
- Moulded hard guard
- Hook style tip for hand free operation
- Supplied with 1m connection lead, terminated in 4mm plugs

**BS EN61010** to 40kV dc or peak to ac to earth  
Secondary voltage is derived from an over voltage category II primary supply

Input resistance	1000MΩ	Working voltage	40kV dc or pk ac, up to 300Hz
Division ratio	1000:1 ±1% into 10MΩ		28kV RMS
	1000:1 ±6% into 1MΩ	Operating temperature	0°C to +50°C
Accuracy DC volt	±2% (1kV to 20kV)		
	±3% (20kV to 40kV)		

T170

	Order Code	1+	5+	10+	25+
	<b>329-1285</b>				