

## Hygrometers

## Relative Humidity



- Portable relative humidity and temperature meter
- Large LCD
- Detachable 1m probe
- Fast response high accuracy
- Measurement in °C or °F, selectable
- Supplied complete with probe and battery

HANNA  
instruments

Range	10.0 to 95.0% RH 0 to 60°C (32 to 140°F)
Resolution	0.1% RH 0.1%°C, 1°F
Accuracy	2% RH, 0.4°C, 1°F
Weight	315g
Battery	1 x 9V PP3 (supplied)
Battery life	100 hrs

teq3

		Price Each		
Order Code		1+	5+	10+
710-6208				

## Moisture Meters

## T606 Moisture Meter



The compact 606 moisture meter has direct humidity display to measure moisture in wood, building materials etc.

- Low cost and user friendly
- Measuring range: wood 6 to 44%, building materials 0.2% to 2%
- Automatic measurement and battery test
- Supplied with protective cap, clip, battery and instruction manual

## Applications

- Measures moisture in lumber piles
- Measures moisture in walls, floors and plaster

testo

T485

		Price Each		
Order Code		1+	5+	10+
T606	311-8435			

## Light Meters

Digital Light Meter  
72-6693

W = 72, D = 32, L = 180

- Includes owner manual and battery
- CE marked

Range	Resolution	Power	9V battery
20,000 LUX	10 LUX	Dimensions	
100,000 LUX	100 LUX	(sensor probe)	W = 55, L = 85, D = 12
200 Ft-cd	0.1Ft-cd		
2,000 Ft-cd	1Ft-cd		
10,000 Ft-cd	10Ft-cd		

An easy to use, versatile, hand-held, microprocessor controlled, digital light meter.

- 3 ranges 2,000/20,000/50,000 LUX
- 3 ranges 200/2,000/10,000 Ft-cd
- Extra large, dual function display with contrast adjustment
- User selectable lighting type (tungsten, fluorescent, daylight and mercury)
- Records max./min./avg. readings
- Data hold and auto power off

TENMA®

New

T566

		Price Each		
Mfrs. List No.	Order Code	1+	3+	5+
72-6693	356-2670			

## Lux Meter



- 3½ digit display
- Low battery indicator
- Hand held digital light meter with integral sensor
- 3 switchable ranges
- Supplied with carry case

0 -	1999 lux	(resolution 1 lux)
1999 -	19999 lux	(resolution 10 lux)
19999 -	50,000 lux	(resolution 100 lux)

Requires 9V PP3 battery for operation.

teq15

		Price Each		
Mfrs. List No.	Order Code	1+	5+	10+
LX101	725-109			



- Large 13mm 3½ digit display
- Selection of 3 measuring ranges (0 to 100,000)
- Simple to use
- Enables the efficiency of lighting installation to be monitored

Measurement range	0 to 100,000 lux
Accuracy	±9% of reading ±1 digit
Resolution	
0 to 2000	1 lux
2,000 to 20,000	10 lux
20,000 to 100,000	100 lux
Battery	1 x PP3 >150 hours life

T354

		Price Each		
Order Code		1+	5+	10+
Luxmeter	908-204			
Carry case	908-216			

## T545 Light Meter



H = 50, W = 68, L = 220

In order to have good light quality the luminous intensity in places of work, hospitals, offices or schools has to fulfil specific minimum values. This can be measured and documented

- Timed mean calculations
- Multi-point mean calculations via 99 measurement points
- Up to 99 locations can be selected
- Logger function (3000 measured valued)
- Hold/Max/Min/Mean
- 2 switchable ranges of resolution
- Supplied with probe, battery and instruction manual

Measurement range	0 to 100,000 Lux	Weight	500g
Resolution	0 to 32,000 Lux 1 Lux	Warranty	2 years
	0 to 100,000 Lux 10 Lux		

T491

		Price Each		
Order Code		1+	5+	10+
T545	311-8447			