

Speedcramps



- Blue plastic octagonal handle for a firm grip in use
- Supplied with plastic covers for both head and slide
- Available in four lengths



MAT10

Length	Mftrs. List No.	Order Code	1+	3+	6+	12+
200	133/20	714-0897				
300	133/30	714-0903				
600	133/60	714-0915				
1000	133/100	714-0927				

Sash Cramps



- Steel sash cramps with malleable cramping heads
- Plated thread screw and T-bar handle

MAT11

Length	Mftrs. List No.	Order Code	1+	3+	6+	12+
750	10959	714-0940				
1050	10960	714-0952				

Multi-Position Clamps



714-7107



714-7119



- Heavy-duty multi-positional arms
- 714-7107 mounted on a powerful on/off magnetic base and has a 2" twist clamp
- 714-7119 fitted with a 2" top twist clamp and a 3" bottom twist clamp
- Unit acts as a third hand and locks items accurately in position
- Ideal for positioning two parts together prior to welding

MAT105

Overall height	Mftrs. List No.	Order Code	1+	3+	6+	12+
420mm	MG1300	714-7107				
400mm	MG1400	714-7119				

Vee-Blocks and Clamps



- Matched numbered pairs
- Made from chrome steel, hardened and ground 60HRC
- Clamps do not protrude over sides on two largest sizes
- Ideal for machining operations



Capacity ∅	L	W	H	Mftrs. List No.	Order Code
25	40	36	45	2-475-005	714-5410
38	40	45	70	2-475-010	714-5421
38	63	45	70	2-475-015	714-5433
54	90	70	125	2-475-020	714-5445

MAT89

Order Code	1+	3+	6+	12+
714-5410				
714-5421				
714-5433				
714-5445				

Magnetic Adjustable Link



- For simple and rapid clamping of two lightweight ferrous parts
- Can be quickly locked at any angle
- Ideal for holding work in confined spaces
- Blocks can be used singly as the basis for jigs



Dimensions of each unit	Overall length	Overall width	Weight
124 25 25	127	51	0.70 kg
60 25 25		(Single unit)	0.32 kg

MAT128

Mftrs. List No.	Order Code	1+	3+	6+	12+
920	715-0258				

Magnetic Clamps



- For effective heavy-duty holding of ferrous plate, tube and bar
- Provides fast, cost-effective workholding
- Levering away the clamps removes the workpiece
- Can be used in high temperature applications

- Plain face clamps intended for use with plates
- V-face clamps for bars and tubes up to 57mm

	Long Face	Short Face	Height	Width
Plain	152	70	44.5	41
Vee	178	95	44.5	41

MAT129

Mftrs. List No.	Order Code	1+	3+	6+	12+
923	715-0271				
924	715-0313				

Magnetic Quick Clamp



- Enables fast and accurate holding of ferrous metals
- Ideal for welding and assembly jobs
- Holds both sheet and tube at 180°, 90°, 75°, 60°, 45° and 30°
- Useful for all light fabrication work
- Dimensions: 100 65 12mm

MAT130

Mftrs. List No.	Order Code	1+	3+	6+	12+
E951	715-0325				

Magnetic Variable Clamp



- For quick and accurate holding of ferrous sheet and tube
- Ideal for welding and assembly jobs
- Can be clamped between 25° – 280°
- Angles 90°, 60°, 45° and 30° are marked for quick reference

- Dimensions: 195 200 11mm

MAT131

Mftrs. List No.	Order Code	1+	3+	6+	12+
E952	715-0337				

Toggle Clamp – Vertical



- The most popular of toggle clamps
- High clamping forces can be generated
- Complete with cushioned PVC handle grip
- Extendible base to guide the clamping arm
- Removable stop pin to alter operating angles
- Zinc-plated and passivated steel

	V75/2B	V150/2B	V250/2B	V350/2B
Nominal holding force	75 kg	150 kg	250 kg	350 kg
Weight	0.05 kg	0.15 kg	0.38 kg	0.80 kg
Height	98	125	175	220
Length	57	70	110	146
Hole centres	24 16	27 12.7	32 19	45 32
Hole ∅	4.4	5.1	7.1	8.3
Clamp arm length	31	43	74	95
Order Code	714-7510	714-7521	714-7533	714-7545

MAT113

Mftrs. List No.	Order Code	1+	3+	6+	12+
V75/2B	714-7510				
V150/2B	714-7521				
V250/2B	714-7533				
V350/2B	714-7545				

continued