

| Voltage | Nominal Lumens | Order Code | Price Each |      |     |
|---------|----------------|------------|------------|------|-----|
|         |                |            | 1+         | 100+ | 1K+ |
| 6.0     | 2.5            | .328-674   |            |      |     |
| 6.0     | 7.5            | 653-627    |            |      |     |
| 6.0     | 7.0            | 328-686    |            |      |     |
| 12.0    | 1.5            | 653-639    |            |      |     |
| 12.0    | 5.0            | .328-698   |            |      |     |
| 12.0    | 4.0            | 328-704    |            |      |     |
| 14.0    | 2.0            | 328-716    |            |      |     |
| 14.0    | 3.8            | 653-640    |            |      |     |
| 14.0    | 6.0            | 328-728    |            |      |     |
| 28.0    | 1.7            | 620-518    |            |      |     |
| 28.0    | 4.5            | .328-730   |            |      |     |
| 28.0    | 4.3            | 653-676    |            |      |     |
| 28.0    | 4.0            | .328-741   |            |      |     |
| 28.0    | 3.8            | 653-664    |            |      |     |
| 28.0    | 2.5            | 653-652    |            |      |     |
| 28.0    | 10.0           | 328-753    |            |      |     |
| 48.0    | 4.0            | .328-765   |            |      |     |
| 60.0    | 2.2            | .328-777   |            |      |     |

| Voltage         | Nominal Lumens | Order Code | Price Each |      |     |
|-----------------|----------------|------------|------------|------|-----|
|                 |                |            | 1+         | 100+ | 1K+ |
| <b>Lens End</b> |                |            |            |      |     |
| 2.5             | 3.1            | 328-789    |            |      |     |
| <b>Standard</b> |                |            |            |      |     |
| 6.3             | 5.0            | 328-790    |            |      |     |
| 14.0            | 6.0            | 328-807    |            |      |     |
| 14.0            | 3.8            | 653-688    |            |      |     |
| 28.0            | 4.5            | 328-819    |            |      |     |
| 28.0            | 3.8            | 653-690    |            |      |     |
| 36.0            | 3.5            | 265-329    |            |      |     |
| 48.0            | 2.8            | 328-820    |            |      |     |
| 60.0            | 2.2            | 328-832    |            |      |     |

### Flanged 11mm, B3½ Krypton Pre-Focus

**SLI**


| Voltage (V) | Current (A) | Nominal Lumens | Nominal Life (Hrs) | Mfrs. List No. | Order Code |
|-------------|-------------|----------------|--------------------|----------------|------------|
| 2.4         | 0.70        | 16.0           | 15                 | KPR102         | 595-226    |
| 2.4         | 0.835       | 18.5           | 15                 | KPR131         | 595-238    |
| 3.6         | 0.30        | 10.6           | 30                 | KPR7           | 595-240    |
| 3.6         | 0.70        | 34.0           | 15                 | KPR103         | 595-251    |
| 4.75        | 0.50        | 32.0           | 20                 | KPR15          | 595-263    |
| 4.8         | 0.70        | 50.0           | 15                 | KPR13          | 595-275    |
| 5.4         | 0.50        | 38.0           | 15                 | KPR12          | 595-287    |

Krypton gas-filled, brighter lamps suitable for torches with Nickel plated pre-focus cap. OPT286

| Voltage | Nominal Lumens | Order Code | Price Each |     |      |     |
|---------|----------------|------------|------------|-----|------|-----|
|         |                |            | 5+         | 25+ | 100+ | 1K+ |
| 2.4     | 16.0           | 595-226    |            |     |      |     |
| 2.4     | 18.5           | 595-238    |            |     |      |     |
| 3.6     | 10.6           | 595-240    |            |     |      |     |
| 3.6     | 34.0           | 595-251    |            |     |      |     |
| 4.75    | 32.0           | 595-263    |            |     |      |     |
| 4.8     | 50.0           | 595-275    |            |     |      |     |
| 5.4     | 38.0           | 595-287    |            |     |      |     |

### Midget Groove (S5.7s) 6mm T1¼



● Low cost replacement filament lamps

| Voltage (V) | Current (A) | Watts | Nominal Lumens | Nominal Life (Hrs) | Order Code |
|-------------|-------------|-------|----------------|--------------------|------------|
| 6.3         | 0.2         | 1.26  | 5.0            | 20,000             | 315-8974   |
| 14          | 0.08        | 1.12  | 6.3            | 750                | 315-8986   |
| 14          | 0.08        | 1.12  | 3.8            | 15,000             | 315-8998   |
| 28          | 0.04        | 1.12  | 4.3            | 4,000              | 315-9000   |
| 28          | 0.04        | 1.12  | 3.8            | 10,000             | 315-9012   |
| 48          | 0.025       | 1.2   | 4.3            | 5,000              | 315-9024   |
| 60          | 0.02        | 1.2   | 2.1            | 3,000              | 315-9036   |

#### Order Multiple=10

| Voltage | Nominal Lumens | Order Code | Price Each |     |      |      |
|---------|----------------|------------|------------|-----|------|------|
|         |                |            | 10+        | 50+ | 100+ | 500+ |
| 6.3     | 5.0            | 315-8974   |            |     |      |      |
| 14      | 6.3            | 315-8986   |            |     |      |      |
| 14      | 3.8            | 315-8998   |            |     |      |      |
| 28      | 4.3            | 315-9000   |            |     |      |      |
| 28      | 3.8            | 315-9012   |            |     |      |      |
| 48      | 4.3            | 315-9024   |            |     |      |      |
| 60      | 2.1            | 315-9036   |            |     |      |      |

### Midget Groove (S5.7s) 6mm, T1¼

**SLI**


| Voltage (V)     | Current (A) | Watts | Nominal Lumens | Nominal Life (Hrs) | Mfrs. List No. | Order Code |
|-----------------|-------------|-------|----------------|--------------------|----------------|------------|
|                 |             |       |                |                    |                |            |
| 2.5             | 0.35        | 0.875 | 3.1            | 10000              | 253            | 328-789    |
| <b>Standard</b> |             |       |                |                    |                |            |
| 6.3             | 0.20        | 1.26  | 5.0            | 20000              | 379            | 328-790    |
| 14.0            | 0.08        | 1.12  | 6.0            | 1000               | 336            | 328-807    |
| 14.0            | 0.08        | 1.12  | 3.8            | 15000              | 386            | 653-688    |
| 28.0            | 0.04        | 1.12  | 4.5            | 4000               | 334            | 328-819    |
| 28.0            | 0.04        | 1.12  | 3.8            | 10000              | 388            | 653-690    |
| 36.0            | 0.03        | 1.08  | 3.5            | 5000               | 788            | 265-329    |
| 48.0            | 0.025       | 1.2   | 2.8            | 5000               | 790            | 328-820    |
| 60.0            | 0.02        | 1.2   | 2.2            | 3000               | 799            | 328-832    |



Standard L = 15.9

IND8X

### Axial Wire Ended, T3.8 and T6.2

**SLI**


| Voltage (V) | Current (A) | Watts | T3.8<br>L = 20.0<br>Lead length = 15.0 (min) |                    | T6.2<br>L = 28.0<br>Lead length = 15.0 (min) |            |
|-------------|-------------|-------|--|--------------------|--|------------|
|             |             |       | Nominal Lumens                               | Nominal Life (Hrs) | Mfrs. List No.                               | Order Code |
| <b>T3.8</b> |             |       |  |                    |  |            |
| 5-8         | 0.10        | 0.6   | 1.9  | 5000               | 3820AL                                       | 620-701    |
| 10-15       | 0.055       | 0.6   | 2.3  | 5000               | 3890AL                                       | 620-713    |
| <b>T6.2</b> |             |       |  |                    |  |            |
| 5-8         | 0.25        | 1.6   | 5.0  | 10000              | 6255AL                                       | 620-725    |
| 10-15       | 0.11        | 1.3   | 7.0  | 5000               | 6275AL                                       | 620-737    |

OPT337

#### Order Multiple=5

| Voltage     | Order Code | Price Each |     |      |      |
|-------------|------------|------------|-----|------|------|
|             |            | 5+         | 25+ | 100+ | 500+ |
| <b>T3.8</b> |            |            |     |      |      |
| 5-8         | .620-701   |            |     |      |      |
| 10-15       | .620-713   |            |     |      |      |
| <b>T6.2</b> |            |            |     |      |      |
| 5-8         | .620-725   |            |     |      |      |
| 10-15       | .620-737   |            |     |      |      |

### Wire ended T1, T1¼

3mm T1, 5mm T1¼



● Low cost replacement filament lamps

| Voltage (V)    | Current (A) | Watts | Nominal Lumens | Nominal Life (Hrs) | Order Code |
|----------------|-------------|-------|----------------|--------------------|------------|
|                |             |       |                |                    |            |
| <b>3mm T1</b>  |             |       |                |                    |            |
| 5              | 0.06        | 0.3   | 0.4            | 25,000             | 315-9310   |
| 5              | 0.06        | 0.3   | 0.6            | 20,000             | 315-9322   |
| 5              | 0.12        | 0.56  | 1.5            | 20,000             | 315-9334   |
| 12             | 0.06        | 0.72  | 1.9            | 5,000              | 315-9346   |
| 28             | 0.03        | 0.67  | 1.9            | 1,000              | 315-9358   |
| 28             | 0.03        | 0.67  | 1.9            | 1,000              | 315-9395   |
| <b>5mm T1¼</b> |             |       |                |                    |            |
| 24             | 0.04        | 0.96  | 2.8            | 10,000             | 315-9360   |
| 28             | 0.04        | 1.12  | 4.3            | 4,000              | 315-9371   |

OPT639

#### Order Multiple=10

| Voltage        | Nominal Lumens | Order Code | Price Each |     |      |      |
|----------------|----------------|------------|------------|-----|------|------|
|                |                |            | 10+        | 50+ | 100+ | 500+ |
| <b>3mm T1</b>  |                |            |            |     |      |      |
| 5              | 0.4            | 315-9310   |            |     |      |      |
| 5              | 0.6            | 315-9322   |            |     |      |      |
| 5              | 1.5            | 315-9334   |            |     |      |      |
| 12             | 1.9            | 315-9346   |            |     |      |      |
| 28             | 1.9            | 315-9358   |            |     |      |      |
| 28             | 1.9            | 315-9395   |            |     |      |      |
| <b>5mm T1¼</b> |                |            |            |     |      |      |
| 24             | 2.8            | 315-9360   |            |     |      |      |
| 28             | 4.3            | 315-9371   |            |     |      |      |

continued