

## 0.1 Watt ±1% (0805 Case Size)

Stocked in the following OHMIC Values:

0R0 = 772-239	120R = 911-744	2K4 = 321-8107	51K = 321-8260
1R5 = 321-7172	130R = 321-7954	2K7 = 911-902	56K = 912-062
2R2 = 321-7784	150R = 911-756	3K = 321-8119	62K = 321-8272
3R3 = 321-7796	160R = 321-7966	3K3 = 911-914	68K = 912-074
4R7 = 321-7802	180R = 911-768	3K6 = 321-8120	75K = 321-8284
6R8 = 321-7814	200R = 321-7978	3K9 = 911-926	82K = 912-086
10R = 911-616	220R = 911-770	4K3 = 321-8132	91K = 321-8296
11R = 321-7826	240R = 321-7980	4K7 = 911-938	100K = 912-098
12R = 911-628	270R = 911-781	5K1 = 321-8144	110K = 321-8302
13R = 321-7838	300R = 321-7991	5K6 = 911-940	120K = 912-104
15R = 911-630	330R = 911-793	6K2 = 321-8156	130K = 321-8314
16R = 321-7840	360R = 321-8004	6K8 = 911-951	150K = 912-116
18R = 911-641	390R = 911-800	7K5 = 321-8168	160K = 321-8326
20R = 321-7851	430R = 321-8016	8K2 = 911-963	180K = 912-128
22R = 911-653	470R = 911-811	9K1 = 321-8170	200K = 321-8338
24R = 321-7863	510R = 321-8028	10K = 911-975	220K = 912-130
27R = 911-665	560R = 911-823	11K = 321-8181	240K = 321-8340
30R = 321-7875	620R = 321-8030	12K = 911-987	270K = 912-141
33R = 911-677	680R = 911-835	13K = 321-8193	300K = 321-8351
36R = 321-7887	750R = 321-8041	15K = 911-999	330K = 912-153
39R = 911-689	820R = 911-847	16K = 321-8200	360K = 321-8363
43R = 321-7899	910R = 321-8053	18K = 912-001	390K = 912-165
47R = 911-690	1K = 911-859	20K = 321-8211	430K = 321-8375
51R = 321-7905	1K1 = 321-8065	22K = 912-013	470K = 912-177
56R = 911-707	1K2 = 911-860	24K = 321-8223	510K = 321-8387
62R = 321-7917	1K3 = 321-8077	27K = 912-025	560K = 912-189
68R = 911-719	1K5 = 911-872	30K = 321-8235	620K = 321-8399
75R = 321-7929	1K6 = 321-8089	33K = 912-037	680K = 912-190
82R = 911-720	1K8 = 911-884	36K = 321-8247	750K = 321-8405
91R = 321-7930	2K = 321-8090	39K = 912-049	820K = 912-207
100R = 911-732	2K2 = 911-896	43K = 321-8259	910K = 321-8417
110R = 321-7942		47K = 912-050	1M = 912-219

Order Multiple=50	Price Each
0805 Case Size	MIXED QUANTITY PRICING
Order Code All Values	50+ 250+ 1000+ 5000+ 15000+

## 0.125 Watt ±1% (1206 Series)

Stocked in the following OHMIC Values:

0R0 = 772-240	120R = 912-360	1K8 = 912-505	27K = 912-645	390K = 912-785
10R = 912-232	150R = 912-372	2K2 = 912-517	33K = 912-657	470K = 912-797
12R = 912-244	180R = 912-384	2K7 = 912-529	39K = 912-669	560K = 912-803
15R = 912-256	220R = 912-396	3K3 = 912-530	47K = 912-670	680K = 912-815
18R = 912-268	270R = 912-402	3K9 = 912-542	56K = 912-682	820K = 912-827
22R = 912-270	330R = 912-414	4K7 = 912-554	68K = 912-694	1M = 912-839
27R = 912-281	390R = 912-426	5K6 = 912-566	82K = 912-700	
33R = 912-293	470R = 912-438	6K8 = 912-578	100K = 912-712	
39R = 912-300	560R = 912-440	8K2 = 912-580	120K = 912-724	
47R = 912-311	680R = 912-451	10K = 912-591	150K = 912-736	
56R = 912-323	820R = 912-463	12K = 912-608	180K = 912-748	
68R = 912-335	1K = 912-475	15K = 912-610	220K = 912-750	
82R = 912-347	1K2 = 912-487	18K = 912-621	270K = 912-761	
100R = 912-359	1K5 = 912-499	22K = 912-633	330K = 912-773	

Order Multiple=50	Price Each
1206 Case Size	MIXED QUANTITY PRICING
Order Code All Values	50+ 250+ 1000+ 5000+ 15000+

## MiniReel™

Surface Mount - ±1%



Tape width = 8mm



- 100mm reel size
- 1000 pieces on each reel
- Ideal for pre-production, prototyping and production shortfalls
- Complete with leader tape
- Surface mount thick film resistors
- ±1% tolerance

## 0.063 Watt ± 1% (0603 Case Size)

Stocked in the following OHMIC Values:

0R0 = 345-5970	82R = 345-6109	1K = 345-6237	12K = 345-6365	150K = 345-6493
10R = 345-5981	100R = 345-6110	1K2 = 345-6249	15K = 345-6377	180K = 345-6500
12R = 345-5993	120R = 345-6122	1K5 = 345-6250	18K = 345-6389	220K = 345-6511
15R = 345-6006	150R = 345-6134	1K8 = 345-6262	22K = 345-6390	270K = 345-6523
18R = 345-6018	180R = 345-6146	2K2 = 345-6274	27K = 345-6407	330K = 345-6535
22R = 345-6020	220R = 345-6158	2K7 = 345-6286	33K = 345-6419	390K = 345-6547
27R = 345-6031	270R = 345-6160	3K3 = 345-6298	39K = 345-6420	470K = 345-6559
33R = 345-6043	330R = 345-6171	3K9 = 345-6304	47K = 345-6432	560K = 345-6560
39R = 345-6055	390R = 345-6183	4K7 = 345-6316	56K = 345-6444	680K = 345-6572
47R = 345-6067	470R = 345-6195	5K6 = 345-6328	68K = 345-6456	820K = 345-6584
56R = 345-6079	560R = 345-6201	6K8 = 345-6330	82K = 345-6468	1M = 345-6596
68R = 345-6080	680R = 345-6213	8K2 = 345-6341	100K = 345-6470	
75R = 345-6092	820R = 345-6225	10K = 345-6353	120K = 345-6481	

## 1000 Pieces Per Reel

0603 case size

Order Code All Values

## Price Per Reel

1+ 3+ 5+

## 0.1 Watt ± 1% (0805 Case Size)

Stocked in the following OHMIC Values:

0R0 = 345-6602	82R = 345-6730	1K = 345-6869	12K = 345-6997	150K = 345-7126
10R = 345-6614	100R = 345-6742	1K2 = 345-6870	15K = 345-7000	180K = 345-7138
12R = 345-6626	120R = 345-6754	1K5 = 345-6882	18K = 345-7011	220K = 345-7140
15R = 345-6638	150R = 345-6766	1K8 = 345-6894	22K = 345-7023	270K = 345-7151
18R = 345-6640	180R = 345-6778	2K2 = 345-6900	27K = 345-7035	330K = 345-7163
22R = 345-6651	220R = 345-6780	2K7 = 345-6912	33K = 345-7047	390K = 345-7175
27R = 345-6663	270R = 345-6791	3K3 = 345-6924	39K = 345-7059	470K = 345-7187
33R = 345-6675	330R = 345-6808	3K9 = 345-6936	47K = 345-7060	560K = 345-7199
39R = 345-6687	390R = 345-6810	4K7 = 345-6948	56K = 345-7072	680K = 345-7205
47R = 345-6699	470R = 345-6821	5K6 = 345-6950	68K = 345-7084	820K = 345-7217
56R = 345-6705	560R = 345-6833	6K8 = 345-6961	82K = 345-7096	1M = 345-7229
68R = 345-6717	680R = 345-6845	8K2 = 345-6973	100K = 345-7102	
75R = 345-6729	820R = 345-6857	10K = 345-6985	120K = 345-7114	

## 1000 Pieces Per Reel

0805 case size

Order Code All Values

## Price Per Reel

1+ 3+ 5+

## 0.125 Watt ± 1% (1206 Case Size)

Stocked in the following OHMIC Values:

0R0 = 345-7230	82R = 345-7369	1K = 345-7497	12K = 345-7620	150K = 345-7758
10R = 345-7242	100R = 345-7370	1K2 = 345-7503	15K = 345-7631	180K = 345-7760
12R = 345-7254	120R = 345-7382	1K5 = 345-7515	18K = 345-7643	220K = 345-7771
15R = 345-7266	150R = 345-7394	1K8 = 345-7527	22K = 345-7655	270K = 345-7783
18R = 345-7278	180R = 345-7400	2K2 = 345-7539	27K = 345-7667	330K = 345-7795
22R = 345-7280	220R = 345-7412	2K7 = 345-7540	33K = 345-7679	390K = 345-7801
27R = 345-7291	270R = 345-7424	3K3 = 345-7552	39K = 345-7680	470K = 345-7813
33R = 345-7308	330R = 345-7436	3K9 = 345-7564	47K = 345-7692	560K = 345-7825
39R = 345-7310	390R = 345-7448	4K7 = 345-7576	56K = 345-7709	680K = 345-7837
47R = 345-7321	470R = 345-7450	5K6 = 345-7588	68K = 345-7710	820K = 345-7849
56R = 345-7333	560R = 345-7461	6K8 = 345-7590	82K = 345-7722	1M = 345-7850
68R = 345-7345	680R = 345-7473	8K2 = 345-7606	100K = 345-7734	
75R = 345-7357	820R = 345-7485	10K = 345-7618	120K = 345-7746	

RP326

## 1000 Pieces Per Reel


1206 case size

Order Code All Values

## Price Per Reel

1+ 3+ 5+

## Surface Mount - ±5%



Supplied on 8mm tape individually marked (reel = 5K pcs)



Case Size	L	Dimensions W	H	Maximum Working Voltage (V)	Temperature Coefficient	Tolerance
0603	1.6	0.8	0.4 - 0.55	50	±200ppm/°C	±5%
0805	2	1.25	0.4 - 0.55	100	±200ppm/°C	±5%
1206	3.2	1.6	0.5 - 0.65	200	±200ppm/°C	±5%

Operating temperature -55°C to +125°C

## 0.063 Watt ±5% (0603 Case Size)

Stocked in the following OHMIC Values:

0R0 = 772-227	56R = 612-339	820R = 612-479	15K = 612-625	150K = 612-741
1R5 = 758-267	68R = 612-340	1K = 612-480	18K = 612-637	180K = 612-753
2R2 = 758-279	82R = 612-352	1K2 = 612-492	22K = 612-649	220K = 612-765
3R3 = 758-280	100R = 612-364	1K5 = 612-509	27K = 612-650	270K = 612-777
4R7 = 758-292	120R = 612-376	1K8 = 612-510	33K = 612-662	330K = 612-789
6R8 = 758-309	150R = 612-388	2K2 = 612-522	39K = 612-674	390K = 612-790
10R = 612-248	180R = 612-390	2K7 = 612-534	47K = 612-686	470K = 612-807
12R = 612-250	220R = 612-406	3K3 = 612-546	56K = 612-698	560K = 612-819
15R = 612-261	270R = 612-418	3K9 = 612-558	68K = 612-704	680K = 612-820
18R = 612-273	330R = 612-420	4K7 = 612-560	82K = 612-716	820K = 612-832
22R = 612-285	390R = 612-420	5K6 = 612-571	100K = 612-728	1M = 612-844
27R = 612-297	390R = 612-431	6K8 = 612-583	120K = 612-730	
33R = 612-303	470R = 612-443	8K2 = 612-595		
39R = 612-315	560R = 612-455	10K = 612-601		
47R = 612-327	680R = 612-467	12K = 612-613		

RP174

## Order Multiple=50

0603 Case Size

Order Code All Values