

Mfrs. List No. 352780 = 152-575, Z356244 = 439-307, 355565 = 285-626, Z356246 = 439-319
352781 = 152-576, 219734

X-152576A = 112-4374, X-439307A = 112-4399, X-285626A = 112-4382, X-439319A = 112-4400

Colour	Order Code	Price Each					
		1+	25+	50+	100+	+	+
Straight							
Black 2m	152-575	566.00	496.00	452.00	300.00	--	--
White 2m	152-576	441.00	411.00	393.00	371.00	--	--
White 2m	112-4374	441.00	411.00	393.00	371.00	--	--
Grey 2m	285-626	457.00	432.00	408.00	361.00	--	--
Grey 2m	112-4382	457.00	432.00	408.00	361.00	--	--
Black 3m	439-307	542.00	501.00	439.00	371.00	--	--
Black 3m	112-4399	542.00	501.00	439.00	371.00	--	--
White 3m	439-319	542.00	501.00	439.00	371.00	--	--
White 3m	112-4400	542.00	501.00	439.00	371.00	--	--
Black 2m	112-4383	457.00	432.00	408.00	322.00	--	--
White 2m	112-4384	441.00	411.00	393.00	342.00	--	--

◇ Fits UK 3 Pin Mains Socket

Coiled 13A Plug Lead



- Spiroflex coiled 1mm² cable, extends to 2.5 metres
- Plug fitted with a 13A fuse and manufactured to **ASTA BS1363A**
- 10A cold condition socket approved by **BSI**

Warning:
The fuse supplied is designed to protect the cord set only. The appliance should be protected separately.

Mfrs. List No. 355737 = 299-959,

Body length=67, Cable length=2.5m (extended)

Current rating	10A @ 250V ac	Cable and connector housings	Black PVC
Fuse supplied	13A (interchangeable)	Plug contacts	Brass
		Socket contacts	Phosphor Bronze

Order Code	Price Each					
	1+	25+	50+	100+	+	+
299-959	1,030.00	887.00	736.00	621.00	--	--

◇ Fits UK 3 Pin Mains Socket

IEC Socket to Bared Ends, 2/2.5m



- Non-rewireable straight and right angled free sockets
- 2m or 3m cable, 3 core 0.75mm² or 1.0mm² stripped and bared PVC cable
- Lead meets **BS4491.EN60.320**
- Approved to **BSI, VDE, IMQ, SEMKO, NEMKO,**

Body length=77 straight, 51 right angle, Cable diameter=6.7-7.0 Free end stripped=38, Conductors bared=6.5-9.5

Cable capacity	2m - 10A @ 250V ac ()	Housing	Black Polycarbonate
	2.5m - 10A @ 250V ac ()	Cable	Black PVC, BS6500, UL94V-0
Socket rating	10A @ 250V ac	Contacts	Phosphor Bronze
		Temperature range	-40°C to +70°C

Mfrs. List No. Black: PZ0x00/y00, White: QZ0x00/y00/WHI where x = 1m straight or 2m right angle and y = length

Colour	Length	Order Code	Price Each					
			1+	50+	100+	250+	+	+
Straight								
Black	2m	148-701	258.00	233.00	224.00	150.00	--	--
Black	2m	999-6931	258.00	233.00	224.00	150.00	--	--
White	2m	469-660	258.00	233.00	224.00	150.00	--	--
White	2m	999-7130	258.00	233.00	224.00	150.00	--	--
Black	2.5m	209-235	281.00	235.00	221.00	144.00	--	--
Black	2.5m	999-7024	281.00	235.00	221.00	144.00	--	--
Right Angle								
Black	2m	148-702	282.00	260.00	250.00	150.00	--	--
Black	2m	999-6940	282.00	260.00	250.00	150.00	--	--
White	2m	469-671	295.00	268.00	205.00	142.00	--	--
White	2m	999-7148	295.00	268.00	205.00	134.00	--	--
Black	2.5m	209-247	306.00	274.00	241.00	158.00	--	--
Black	2.5m	999-7032	306.00	274.00	241.00	158.00	--	--

IEC to UK Mains Lead Cold Condition



- UK mains lead terminating with a 13A plug with 5A fitted fuse, and a cold condition IEC plug
- 2m Lead rated at 5A
- VDE approved cable
- Available in black and white

232595

Colour	Order Code	Price Each			
		1+	25+	50+	100+
White	389-3121	107.00	97.00	91.00	90.00
Black	389-3133	102.00	92.00	88.00	--

Extension Lead, 2m



- High quality non-rewireable extension lead, meets European standard **BS4491.EN60.320**
- Two metres of 1.00mm² cable approved to **BASEC BS6500**
- 10A socket approved to **VDE, SEV**

Socket length=65, Plug length=77 Cable length=2m Diameter=6.9-7.2

Current rating	10A @ 250V ac	Male contacts	Brass
Cable and connector housings	Black PVC	Female contacts	Phosphor bronze

209217

Order Code	Price Each					
	1+	25+	50+	100+	+	+
152-577	451.00	418.00	389.00	314.00	--	--
112-4375	451.00	418.00	389.00	314.00	--	--

International Mains Leads

North America, 2m



- Non-rewireable lead suitable for use in USA and Canada
- Plug, **UL498** recognised and **CSA 22.2 No.42**
- 2 metres of light duty 18 AWG **SVT** cable
- Available with or without IEC socket

Cable length = 2m, Diameter = 6.6mm - 6.9mm

Current rating	10A @ 125V	Plug contacts	Brass, Nickel plated
Cable and Connector housings	Black PVC	Socket Contacts	Phosphor Bronze

219690

Order Code	Price Each					
	1+	25+	50+	100+	+	+
Plug to IEC Socket						
210-705	422.00	399.00	379.00	359.00	--	--
112-4380	422.00	399.00	379.00	359.00	--	--
Plug to Bare Ends						
420-3045	339.00	320.00	304.00	288.00	--	--
112-4393	339.00	320.00	304.00	288.00	--	--

IEC Free Sockets

Rewireable Free Sockets



Black and White



H=18.4, W=26.4 D=78.3 (inc. sleeve)

H=18.4, W=65 (inc sleeve) D=51.9

- Rewireable, line socket style connectors, complies with **BS4491**
- Internal screw terminations and strain relief
- Approvals: **UL, CSA, VDE, IMQ**

NEW

Contact rating	10A @ 250V	Housing Contacts	Nylon UL94V-0
			Brass, Nickel plated

Connectors - Power & Mains

Compliant Non-compliant Limited stock - RoHS replacement available **RoHS**