

RT-375 Super Clear- 2:1 Shrink Ratio



- Flexible modified Clear fluoropolymer tubing
- Extreme clarity
- Excellent physical and electrical properties
- 2:1 shrink ratio
- Flame retardant to VW-1
- UL, CSA and MIL-DTL-23053/18
- Minimum shrink temperature +125°C
- Operating temperature -55°C to 150°C

208300

1.2m Lengths

Dia. Nom.	Shrunk	Mftrs. List No.	Order Code	1+	5+	10+	25+	+
1.2	0.6	RT-375-3/64-X-4FT	121-0443	140.00	128.00	121.00	116.00	--
1.6	0.8	RT-375-1/16-X-4FT	121-0444	142.00	129.00	122.00	117.00	--
2.4	1.2	RT-375-3/32-X-4FT	121-0446	152.00	137.00	130.00	125.00	--
3.2	1.6	RT-375-1/8-X-4FT	121-0447	164.00	147.00	138.00	132.00	--
4.8	2.4	RT-375-3/16-X-4FT	121-0448	176.00	160.00	149.00	143.00	--
6.4	3.2	RT-375-1/4-X-4FT	121-0449	193.00	176.00	166.00	158.00	--
9.5	4.8	RT-375-3/8-X-4FT	121-0450	251.00	228.00	215.00	207.00	--
12.7	6.4	RT-375-1/2-X-4FT	121-0451	290.00	263.00	247.00	238.00	--
19.1	9.5	RT-375-3/4-X-4FT	121-0453	353.00	320.00	301.00	291.00	--
25.4	12.7	RT-375-1-X-4FT	121-0454	510.00	460.00	436.00	418.00	--

RP-4800 High Shrink - 4:1 Shrink Ratio



- Flexible Black polyolefin tubing
- High expansion ratio
- Good mechanical strength
- 4:1 shrink ratio, 4 sizes cover whole range
- Flame retardant
- MIL-DTL-23053/5 Class 1 and VG95343 Part 5A
- Minimum shrink temperature +95°C
- Operating temperature -55°C to +135°C
- UL (E35586) recognised

208298

1.2m Lengths

Dia. Nom.	Shrunk	Mftrs. List No.	Order Code	1+	5+	10+	25+	+
25.4	7	RP-4800-NR1-0	121-0455	1,268.00	1,148.00	1,083.00	1,040.00	--
50.8	14	RP-4800-NR2-0	121-0456	1,592.00	1,440.00	1,360.00	1,305.00	--
76.2	20.6	RP-4800-NR3-0	121-0457	2,427.00	2,157.00	2,037.00	1,955.00	--
101.6	26.7	RP-4800-NR4-0	121-0458	2,973.00	2,690.00	2,540.00	2,437.00	--

ATUM Adhesive Lined 3:1 Shrink Ratio



- Semi-flexible adhesive lined Black polyolefin tubing
- Adhesive lining provides high strength bonding to wide range of substrates
- Good mechanical and solvent resistance
- 3:1 shrink ratio
- MIL-DTL-23053/4 Class 3 approved
- Minimum shrink temperature +80°C
- Operating temperature -55°C to +110°C

208299

1.2m Lengths

Dia. Nom.	Shrunk	Mftrs. List No.	Order Code	1+	5+	10+	25+	+
3	1	ATUM-3/1-0-4FT	121-0459	409.00	398.00	384.00	377.00	--
4.5	1.5	ATUM-4.5/1.5-0-STK	417-2851	476.00	434.00	419.00	390.00	--
6	2	ATUM-6/2-0-4FT	121-0460	544.00	530.00	510.00	499.00	--
9	3	ATUM-9/3-0-4FT	121-0461	673.00	654.00	632.00	620.00	--
12	4	ATUM-12/4-0-4FT	121-0462	735.00	713.00	690.00	676.00	--
19	6	ATUM-19/6-0-4FT	121-0463	955.00	928.00	897.00	879.00	--
24	8	ATUM-24/8-0-4FT	121-0465	1,406.00	1,365.00	1,318.00	1,291.00	--
40	13	ATUM-40/13-0-4FT	121-0466	2,816.00	2,736.00	2,642.00	2,590.00	--

RoHS Directive

Worried about the part number lottery?
Count on us for traceability
-visit www.rohs.info

Don't risk anyone else for RoHS

RNF-100 - 2:1 Shrink Ratio



- Flexible coloured polyolefin tubing
- Available in 1.2m lengths and bulk spools (Black only)
- Conforms to irregular shapes
- Excellent physical, chemical and electrical properties
- Wide range of colours and sizes
- 2:1 shrink ratio
- Flame retardant (except Clear)
- MIL-DTL-23053/5 Class 1&2, VG95353 Part 5B and DEF-STAN 59-97 Type 2B approved
- Minimum shrink temperature +95°C
- Operating temperature -55°C to +135°C
- UL (E35586), CSA (LR31929) recognised

1.2m Lengths

208301.343067

1.2m Lengths

Dia. Nom.	Shrunk	Mftrs. List No.	Order Code	1+	5+	10+	25+	+
Black								
1.2	0.6	RNF-100-3/64-0-4FT	121-0347	125.00	122.00	119.00	116.00	--
1.6	0.8	RNF-100-1/16-0-4FT	121-0349	108.00	106.00	102.00	99.00	--
2.4	1.2	RNF-100-3/32-0-4FT	121-0351	108.00	106.00	102.00	99.00	--
3.2	1.6	RNF-100-1/8-0-4FT	121-0352	125.00	122.00	119.00	116.00	--
4.8	2.4	RNF-100-3/16-0-4FT	121-0353	127.00	124.00	121.00	118.00	--
6.4	3.2	RNF-100-1/4-0-4FT	121-0354	170.00	166.00	162.00	157.00	--
9.5	4.8	RNF-100-3/8-0-4FT	121-0355	223.00	216.00	212.00	207.00	--
12.7	6.4	RNF-100-1/2-0-4FT	121-0356	258.00	251.00	245.00	239.00	--
19.0	9.5	RNF-100-3/4-0-4FT	121-0357	315.00	305.00	298.00	291.00	--
25.4	12.7	RNF-100-1-0-4FT	121-0358	444.00	432.00	421.00	410.00	--
38.0	19.0	RNF-100-1-1/2-0-4FT	121-0359	770.00	748.00	732.00	711.00	--
51.0	25.4	RNF-100-2-0-4FT	121-0360	1,155.00	1,122.00	1,096.00	1,066.00	--
76.0	38.0	RNF-100-3-0-STK	121-0362	1,958.00	1,845.00	1,701.00	1,612.00	--
102.0	51.0	RNF-100-4-0-STK	121-0363	3,099.00	2,920.00	2,696.00	2,552.00	--
Red								
1.2	0.6	RNF-100-3/64-2-4FT	121-0364	125.00	122.00	119.00	116.00	--
1.6	0.8	RNF-100-1/16-2-4FT	121-0365	108.00	106.00	102.00	99.00	--
2.4	1.2	RNF-100-3/32-2-4FT	121-0366	108.00	106.00	102.00	99.00	--
3.2	1.6	RNF-100-1/8-2-4FT	121-0367	125.00	122.00	119.00	116.00	--
4.8	2.4	RNF-100-3/16-2-4FT	121-0368	127.00	124.00	121.00	118.00	--
6.4	3.2	RNF-100-1/4-2-4FT	121-0369	170.00	166.00	162.00	157.00	--
9.5	4.8	RNF-100-3/8-2-4FT	121-0370	223.00	216.00	212.00	207.00	--
12.7	6.4	RNF-100-1/2-2-4FT	121-0371	258.00	251.00	245.00	239.00	--
19.0	9.5	RNF-100-3/4-2-4FT	121-0372	315.00	305.00	298.00	291.00	--
25.4	12.7	RNF-100-1-2-4FT	121-0374	444.00	432.00	421.00	410.00	--
38.0	19.0	RNF-100-1-1/2-2-4FT	121-0375	770.00	748.00	732.00	711.00	--
51.0	25.4	RNF-100-2-2-4FT	121-0378	1,155.00	1,122.00	1,096.00	1,066.00	--
Yellow								
1.2	0.6	RNF-100-3/64-4-4FT	121-0379	125.00	122.00	119.00	116.00	--
1.6	0.8	RNF-100-1/16-4-4FT	121-0380	108.00	106.00	102.00	99.00	--
2.4	1.2	RNF-100-3/32-4-4FT	121-0381	108.00	106.00	102.00	99.00	--
3.2	1.6	RNF-100-1/8-4-4FT	121-0382	125.00	122.00	119.00	116.00	--
4.8	2.4	RNF-100-3/16-4-4FT	121-0383	127.00	124.00	121.00	118.00	--
6.4	3.2	RNF-100-1/4-4-4FT	121-0384	170.00	166.00	162.00	157.00	--
9.5	4.8	RNF-100-3/8-4-4FT	121-0386	223.00	216.00	212.00	207.00	--
12.7	6.4	RNF-100-1/2-4-4FT	121-0387	258.00	251.00	245.00	239.00	--
19.0	9.5	RNF-100-3/4-4-4FT	121-0388	315.00	305.00	298.00	291.00	--
25.4	12.7	RNF-100-1-4-4FT	121-0389	444.00	432.00	421.00	410.00	--
38.0	19.0	RNF-100-1-1/2-4-4FT	121-0390	770.00	748.00	732.00	711.00	--
50.8	25.4	RNF-100-2-4-4FT	304-5584	1,099.00	1,052.00	1,027.00	943.00	--
Green								
1.2	0.6	RNF-100-3/64-5-4FT	121-0391	125.00	122.00	119.00	116.00	--
1.6	0.8	RNF-100-1/16-5-4FT	121-0392	108.00	106.00	102.00	99.00	--
2.4	1.2	RNF-100-3/32-5-4FT	304-5614	103.00	99.00	96.00	89.00	--
3.2	1.6	RNF-100-1/8-5-4FT	121-0393	125.00	122.00	119.00	116.00	--
4.8	2.4	RNF-100-3/16-5-4FT	121-0394	127.00	124.00	121.00	118.00	--
6.4	3.2	RNF-100-1/4-5-4FT	121-0395	170.00	166.00	162.00	157.00	--
9.5	4.8	RNF-100-3/8-5-4FT	121-0396	223.00	216.00	212.00	207.00	--
12.7	6.4	RNF-100-1/2-5-4FT	121-0398	258.00	251.00	245.00	239.00	--
19.0	9.5	RNF-100-3/4-5-4FT	121-0399	315.00	305.00	298.00	291.00	--
25.4	12.7	RNF-100-1-5-4FT	121-0400	444.00	432.00	421.00	410.00	--
51.0	25.4	RNF-100-2-5-4FT	121-0402	1,155.00	1,122.00	1,096.00	1,066.00	--
Blue								
1.2	0.6	RNF-100-3/64-6-4FT	304-5717	113.00	110.00	107.00	104.00	--
1.6	0.8	RNF-100-1/16-6-4FT	121-0404	108.00	106.00	102.00	99.00	--
2.4	1.2	RNF-100-3/32-6-4FT	121-0405	108.00	106.00	102.00	99.00	--
3.2	1.6	RNF-100-1/8-6-4FT	121-0406	125.00	122.00	119.00	116.00	--
4.8	2.4	RNF-100-3/16-6-4FT	121-0408	127.00	124.00	121.00	118.00	--
6.4	3.2	RNF-100-1/4-6-4FT	121-0410	170.00	166.00	162.00	157.00	--
9.5	4.8	RNF-100-3/8-6-4FT	121-0411	223.00	216.00	212.00	207.00	--
12.7	6.4	RNF-100-1/2-6-4FT	121-0412	258.00	251.00	245.00	239.00	--
19.0	9.5	RNF-100-3/4-6-4FT	121-0413	315.00	305.00	298.00	291.00	--
25.4	12.7	RNF-100-1-6-4FT	121-0414	444.00	432.00	421.00	410.00	--
38.1	19.1	RNF-100-1-1/2-6-4FT	304-5810	732.00	700.00	685.00	628.00	--
51.0	25.4	RNF-100-2-6-4FT	121-0416	1,155.00	1,122.00	1,096.00	1,066.00	--
White								
1.2	0.6	RNF-100-3/64-9-4FT	304-5833	120.00	115.00	112.00	103.00	--
1.6	0.8	RNF-100-1/16-9-4FT						