

Order Multiple=10

Rating	Order Code	Price Each			
		10+	100+	250+	500+
375mA	992-2318	37.00	35.00	32.00	26.00
500mA	992-2326	38.00	36.00	33.00	27.00
750mA	992-2334	35.00	31.00	30.00	24.00
1A	992-2342	35.00	31.00	30.00	26.00
1.5A	992-2350	35.00	31.00	30.00	24.00
2A	992-2369	35.00	31.00	30.00	26.00
2.5A	992-2377	35.00	31.00	30.00	24.00
3A	992-2385	35.00	31.00	30.00	24.00
3.5A	992-2393	35.00	31.00	30.00	24.00
4A	992-2407	35.00	31.00	30.00	24.00
5A	992-2415	35.00	31.00	30.00	26.00

Fuse and Fuseholder Combinations

Nanofuse - 125V ac/dc & Omni Block



The Omni Block fuseholder permits quick and easy replacement of nanofuses. The fuse holder is pre-installed with a nanofuse and can be placed on the PCB in one operation. The surface mount fuse can then be replaced without the normal problems of SMD rework. The supplied fuse has silver plated contacts to prevent it soldering into the holder when reflow soldered. **UL** Recognised and **CSA** approved.

Fuse holder rated at 7A Voltage rating 125V ac/dc
 Fuse holder thermoplastic to UL94V-0 Operating temperature -55°C to +125°C
 Mfrs. List No. 154 + Rating. Add suffix H for strip of 100 & T for antisurge

Fuse Fitted	Order Code	Price Each			
		10+	50+	100+	500+
Quick Blow (F)					
62mA	664-807	180.00	141.00	120.00	115.00
125mA	664-819	192.00	151.00	131.00	121.00
250mA	664-820	110.00	93.00	84.00	80.00
500mA	664-832	111.00	94.00	84.00	80.00
1A	664-844	110.00	93.00	84.00	80.00
2A	664-856	107.00	91.00	82.00	76.00
3A	664-868	107.00	91.00	82.00	76.00
5A	664-870	107.00	91.00	82.00	76.00
Antisurge (T)					
375mA	664-893	148.00	130.00	119.00	114.00
500mA	664-900	136.00	120.00	111.00	78.00
750mA	664-911	136.00	120.00	111.00	78.00
1A	664-923	152.00	134.00	122.00	86.00
1.5A	664-935	148.00	129.00	118.00	84.00
2A	664-947	136.00	120.00	111.00	78.00
2.5A	664-959	137.00	120.00	111.00	78.00
3A	664-960	137.00	120.00	111.00	78.00
3.5A	664-972	148.00	131.00	119.00	84.00
4A	664-984	141.00	125.00	115.00	80.00
5A	664-996	141.00	125.00	115.00	80.00

FUS264/220502

Fuse Fitted	Order Code	Price Each			
		10+	50+	100+	500+
Quick Blow (F)					
62mA	994-3595	180.00	141.00	120.00	115.00
125mA	994-3609	192.00	151.00	131.00	121.00
250mA	994-3617	110.00	93.00	84.00	80.00
500mA	994-3625	111.00	94.00	84.00	80.00
1A	994-3633	110.00	93.00	84.00	80.00
2A	994-3641	107.00	91.00	82.00	76.00
3A	994-3650	107.00	91.00	82.00	76.00
5A	994-3668	107.00	91.00	82.00	76.00
Antisurge (T)					
375mA	994-3676	148.00	130.00	119.00	114.00
500mA	994-3684	136.00	120.00	111.00	78.00
750mA	994-3692	136.00	120.00	111.00	78.00
1A	994-3706	152.00	134.00	122.00	86.00
1.5A	994-3714	148.00	129.00	118.00	84.00
2A	994-3722	136.00	120.00	111.00	78.00
2.5A	994-3730	137.00	120.00	111.00	78.00
3A	994-3749	137.00	120.00	111.00	78.00
3.5A	994-3757	148.00	131.00	119.00	84.00
4A	994-3765	141.00	125.00	115.00	80.00
5A	994-3773	141.00	125.00	115.00	80.00

20 x 5mm Fuses

Quick Blow(F) Ceramic

MCF04C Series



Complies with IEC 127, DIN41660 and BS4265

Voltage rating 250V Breaking capacity 1500A @ 250V


Mfrs. List No. MCF04C + Rating

FUS287/204484

Current Rating	Order Code	Price Each				
		10+	100+	500+	1K+	+
100mA	112-3145	30.00	27.00	26.00	23.00	--
125mA	112-3147	30.00	27.00	26.00	23.00	--
200mA	112-3150	30.00	27.00	26.00	23.00	--
250mA	112-3151	30.00	27.00	26.00	23.00	--
315mA	112-3155	30.00	27.00	26.00	23.00	--
400mA	112-3156	30.00	27.00	26.00	23.00	--
500mA	112-3158	30.00	27.00	26.00	23.00	--
630mA	112-3161	30.00	27.00	26.00	23.00	--
800mA	112-3162	30.00	27.00	26.00	23.00	--
1A	112-3148	16.00	14.00	14.00	12.00	--
1.25A	112-3143	15.00	14.00	13.00	11.00	--
1.6A	112-3144	14.00	13.00	12.00	10.00	--
2A	112-3152	14.00	13.00	12.00	10.00	--
2.5A	112-3149	15.00	14.00	13.00	11.00	--
3.15A	112-3153	14.00	13.00	12.00	10.00	--
4A	112-3157	14.00	13.00	12.00	10.00	--
5A	112-3159	14.00	13.00	12.00	10.00	--
6.3A	112-3160	15.00	13.00	12.00	11.00	--
8A	112-3163	15.00	14.00	13.00	11.00	--
10A	112-3146	15.00	14.00	13.00	11.00	--

Quick Blow (F) HRC Ceramic

20 x 5mm Fuses S501 Series



Complies with IEC127:Standard Sheet I

Approved to SEMKO (500mA to 5A)

Voltage rating (Vn) 250V ac
 Breaking capacity 1500A @ Vn, Cos φ = 0.7 to 0.8

204522

Rating	Order Code	Price Each			
		10+	250+	500+	1K+
100mA	112-3097	40.00	36.00	34.00	33.00
250mA	112-3101	36.00	32.00	31.00	30.00
500mA	112-3106	13.00	12.00	11.00	10.00
630mA	112-3109	13.00	12.00	11.00	10.00
800mA	112-3110	13.00	12.00	11.00	10.00
1A	112-3100	11.00	10.00	9.00	8.00
2A	112-3102	11.00	10.00	9.00	8.00
3.15A	112-3103	11.00	10.00	9.00	8.00
4A	112-3104	11.00	10.00	9.00	8.00
5A	112-3107	11.00	10.00	9.00	8.00
6.3A	112-3108	11.00	10.00	9.00	8.00
8A	112-3111	11.00	10.00	9.00	8.00
10A	112-3098	11.00	10.00	9.00	8.00

Quick Blow (F) Glass

20 x 5mm Fuses MCF05G



Complies with IEC127 Part 2 Sheet II, DIN41661 and BS4265

Mfrs. List No. MCF05G + Rating

Current Rating	Order Code	Price Each				
		10+	100+	500+	1K+	+
100mA	112-3167	18.00	17.00	16.00	15.00	--
125mA	112-3169	18.00	17.00	16.00	15.00	--
160mA	112-3170	18.00	17.00	16.00	15.00	--
200mA	112-3173	18.00	17.00	16.00	15.00	--
250mA	112-3174	18.00	17.00	16.00	15.00	--
315mA	112-3177	18.00	17.00	16.00	15.00	--
400mA	112-3179	7.00	7.00	6.00	4.00	--
500mA	112-3182	7.00	7.00	6.00	4.00	--
630mA	112-3185	7.00	7.00	6.00	4.00	--
800mA	112-3186	7.00	7.00	6.00	4.00	--
1A	112-3171	7.00	7.00	6.00	4.00	--
1.25A	112-3164	7.00	7.00	6.00	4.00	--
1.6A	112-3165	7.00	7.00	6.00	4.00	--
2A	112-3175	7.00	7.00	6.00	4.00	--
2.5A	112-3172	7.00	7.00	6.00	4.00	--
3.15A	112-3176	7.00	7.00	6.00	4.00	--
4A	112-3181	7.00	7.00	6.00	4.00	--
5A	112-3183	7.00	7.00	6.00	4.00	--
6.3A	112-3184	7.00	7.00	6.00	4.00	--
8A	112-3187	7.00	7.00	6.00	4.00	--
10A	112-3168	7.00	7.00	6.00	4.00	--

Fuses, Circuit Breakers & Consumer Units

19

Compliant
 Non-compliant
 + Limited stock - RoHS replacement available
RoHS