

**BS3G210 Type A**  
**7/0.15mm (0.124mm<sup>2</sup>) 26 AWG**

Maximum outside dia. 1.05mm Current rating 4A  
Voltage rating 300V Operating temperature -50°C to +190°C (flexing environment)  
-75°C to +200°C (static environment)

**25m Reels**

Colour	Order Code	Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	322-0850	Red	322-0862	White	322-0874	Pink	322-0886
Blue	322-0898	Yellow	322-0904	Green	322-0916		

**100m Reels**

Colour	Order Code	Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	322-0928	Red	322-0930	White	322-0941	Pink	322-0953
Blue	322-0965	Yellow	322-0977	Green	322-0989		

		Price Per Reel			
		1+	5+	10+	25+
25m All Colours					
100m All Colours					

**BS3G210 Type A**  
**7/0.2mm (0.22mm<sup>2</sup>) 24 AWG**

Maximum outside dia. 1.2mm Current rating 6A  
Voltage rating 300V Operating temperature -50°C to +190°C (flexing environment)  
-75°C to +200°C (static environment)

**25m Reels**

Colour	Order Code	Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	322-0990	Red	322-1003	White	322-1015	Pink	322-1027
Blue	322-1039	Yellow	322-1040	Green	322-1052		

**100m Reels**

Colour	Order Code	Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	322-1064	Red	322-1076	White	322-1088	Pink	322-1090
Blue	322-1106	Yellow	322-1118	Green	322-1120		

		Price Per Reel			
		1+	5+	10+	25+
25m All Colours					
100m All Colours					

**BS3G210 Type A**  
**19/0.15mm (0.338mm<sup>2</sup>) 22 AWG**

Maximum outside dia. 1.36mm Current rating 8A  
Voltage rating 300V Operating temperature -50°C to +190°C (flexing environment)  
-75°C to +200°C (static environment)

**25m Reels**

Colour	Order Code	Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	322-1131	Red	322-1143	White	322-1155	Pink	322-1167
Blue	322-1179	Yellow	322-1180	Green	322-1192		

**100m Reels**

Colour	Order Code	Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	322-1209	Red	322-1210	White	322-1222	Pink	322-1234
Blue	322-1246	Yellow	322-1258	Green	322-1260		

		Price Per Reel			
		1+	5+	10+	25+
25m All Colours					
100m All Colours					

**BS3G210 Type A**  
**19/0.20mm (0.597mm<sup>2</sup>) 20 AWG**

Maximum outside dia. 1.6mm Current rating 11A  
Voltage rating 300V Operating temperature -50°C to +190°C (flexing environment)  
-75°C to +200°C (static environment)

**25m Reels**

Colour	Order Code	Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	322-1271	Red	322-1283	White	322-1295	Pink	322-1307
Blue	322-1313	Yellow	322-1325	Green	322-1337		

**100m Reels**

Colour	Order Code	Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	322-1349	Red	322-1350	White	322-1362	Pink	322-1374
Blue	322-1386	Yellow	322-1398	Green	322-1404		

		Price Per Reel			
		1+	5+	10+	25+
25m All Colours					
100m All Colours					

**BS3G210 Type B**  
**7/0.20mm (0.22mm<sup>2</sup>) 24 AWG**

Maximum outside dia. 1.2mm Current rating 6A  
Voltage rating 600V Operating temperature -50°C to +190°C (flexing environment)  
-75°C to +200°C (static environment)

**25m Reels**

Colour	Order Code	Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	322-1416	Red	322-1428	White	322-1430	Pink	322-1441
Blue	322-1453	Yellow	322-1465	Green	322-1477		

**100m Reels**

Colour	Order Code	Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	322-1489	Red	322-1490	White	322-1507	Pink	322-1519
Blue	322-1520	Yellow	322-1532	Green	322-1544		

		Price Per Reel			
		1+	5+	10+	25+
25m All Colours					
100m All Colours					

**BS3G210 Type B**  
**19/0.15mm (0.338mm<sup>2</sup>) 22 AWG**

Maximum outside dia. 1.35mm Current rating 8A  
Voltage rating 600V Operating temperature -50°C to +190°C (flexing environment)  
-75°C to +200°C (static environment)

**25m Reels**

Colour	Order Code	Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	322-1556	Red	322-1568	White	322-1570	Pink	322-1581
Blue	322-1593	Yellow	322-1600	Green	322-1611		

**100m Reels**

Colour	Order Code	Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	322-1623	Red	322-1635	White	322-1647	Pink	322-1659
Blue	322-1660	Yellow	322-1672	Green	322-1684		

		Price Per Reel			
		1+	5+	10+	25+
25m All Colours					
100m All Colours					

**BS3G210 Type B**  
**19/0.2mm (0.597mm<sup>2</sup>) 20 AWG**

Maximum outside dia. 1.6mm Current rating 11A  
Voltage rating 600V Operating temperature -50°C to +190°C (flexing environment)  
-75°C to +200°C (static environment)

**25m Reels**

Colour	Order Code	Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	322-1696	Red	322-1702	White	322-1714	Pink	322-1726
Blue	322-1738	Yellow	322-1740	Green	322-1751		

**100m Reels**

Colour	Order Code	Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	322-1763	Red	322-1775	White	322-1787	Pink	322-1799
Blue	322-1805	Yellow	322-1817	Green	322-1829		

		Price Per Reel			
		1+	5+	10+	25+
25m All Colours					
100m All Colours					

**BS3G210 Type B**  
**19/0.25mm (0.933mm<sup>2</sup>) 18 AWG**

Maximum outside dia. 1.85mm Current rating 15A  
Voltage rating 600V Operating temperature -50°C to +190°C (flexing environment)  
-75°C to +200°C (static environment)

**25m Reels**

Colour	Order Code	Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	322-1830	Red	322-1842	White	322-1854	Pink	322-1866
Blue	322-1878	Yellow	322-1880	Green	322-1891		

**100m Reels**

Colour	Order Code	Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	322-1908	Red	322-1910	White	322-1921	Pink	322-1933
Blue	322-1945	Yellow	322-1957	Green	322-1969		

		Price Per Reel			
		1+	5+	10+	25+
25m All Colours					
100m All Colours					

continued