

Commercial 'D' Range

Economy 'D' (Formed Pin)

McMurdo

- Solder bucket, right angled and PCB termination styles
- Solder bucket and 90° contacts are stamped and formed
- 90° style features a 2.54mm spacing between contact rows and screwlocks
- Suitable for applications in instrumentation, computer interfacing, process control and professional electrical equipment

Contact rating	5A @ 70°C	Housing	Steel, yellow passivate over zinc plating
Contact resistance	15mΩ max	Insulator	White or black two piece polyester, UL94V-0
Working voltage	500V dc/ac peak	Contacts	Formed copper alloy, gold over nickel plating
Temperature range	-55°C to +105°C	Terminations	Solder bucket - tinned PCB - gold plated
Mating cycles	100		

CS42

Solder Bucket

McMurdo



Mftrs. List No. SDE9P = 150-808, SDA15P = 150-809, SDB25P = 150-810, SDC37P = 150-811
SDE9S = 150-812, SDA15S = 150-813, SDB25S = 150-814, SDC37S = 150-815


CS43

Order Multiple=5

No. of Ways	Order Code	5+	25+	100+	250+	500+	1000+
Plugs							
9	150-808						
15	150-809						
25	150-810						
37	150-811						
Sockets							
9	150-812						
15	150-813						
25	150-814						
37	150-815						

90° PCB

McMurdo



Mftrs. List No. SDE9PN = 150-816, SDA15PN = 150-817, SDB25PN = 150-818, SDC37PN = 150-819
SDE9SN = 150-820, SDA15SN = 150-821, SDB25SN = 150-822, SDC37SN = 150-823

CS44

No. of Ways	Order Code	1+	25+	100+	250+	500+	1000+
Plugs							
9	150-816						
15	150-817						
25	150-818						
37	150-819						
Sockets							
9	150-820						
15	150-821						
25	150-822						
37	150-823						

90° PCB with Screwlocks

McMurdo



Mftrs. List No. SDES9PN = 150-710, SDAS15PN = 150-711, SDBS25PN = 150-712
SDCS37PN = 150-713, SDES9SN = 150-714, SDAS15SN = 150-715
SDBS25SN = 150-716, SDCS37SN = 150-717

CS45

No. of Ways	Order Code	1+	25+	100+	250+	500+	1000+
Plugs							
9	150-710						
15	150-711						
25	150-712						
37	150-713						
Sockets							
9	150-714						
15	150-715						
25	150-716						
37	150-717						

Straight PCB (Turned Pin)

McMurdo



Mftrs. List No. SDE9POL = 150-718, SDA15POL = 150-719, SDB25POL = 150-720, SDC37POL = 150-721, SDE9SOL = 150-722, SDA15SOL = 150-723, SDB25SOL = 150-724, SDC37SOL = 150-725

CS46

No. of Ways	Order Code	1+	25+	100+	250+	500+	1000+
Plugs							
9	150-718						
15	150-719						
25	150-720						
37	150-721						
Sockets							
9	150-722						
15	150-723						
25	150-724						
37	150-725						

'Solda' D (Formed Pin)

ITT Cannon



- A quality range of formed contact style solder bucket 'D' connectors
- Fully mateable and suitable for use with all standard 'D' range connectors and accessories

Contact rating	3A @ 25°C	Housing	Steel, yellow chromate over zinc plating
Contact resistance	20mΩ max	Insulator	Monobloc polyester, UL94V-0
Working voltage	350V dc/ac peak	Contacts	Formed copper alloy, gold over nickel plating
Temperature range	-55°C to +125°C		
Mating cycles	100		

FOR TIN & DIMPLE SOLDA 'D' SEE PAGE 461

CS48

No. of Ways	Mftrs. List No.	Order Code	1+	25+	100+	250+	500+	1000+
Solder Bucket Plugs								
9	ADE9P	315-126						
15	ADA15P	315-138						
25	ADB25P	315-140						
37	ADC37P	315-151						
Solder Bucket Sockets								
9	ADE9S	315-163						
15	ADA15S	315-175						
25	ADB25S	315-187						
37	ADC37S	315-199						
Straight PCB Plugs								
9	—	105-521						
25	—	105-523						
Straight PCB Sockets								
9	—	105-525						
25	—	105-527						