


High Density 'D' Tin and Dimple — Continued

Crimp Housings, Formed Contacts and Tooling

McMurdo



Pin contact Socket contact


Open crimp conductor diameters
24/28 AWG, 0.08—0.22mm², 7/0.2 or 10/0.1

Mfrs. List No.	HDEC15PTD = 151-210, HDEC15ST = 151-213, MP642-06 = 151-222, MP643-15 = 151-225,	HDAC26PTD = 151-211, HDAC26ST = 151-214, MP642-05 = 151-223, MP600-DHD = 151-226,	HDBC44PTD = 151-212, HDBC44ST = 151-215, MP643-16 = 151-224, MP601HD = 151-227
----------------	---	--	---

CS80

No. of Ways	Order Code	Price Each				
		1+	25+	50+	100+	250+
Plug Housing						
15	.151-210					
26	.151-211					
44	.151-212					
Socket Housing						
15	.151-213					
26	.151-214					
44	.151-215					
Mating Cycles		Price Per Pack				
		1+	10+			
Pin Contacts (100 Per Pack)						
50	.151-222					
200	.151-223					
Socket Contacts (100 Per Pack)						
50	.151-224					
200	.151-225					
Ratchet Crimp Tool		Price Each				
151-226.						
Insertion/ Extraction Tool		Price Each				
151-227		10.5				

90° PCB Sockets – with Boardlocks and Screwlocks **McMurdo**




Mfrs List No. HDEX15SNT = 210-535, HDAX26SNT = 210-547, HDBX44SNT = 210-559

CS81

No. of Ways	Order Code	Price Each				
		1+	25+	50+	100+	250+
15	.210-535					
26	.210-547					
44	.210-559					

Straight PCB Plugs (Turned Pin) **McMurdo**



Mfrs. List No. HDE15POLTD = 151-216, HDA26POLTD = 151-217, HDB44POLTD = 151-218


CS82

No. of Ways	Order Code	Price Each				
		1+	25+	50+	100+	250+
15	.151-216					
26	.151-217					
44	.151-218					

Plastic 'D'

Plastic 90° PCB

ELCO



Contact rating	1A	Housing	Polyester, UL94V-0
Contact resistance	5m Ω max	Contacts	Phosphor bronze, gold over nickel plating
Working voltage	350V dc/ac peak		
Temperature range	-55°C to 105°C		
Mating cycles	50		

CS473

No. of Ways	Mfrs. List No.	Order Code	Price Each				
			1+	25+	50+	100+	250+
Plugs							
9	108343009000001	.637-531					
15	108343015000001	.637-543					
25	108343025000001	.637-555					
37	108343037000001	.637-567					
Sockets							
9	208343009000001	.637-579					
15	208343015000001	.637-580					
25	208343025000001	.637-592					
37	208343037000001	.637-609					

Micro-Miniature 'D' Connectors

Metal and Plastic Shell

Cinch


- A high quality, high density range of environmental connectors
- Lightweight, durable shell
- Twisted pin contact
- Ideal for industrial application where size and mateability are important
- Metal and plastic version, complete with dust cover

Current rating	3A	Housing (metal body)	Aluminium alloy
Working voltage	200V dc/ac peak		Cadium plated
Proof voltage	600V dc/ac peak		Yellow chromate
Contact resistance	≤ 8mΩ	(plastic body)	Thermoplastic polyester
Insulation resistance	5000MΩ		G.F UL94V-0
Temperature range	-55°C to 125°C	Insulator	Diallyl phthalate G.R
Mating cycles	500	Contact material	Copper alloy, 50µ gold plated

CS344

Metal Shell - Flying Leads

Cinch



- 450mm colour coded PTFE flying leads

CS342

No. of Ways	Mfrs. List No.	Order Code	Price Each				
			1+	10+	25+	100+	250+
Plug							
9	DCCM-9P6E518.OB	.750-591					
15	DCCM-15P6E518.OB	.750-608					
25	DCCM-25P6E518.OB	.750-610					
37	DCCM-37P6E518.OB	.750-621					
51	DCCM-51P6E518.OB	.750-633					
Socket							
9	DCCM-9S6E518.OB	.750-645					
15	DCCM-15S6E518.OB	.750-657					
25	DCCM-25S6E518.OB	.750-669					
37	DCCM-37S6E518.OB	.750-670					
51	DCCM-51S6E518.OB	.750-682					
2 Per Pack			Price Per Pack				
			1+	10+	25+	100+	250+
Jack posts							
M83513/5-07			.750-797				
Jack screws							
M835135-05			.750-803				

Plastic Shell - Flying Leads

Cinch



- 450mm Colour coded PTFE flying leads