

- 3 pole switches, 22.5 dia. single hole mounting
- Aux. contacts can be added to switches - max. of 2 side mounting blocks, with 1n/o+1n/c contact per block
- IP65 protection
- Black/silver handle - Main Switch
- Red/yellow handle - Main/Emergency - Off Switch
- Padlockable in 'Off' position
- Complies with IEC 60947-3 & IEC 60204-1

Rated Operational Current, AC21A (max. 690v)	Rated Operational Power, AC23A 380-440v, 3ph	Rated Operational Power, AC3 380-440v, 3 ph
20A	5.5 kW	3.7 kW
25A	7.5 kW	5.5 kW
32A	11 kW	7.5 kW


CTL376

Rating, AC21A	Order Code	Price Each		
		1+	5+	10+
Main Switch				
20A	341-3123			
25A	341-3135			
32A	341-3147			
Main/Emergency-Off Switch				
20A	341-3093			
25A	341-3100			
32A	341-3111			
Aux Contact Blocks				
20A-32A	341-3627			

Main/Emergency-Off Switch Front Panel Mounting



New




- 3 and 4 pole switches
- Aux. contacts can be side mounted (max of 2) 1n/o+1n/c contact per block
- IP65 protection
- Red/yellow handle - padlockable in 'Off' position
- Complies with IEC 60947-3 & IEC 60204-1

Rated Operational Current, AC21A (max. 690v)	Rated Operational Power, AC23A 380-440v, 3ph	Rated Operational Power, AC3 380-440v 3ph
20A	5.5kW	3.7kW
25A	7.5kW	5.5kW
32A	11kW	7.5kW
40A	15kW	11kW
63A	22kW	18.5kW
80A	30kW	22kW
100A	37kW	30kW

CTL373

Rating, AC21A	Order Code	Price Each		
		1+	5+	10+
3 Pole				
20A	341-3159			
25A	341-3160			
32A	341-3172			
40A	341-3184			
63A	341-3196			
80A	341-3202			
100A	341-3214			
4 Pole				
20A	341-3378			
25A	341-3380			
32A	341-3391			
40A	341-3408			
63A	341-3410			
80A	341-3421			
100A	341-3433			
Aux. Contact Blocks				
For 20A-32A	341-3597			
For 40A-63A	341-3603			
For 80A-100A	341-3615			

Main/Emergency-Off Switch Base Mounting, Door Interlock



Rating (Amps)	Switch mounting depth - back plate to inside of door min/max
20	91/174mm
25/32	85/175mm
40/63	96/193mm
80/100	103/198mm

- 3 and 4 pole switches
- Aux. contacts can be side mounted (max of 2) 1n/o + 1n/c contact per block
- IP65 protection
- Red/yellow handle - padlockable in 'Off' position
- Door interlock in 'On' position
- Metal operating shaft
- Complies with IEC 60947-3 & IEC 60204-1

Rated Operational Current, AC21A (max. 690v)	Rated Operational Power, AC23A 380-440v, 3ph	Rated Operational Power, AC3 380-440v, 3 ph
20A	5.5 kW	3.7 kW
25A	7.5 kW	5.5 kW
32A	11 kW	7.5 kW
40A	15 kW	11 kW
63A	22 kW	18.5 kW
80A	30 kW	22 kW
100A	37 kW	30 kW

CTL375

Rating, AC21A	Order Code	Price Each		
		1+	5+	10+
3 Pole				
20A	341-3263			
25A	341-3275			
32A	341-3287			
40A	341-3299			
55A	341-3305			
80A	341-3317			
100A	341-3329			
4 Pole				
20A	341-3482			
25A	341-3494			
32A	341-3500			
40A	341-3512			
63A	341-3524			
80A	341-3536			
100A	341-3548			
Aux. Contact Blocks				
For 20A-32A	341-3627			
For 40A-63A	341-3639			
For 80A-100A	341-3640			

Load Break Switches

Enclosed Load Break Switches IP30

ABB Control Limited



- Is able to be Padlocked in the OFF position
- Door is unable to be Opened in the ON Position
- Local Isolator
- Main switch
- Maintenance, & Motor Control Switch.
- All aspects of Safety Adhered to whilst in Use

ABB SAFELINE is a of ABB Control

AC21 400V	AC23 400V	No of Poles	IP Rating	Description	Mftrs List No
16	11	3	30	16 amp 3 Pole	OT16E3GB30
25	16	3	30	25 amp 3 Pole	OT25E3GB30
32	21	3	30	32 amp 3 Pole	OT32E3GB30

PRO390

A	Order Code	Price Each					
		1+	2+	5+	10+	20+	50+
16	718-7452						
25	718-7464						
32	718-7476						

continued