# **Industrial Safety Matting — continued**

#### Cobamat Standard Duty







- The industrial environments' general duckboarding
- Allows swarf to drop through the holes 

  Reduces noise Provides smooth, safe surface to work
- Reduces fatigue when standing for
- long periods

Manufactured	from	flexible	PVC	extru-
sion				

- Reversible
- Prevents slipping in wet and oily condi-
- Available in a range of widths


Hole size: 22x22mm Length: 5m rolls

Width	Colour	Order Code	Width	Colour	Order Code
0.6m	Black	708-2885	0.9m	Black	708-2927
0.6m	Blue	708-2897	0.9m	Blue	708-2939
0.6m	Red	708-2903	0.9m	Red	708-2940
0.6m	Green	708-2915	0.9m	Green	708-2952
					HS1022

_						110102	
	Price Per Roll						
Order Code	1+	3+	6+	12+	24+	48+	
708-2885							
708-2897							
708-2903							
708-2915							
708-2927							
708-2939							
708-2940							
708-2952							

## Solid Vinyl Matting





Upper diamond surface is designed to create a vacuum to hold the matting down

Flame-retardant and Chemical-resistant

Order Code

708-4870

WHS084	708-4882	1.2m	10.0m		Service of	- 4
80+	40+	er Roll 20+	Price P	5+	1+	Order Code 708-4870 708-4882

Length


5.0m

# **Anti-Fatigue Matting for wet or dry areas**

### **Anti-Fatigue Matting for Wet or Dry Areas High Duty Interlocking Tiles**



New



Individual components made from a high quality rubber

Width

1.2m

- Can be interlocked to provide coverage of any desired length in both 0.9m and 1.5m widths
- Raised circular surface offers slip resistance in all directions
- Holes allow drainage of liquids and dehris

Thickness: 12.5mm Colour: Black

Description	Length	Width	Order Code
dged all round	1.5m	0.9m	353-0620
dged 2 long and 1 short side	1.5m	0.9m	353-0632
dged 2 sides long	1.5m	0.9m	353-0644
dged 2 short and 1 long side	1.5m	0.9m	353-0656
dged 2 short sides	1.5m	0.9m	353-0668

						потиг	
	Price Each						
Order Code	1+	5+	10+	20+	40+	80+	
353-0620							
353-0632							
353-0644							
353-0656							
353-0668							

### **Anti-Fatigue Matting for Wet or Dry Areas Fatigue Step Black Tiles**



New





0.9m x 0.9m Thickness: Colour: 16mm Black with Black or Yellow bevelled edges and corner

Description	Order Code
Fatigue Step Black	353-0747
Black Bevelled Edge	353-0759
Black Connector	353-0760
Black Corner	353-0772
Yellow Edging	353-0784
Yellow Corner	353-0796

- hard-wearing rubber Soft, yet resilient material offers fatigue relief properties
- Slip resistant
- Versatile single units interlock to fit any area
- High drainage properties
- Optional extras: corner units, bevelled edge units and connectors

	Price Each					
Order Code	1+	5+	10+	20+	40+	80+
353-0747						
353-0759						
353-0760						
353-0772						
353-0784						
353-0796						

### **Anti-Fatigue Matting for Wet or Dry Areas** Solid Fatigue Step Tiles



New

HS1024



- Manufactured from extremely durable rubber
- Designed to offer the highest comfort factor
- Tiles interlock to form mat size and shape of your choice
- Heat resistant, withstands molten glass
- Ideal for use where employees are standing for prolonged periods
- Optional extras: Corner units, bevelled edges and connectors

