

## Dial Thickness Gauge



- Lightweight and easy to handle
- Gauge is mounted in a hand contoured frame with a thumb release mechanism
- For fast direct measurement
- Used to measure thickness of paper, cellophane, plastic film and metal plates

Range	Grads.	Throat Depth	Top Anvil	Bottom Anvil
0-10mm	0.01mm	100mm	10mm	11mm

TE081

Range	Order Code	1+	3+	6+	12+	24+
0-10mm	724-5774					

## Thickness Gauge



- Compact pocket sized Digimatic thickness gauge
- Inch/metric conversion
- Measuring faces are hardened, ground and lapped
- Ideal for measuring paper, leather, plastic, sheet metal and film

Resolution	Range	Accuracy	Mftrs. List No.
0.01mm 0.00005"	0-12mm 0-05"	±0.02mm ±0.001mm	700-118

MAI138

Order Code	1+	3+	6+	12+
321-6342				

Mitutoyo

New

## Stands

### Dial Gauge Stand



- Gauge stand for dial indicators digimatic indicators, linear gauges
- Indicator can be stem or lug mounted
- 3/8" clamp stem
- Optional reducing sleeve required for 8mm stems

Capacity	100mm
Fine adjustment	1mm

MAI139

	Mftrs. List No.	Order Code	1+	3+	6+	12+
Stand	2003	321-6317				
Sleeve	206983	321-6329				

Mitutoyo

New

## Magnetic Bases

### Magnetic Bases



- Sets include Nogaflex articulated arm with fine adjustment
- Can be locked in any position
- Includes lever dial test indicator
- Arm made from steel, polished and chrome plated
- Dial gauge clamp for dovetail and stem clamping up to 3/8" Ø
- Available with switchable or permanent base
- Supplied in plastic carry case

L = 140, W = 25, H = 125	Lever Indicator	Dial Ø	Graduation	Reading	Range	Stylus Length
		36	0.01	0-40-0	0-8	26.3

MAI91

	Mftrs. List No.	Order Code	1+	3+	6+	12+
Switchable	NF1200	716-1426				
Permanent	NF1300	716-1438				

NOGA

## Magnetic Base



- Segmented snake arm can be locked in any position
- Provides clamping for plunger and lever indicators between 1/8" and 1/2" Ø
- Fitted with a powerful magnetic base which has 80 kg pull

Indicator supplied separately  
For indicators see page 1027

## LINEAR TOOLS

MAI90

Mftrs' List No.	Order Code	1+	3+	6+	12+
MB-SX	716-1384				

## Magnetic Stand



- Magnetic base stand suitable for most Mitutoyo dial indicators
- The indicator can be lug or stem mounted (stem 8mm dia.)
- Powerful magnetic base has an on/off lever preventing damage to delicate surfaces

Overall height = 220mm,  
Maximum reach = 145mm

MAI1

Mftrs. List No.	Order Code	1+	3+	6+	12+
7010S	457-450				

## Flexigrip Major



- A heavy-duty clamp fitted to a uni-joint arm for versatile gauging applications
- Detachable clamp can be used independently from arm
- Suitable for stands and workholding
- Holds stem sizes 8mm/Ø


Indicator sold separately

MAI66

Mftrs' List No.	Order Code	1+	3+	6+
7019-001	715-7095			

## Centre Finders

### Edge and Centre Finder



- Accurately and quickly locates centre of round bar work pieces
- 3/8" shank fits into drill or collet chuck
- Align pointer on shank to obtain centre line of round bar up to 55mm

MAI100

Mftrs' List No.	Order Code	1+	3+	6+	12+
4200-100	716-2339				

continued