## Security - Access Control, CCTV & Warning Devices Farnell

#### Indoor Pan and Tilt Head DENNARD The type 490 pan and tilt head **Recent** is ideal for use with pavloads up to 7kg, without the need for counter balance weights or springs. Fitted with low speed synchronous motors, the 490 is virtually silent in operation. All units have internal limit switches that are readily adjusted upon removal of the rear cover. The unit is robustly constructed from aluminium alloy castings, powder coated and stoved with plated steel shafts, supplied with a 1.5m flying lead and is suitable for upright or inverted operation. Elegantly styled • 4.4°/sec. tilt speed Payloads up to 7kg Internal limit switches õ 2000 hours lamp life 6.1°/sec. pan speed $\begin{array}{c} 20^{\circ}-360^{\circ} \\ \pm 10^{\circ}-\pm 180^{\circ} \end{array}$ Pan movement Tilt torque 67ka cm Backlash 0.5° maximum Tilt movement Pan torque 50ka cm Weight 4ka SSW669 **Price Each** Order Code 1+ 4+ 490 Pan & Tilt Head 354-4394 642B Pan & Tilt Bracket 354-4400 **External Pan and Tilt Head** DENNARD The type 2000 pan and tilt head comes with conventional externally adjustable Addition limit switches, ease of maintenance and servicing have been significantly improved over conventional pan and tilt designs. All external fixings are the same size, and can be operated upright or inverted. Aesthetically styled Payloads of up to 20kg Pressure die cast construction • Weatherproof to IP66 Anti-backlash pan gearing $5^{\circ} - 350^{\circ} \pm 20^{\circ} - \pm 90^{\circ}$ Pan movement Tilt torque 400kg cm Tilt movement Backlash 0.5° maximum Pan torque 150kg cm Weight 7.5kg SSW665 **Price Each** Order Code 1+ 4+ 490 Pan & Tilt Head 354-4291 435 Pan & Tilt Bracket 354-4308 Corner adapt. for Bracket 354-4310 Internal CCD Camera Brackets Recent Addition These are high quality, unobtrusive CCD camera brackets, which come complete with full swivel joints, allowing maximum surveillance Powder coated 4" or 6" length arm Constructed from 18swg box section SSW670 Price Each Order Code 1+ 5+ 4" Small CCD Bracket 354-2440 6" Small CCD Bracket 354-2452 **Internal CCD Camera Brackets Cecent** This is a substantial camera bracket for the larger size CCTV camera, complete with a swivel joint, which allows accurate positioning of the camera. thousands of Best Value products. Powder coated 9" length arm 4" x 4" fixing plate Constructed from 16swg box section SSW671

Price Each

1+

5+

# **Infrared Lamps**

## Microlight Illuminators



# These microlights have been

Recent Addition designed to provide a low power, low cost, high performance infrared illuminator, at a size complementing CCD camera equipment

DENNARD


These units are constructed from aluminium alloy, powder coated and stoved with stainless fittings. Silicone O-ring sealing and one metre, high temperature outdoor cable, factory fitted, offers

weatherproofing to BS.EN.60529 level IP65. Average lamp life is 2000 hours with specially modified 12V 50mm tungsten halogen lamps. Please see below for suitable power supply, as these lamps require a dedicated supply.

- 20W, 50W, 75W
- Narrow or medium beam angle Weatherproof to IP65

Please Note: When fitting replacement lamps, care must be taken not to touch the filament envelope or reflective inner face as this will be detrimental to the lamp life SSW672

			33W
		Price Each	
	Order Code	1+	4+
Illuminators			
20W Narrow	354-2580		
20W Medium	354-2592		
50W Narrow	354-2609		
20W Medium	354-2610		
75W Narrow	354-2622		
75W Medium	354-2634		
Power Supplies			
PSU for 20 or 50W	354-2646		
PSU for 75W	354-2658		
PSU with Photoswitch for 20 or 50W	354-2660		
PSU with Photoswitch for 75W	354-2671		
Spare Bulbs			
20W Narrow Spare Bulb	354-2683		
20W Medium Spare Bulb	354-2695		
50W Narrow Spare Bulb	354-2701		
50W Medium Spare Bulb	354-2713		
75W Narrow Spare Bulb	354-2725		
75W Medium Spare Bulb	354-2737		



9" Camera Bracket

**Order Code** 

354-2464