

## Ersa Soldering/De-Soldering Stations

### Soldering Station Analog 60



- Precise Resistronic temperature control
- Temperature adjustable between 150°C and 450°C
- LED indicator
- Heat up time 60s
- Ergonomic design
- Supplied with UK style and European Schuko power cord



**New**

Station contain supply unit, soldering iron with tip 832CD and support

|                               |                             |
|-------------------------------|-----------------------------|
| Technical data supply unit    |                             |
| Power Supply:                 | 230Vac @ 50/60Hz            |
| Output:                       | 60W                         |
| Temperature Range:            | 150°C to 450°C (continuous) |
| Technical data soldering iron |                             |
| Supply:                       | 24Vac                       |
| Weight:                       | 60g                         |
| Heat up time:                 | 60s                         |
| Length Connection lead:       | 1.5m high flexible          |

SOL303

|                    | Order Code | Price Each |
|--------------------|------------|------------|
| Station Analog 60  | 875-170    | 1+         |
| Spare Heat Element | 875-181    |            |

### Soldering Station Analog 60A/80A



- Precise Resistronic temperature control
- Temperature adjustable between 150°C and 450°C
- LED indicator
- 80W and 60W version available
- Heat up time 40s 80W version, 60s 60W version
- Ergonomic design



**New**

- ESD safe
- Supplied with UK style and European Schuko power cord

Station contains supply unit, soldering iron with tip 832CD and support

|                               |                                |
|-------------------------------|--------------------------------|
| Technical data supply unit    |                                |
| Power Supply:                 | 230Vac @ 50/60Hz               |
| Output:                       | Analog 60A 60W, Analog 80A 80W |
| Temperature Range:            | 150°C to 450°C (continuous)    |
| Technical data soldering iron |                                |
| Supply:                       | 24Vac                          |
| Weight:                       | 52g                            |
| Heat up time:                 | Analog 60A 60S, Analog 80A 40S |
| Length Connection lead:       | 1.5m high flexible             |

SOL304

|                            | Order Code | Price Each |
|----------------------------|------------|------------|
| Station Analog 60A         | 875-193    | 1+         |
| Station Analog 80A         | 875-211    |            |
| <b>Spare Heat Elements</b> |            |            |
| For Analog 60A             | 875-200    |            |
| For Analog 80A             | 875-223    |            |

### Soldering Station SMT Unit 60A



- Soldering and desoldering station
- Suitable for soldering, SMD soldering, Desoldering and Repair
- Electronic temperature control
- LED operation indicator
- Supplied with UK style and European Schuko power cord



**New**

Station contains supply unit, soldering iron micro tool with tip 212BD, thermal tweezer pincette 40 with two tips 422ED and 2 supports

|  |                             |
|--|-----------------------------|
| Technical data supply unit                 |                             |
| Power supply:                              | 230Vac @ 50/60Hz            |
| Output:                                    | 60W                         |
| Temperature range:                         | 150°C to 400°C (Continuous) |
| Technical data soldering iron micro tool   |                             |
| Supply:                                    | 24Vac                       |
| Weight:                                    | 25g                         |
| Heat up time:                              | 50s                         |
| Length connection lead:                    | 1.2m high flexible          |
| Technical data thermal tweezer pincette 40 |                             |
| Supply:                                    | 24Vac                       |
| Weight:                                    | 75g                         |
| Heat up time:                              | 60s                         |
| Length connection lead:                    | 1.2m high flexible          |

SOL307

| Mfrs. List no.       | Order Code | Price Each |
|----------------------|------------|------------|
| Station SMT Unit 60A | 875-338    | 1+         |

### Soldering Station Twin 80A



- Two soldering tools can be used simultaneously and controlled independently
- Electronic temperature control
- ESD safe
- Supplied with UK style and European Schuko power cord



**New**

Station contains supply unit, soldering iron micro tool with tip 212BD, soldering iron ergonomic tool with tip 832CD and 2 supports

|  |                             |
|--|-----------------------------|
| Technical data supply unit                   |                             |
| Power supply:                                | 230Vac @ 50/60Hz            |
| Output:                                      | 80W                         |
| Temperature range:                           | 150°C to 400°C (continuous) |
| Technical data soldering iron micro tool     |                             |
| Supply:                                      | 24Vac                       |
| Weight:                                      | 50g                         |
| Heat up time:                                | 50s                         |
| Length connection lead:                      | 1.2m high flexible          |
| Technical data soldering iron ergonomic tool |                             |
| Supply:                                      | 24Vac                       |
| Weight:                                      | 52g                         |
| Heat up time:                                | 60s                         |
| Length connection lead:                      | 1.2m high flexible          |

SOL308

| Mfrs. List no.                | Order Code | Price Each |
|-------------------------------|------------|------------|
| Station Micro Con 60iA        | 875-340    | 1+         |
| <b>Spare Heating Elements</b> |            |            |
| Ergonomic Tool                | 875-200    |            |
| Micro Tool                    | 875-351    |            |

### Soldering Station Digital 60A/80A



- Thermocouple temperature control
- Temperature adjustable between 50°C and 450°C
- LED temperature display 3 digit
- LED indicator
- 80W and 60W version available
- Heat up time Digital 60A 12s Digital 80A 40s



**New**

- Ergonomic design
- ESD safe
- Supplied with UK style and European Schuko power cord

Station contains supply unit, soldering iron with tip 612AD (Digital 60A), 832CD (Digital 80A) and support

|                               |                                  |
|-------------------------------|----------------------------------|
| Technical data supply unit    |                                  |
| Power Supply:                 | 230Vac @ 50/60Hz                 |
| Output:                       | Digital 60A 60W, Digital 80A 80W |
| Temperature Range:            | 50°C to 450°C (continuous)       |
| Technical data soldering iron |                                  |
| Supply:                       | 24Vac                            |
| Weight:                       | Digital 60A 50g, Digital 80A 52g |
| Heat up time:                 | Digital 60A 12S, Digital 80A 40S |
| Length Connection lead:       | 1.5m high flexible               |

SOL305

|                            | Order Code | Price Each |
|----------------------------|------------|------------|
| Station Digital 60A        | 875-235    | 1+         |
| Station Digital 80A        | 875-259    |            |
| <b>Spare Heat Elements</b> |            |            |
| For Digital 60A            | 875-200    |            |
| For Digital 80A            | 875-223    |            |

### Soldering Station Micro CON 60iA



- Microprocessor controlled soldering station
- ESD safe
- Fuzzy logic temperature control compensates ambient temperature changes
- Heat up times between 8 and 12s
- Automatic detection of four soldering and desoldering tools



**New**

- Menu driven, 8 pre-set temperatures
- 7 digit LED display
- 4 digit password lockout
- Temperature windows
- Alarm functions
- RS232 interface for remote control through PC software available
- Supplied with UK style and European Schuko power cord