Checker®

Modern Day Replacement for Litmus Paper

Checker® represents the latest generation of lightweight, pocket-sized pH testers to be specially designed and developed by Hanna Instruments. At the cost of a few rolls of pH litmus paper, you can now have the industry's most advanced electronic pH tester. Checker® will supply you with fast and accurate readings on a large Liquid Crystal Display. Simply immerse the probe into your sample and read the pH value. Unlike other pH testers, the Checker® electrode can be changed and any pH electrode of different shape or size can be used. Checker® is also suitable for checking electrodes in pipes and tanks and various other industrial applications.

Order your Checker® according to your needs and the type of electrode you intend to use:

Checker® - Meter with built-in screw connector (without electrode).

Checker® B - Meter with built-in BNC connector (without electrode).

Checker® 1 - Checker® meter, complete with an HI 1270 screw-type, combination, pH electrode (page D25).

For calibration and maintenance solutions see pages E3, E5, E7, E10.

Note: Electrodes for Checker® and Checker® B should be ordered separately. Choose from a wide selection of Hanna glass or epoxy electrodes (see the electrode section).

Some of the Checkers' outstanding features include:

- Large and easy-to-read LCD
- High accuracy with 0.01 pH resolution
- Two point fast and accurate calibration
- Secure single action 'ON/OFF' switch
- Usable with virtually any pH electrode
- Checker® 1 supplied with a rugged epoxy pH electrode
- · Compact size
- Battery life: 3000 hours of continuous use
- Wide range: 0.00 to 14.00 pH
- Replaceable pH electrode



| SPECIFICATIONS | Checker® | Checker® 1 | Checker® B |
|--------------------------|---|----------------------|------------|
| ELECTRODE | optional | HI _. 1270 | optional |
| RANGE | 0.00 to 14.00 pH | | |
| RESOLUTION | 0.01 pH | | |
| ACCURACY | ±0.2 pH | | |
| CALIBRATION | Two point through Offset and Slope trimmers | | |
| TEMPERATURE COMPENSATION | N/A | | |
| ENVIRONMENT | 0 to 50°C (32 to 122°F); 95% RH | | |
| BATTERYTYPE | 2 x 1.4 Volts | | |
| BATTERYLIFE . | 3000 hours of continuous use | | |
| DIMENSIONS | 66 x 50 x 25 mm (2.6 x 2.0 x 1") | | |
| WEIGHT | 63 g (2.2 oz.) | | |