

# CMP BATTERIES STANDBY DIVISION



**Sonnenschein**

14 Gunnels Wood Park,  
Stevenage, Herts,  
SG1 2BH

Telephone : 01438 359090

Telefax : 01438 727684

E-Mail : cmp.standby@btinternet.com

## Fax Transmission

---

**To:** \_\_\_\_\_ **From:** Mike Carrington.

---

**Company:** Farnell **Pages:** 2

---

**Fax:** 0113 279 4279 **Date:** 28 January 1999

---

**Re:** Lithium Transport LTN-065-18-a **CC:** \_\_\_\_\_

---

European and world-wide carrier organisations classify lithium batteries in two categories, non-restricted and restricted. Lithium batteries falling into the non-restricted category can be shipped via any carrier without special requirements.

Lithium batteries are non-restricted if they meet the following requirements.

- Each cell contains no more than 0.5 g of lithium or lithium alloy.
- Each battery pack contains an aggregate quantity of no more than 1 g of lithium or lithium alloy
- Each cell is hermetically sealed
- Batteries are separated from each other in the pack so as to prevent shorting
- Batteries are packed in strong outside packaging (except when installed in electronic devices).

Table 1 indicates the Sonnenschein Lithium Battery models that belong to this category. Lithium Batteries that belong to the restricted category require special care during transportation. The requirements are shown Table 2.

Size	Non-Restricted Types	Restricted Types
Flat cells		
BEL	SL-340	
1/6D	SL-386	
1/10D	SL-389	
Small Cells		
½ AA	SL-350 SL-550 SL-750 SL2350	
2/3 AA	SL-361 SL-561 SL-761 SL2361	
AA	SL-360 SL-560 SL-760 SL2360	
Big Cells		
C		SL-770 SL2770
D		SL780 SL2780
DD		SL-790
Computer Batteries		
Computer-Battery	SL-360/461	
Computer-Battery	SL-360/486	

**Table 1**

Correlation between Sonnenschein Lithium Batteries, and transport categories.

---

The information contained within this facsimile is for use by the intended recipient only. Should this be inadvertently sent to the wrong place please return it to the number shown at the top of the first page.

Class	Limitations and Instructions	Passenger aircraft IATA DGR	Cargo aircraft IATA DGR	Road/Railway transport ADR/RID	Sea Transport IMDG Code
<b>Lithium Batteries</b> UN No. 3090, Class 9	Maximum amount of lithium per cell Maximum amount of lithium per battery pack Maximum amount of lithium per inner packaging Maximum gross weight per package Packing group Packing Instruction Marking	Forbidden	12 g  500 g 500 g 35 kg II 903 Hazard Label Handling Label for cargo only	12 g  500 g 500g 100 kg II Hazard Label	12 g  500 g 500g 250 kg II
<b>Lithium Batteries contained in equipment</b> UN No. 3091, Class 9	Maximum amount of lithium per cell Maximum amount of lithium per battery pack Maximum amount of lithium per any piece of equipment Maximum gross weight per package Packing group Packing Instruction Marking	3 g  125 g 5 kg II 912 Hazard Label	12 g  500 g 5 kg II 912 Hazard Label	12 g  500 g  100 kg II Hazard Label	12 g  500 g  max. 10 batts 250 kg II

**Table 2.**

Transport regulations for lithium batteries falling into the restricted category as per table 1:

Cells containing more than 0.5 g of lithium and battery packs containing more than 1 g of Lithium.

Packaging instruction and lithium contents are available from Sonnenschein Lithium upon request.

The applicable documents are:

ADR: European Agreement concerning the international Carriage of Dangerous Good. by Road

IATA DGR: International Air Transport Association, Dangerous Goods Regulations, 38th Edition, 1 January 1995.

IMDG Code: International Maritime Dangerous Goods Code

RID: International Statutory Order on the Conveyance of Dangerous Goods by Rail

UN: United Nations Recommendations on the Transport of Dangerous Goods, Tests and Criteria.

Mgc/lithium/065-18-a