


## Small Signal Schottky Diodes

### Features

- The SD103 series is a Metal-on-silicon Schottky barrier device which is protected by a PN junction guard ring.
- The low forward voltage drop and fast switching make it ideal for protection of MOS devices, steering, biasing and coupling diodes for fast switching and low logic level applications.
- Other applications are click suppression, efficient full wave bridges in telephone subsets, and blocking diodes in rechargeable low voltage battery systems.
- These diodes are also available in the SOD123 and SOD323 case with type designations SD103AW(S)-V...SD103CW(S)-V, and in the MiniMELF case with type designations LL103A thru LL103C.
- For general purpose applications
- Lead (Pb)-free component
- Component in accordance with RoHS2002/95/EC and WEEE 2002/96/EC



94 9367

### Mechanical Data

**Case:** DO35 Glass case

**Weight:** approx. 125 mg

**Cathode Band Color:** black

**Packaging Codes/Options:**

TR/10 k per 13" reel (52 mm tape), 50 k/box

TAP/10 k per Ammpack (52 mm tape), 50 k/box

### Applications

- HF-Detector
- Protection circuit
- Small battery charger
- AC-DC/DC-DC converters

### Parts Table

| Part   | Type differentiation | Ordering code           | Type Marking | Remarks               |
|--------|----------------------|-------------------------|--------------|-----------------------|
| SD103A | $V_R = 40\text{ V}$  | SD103A-TR or SD103A-TAP | SD103A       | Tape and Reel/Ammpack |
| SD103B | $V_R = 30\text{ V}$  | SD103B-TR or SD103B-TAP | SD103B       | Tape and Reel/Ammpack |
| SD103C | $V_R = 20\text{ V}$  | SD103C-TR or SD103C-TAP | SD103C       | Tape and Reel/Ammpack |

### Absolute Maximum Ratings

$T_{amb} = 25\text{ }^\circ\text{C}$ , unless otherwise specified

| Parameter                             | Test condition | Part   | Symbol    | Value             | Unit |
|---------------------------------------|----------------|--------|-----------|-------------------|------|
| Peak inverse voltage                  |                | SD103A | $V_R$     | 40                | V    |
|                                       |                | SD103B | $V_R$     | 30                | V    |
|                                       |                | SD103C | $V_R$     | 20                | V    |
| Power dissipation (infinite heatsink) |                |        | $P_{tot}$ | 400 <sup>1)</sup> | mW   |
| Single cycle surge 60 Hz sine wave    |                |        | $I_{FSM}$ | 15                | A    |

<sup>1)</sup> Valid provided that leads at a distance of 4 mm from case are kept at ambient temperature

### Thermal Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified

| Parameter                                  | Test condition | Symbol     | Value                       | Unit               |
|--|----------------|------------|-----------------------------|--------------------|
| Thermal resistance junction to ambient air |                | $R_{thJA}$ | 310 <sup>1)</sup>           | K/W                |
| Junction temperature                       |                | $T_j$      | 125 <sup>1)</sup>           | $^{\circ}\text{C}$ |
| Storage temperature range                  |                | $T_{stg}$  | - 55 to + 150 <sup>1)</sup> | $^{\circ}\text{C}$ |

<sup>1)</sup> Valid provided that leads at a distance of 4 mm from case are kept at ambient temperature

### Electrical Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified

| Parameter                 | Test condition   | Part   | Symbol     | Min | Typ. | Max | Unit          |
|---------------------------|--|--------|------------|-----|------|-----|---------------|
| Reverse Breakdown Voltage | $I_R = 50\text{ }\mu\text{A}$                                      | SD103A | $V_{(BR)}$ | 40  |      |     | V             |
|                           |  | SD103B | $V_{(BR)}$ | 30  |      |     | V             |
|                           |  | SD103C | $V_{(BR)}$ | 20  |      |     | V             |
| Leakage current           | $V_R = 30\text{ V}$  | SD103A | $I_R$      |     |      | 5   | $\mu\text{A}$ |
|                           | $V_R = 20\text{ V}$  | SD103B | $I_R$      |     |      | 5   | $\mu\text{A}$ |
|                           | $V_R = 10\text{ V}$  | SD103C | $I_R$      |     |      | 5   | $\mu\text{A}$ |
| Forward voltage drop      | $I_F = 20\text{ mA}$   |        | $V_F$      |     |      | 370 | mV            |
|                           | $I_F = 200\text{ mA}$  |        | $V_F$      |     |      | 600 | mV            |
| Diode capacitance         | $V_R = 0\text{ V}$ , $f = 1\text{ MHz}$                            |        | $C_D$      |     | 50   |     | pF            |
| Reverse recovery time     | $I_F = I_R = 50\text{ to }200\text{ mA}$ ,<br>recover to $0.1 I_R$ |        | $t_{rr}$   |     | 10   |     | ns            |

### Typical Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified




Figure 1. Forward Current vs. Forward Voltage




Figure 2. Forward Current vs. Forward Voltage




Figure 3. Reverse Current vs. Junction Temperature




Figure 5. Typ. Non Repetitive Forward Surge Current vs. Pulse Width





Figure 4. Diode Capacitance vs. Reverse Voltage

## Package Dimensions in millimeters (inches): DO35



Rev. 6 - Date: 29. January 2007  
 Document no.: 6.560-5004.02-4  
 94 9366

### Ozone Depleting Substances Policy Statement

It is the policy of Vishay Semiconductor GmbH to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

We reserve the right to make changes to improve technical design  
and may do so without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany



## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.