


POWER ROCKER SWITCH

CR Series

Features

- Rugged design with current switching up to 20 amps
- 2-color molded button available for maximum visibility
- Lighted and non-lighted versions
- Splash-proof option available
- Available in a wide variety of colors
- Fits to 3 panel cut-out widths
- Mechanical life: min. 100,000 operations



Electrical Ratings

| Switch Series | EN61058 Rating | UL1054 Rating | Electrical Life at Rated Load | |
|---------------|---------------------|---|------------------------------------|-----------------------------------|
| | | | According to VDE (Min. Operations) | According to UL (Min. Operations) |
| CR | 16(4)A, 250V~, T125 | 20A, 125VAC; 16A, 250VAC; 3/4HP, 250VAC | 10,000 | 6,000 |

Specifications

Electrical

| | |
|-----------------------------|------------------------------------|
| Dielectric Strength: | 1000VAC for 1 minute |
| Insulation Resistance: | 10 ⁸ ohms min at 500VDC |
| Initial Contact Resistance: | 0.020 ohms max |
| Temperature Range: | -20°C to +85°C |

Materials

| | |
|-------------------------|----------------------------|
| Actuator (non-lighted): | Nylon 66 94V-2 |
| Actuator (lighted): | Polycarbonate |
| Housing: | Nylon 66 94V-2 |
| Case: | Nylon 66 94V-2 |
| Spring: | Steel Wire |
| Contacts: | Silver Alloy |
| Movable Arm: | Silver-Plated Copper Alloy |
| Terminals: | Tin-Plated Copper Alloy |



