



TECHNICAL HOTLINE +44 (0)1268 563720

PORTABLE POWER

LCP 102 004 = 313518

LEAD CONNECTORS

GARDEN EXTENSION LEADS

RUBBER PLUGS

CABLE COUPLERS

10 AMP
TWO & THREE PIN

SPARES

10 AMP
TWO PIN

LCP 102 BLU

LCP 103 BLK

LCP 102P BLK

LCP 102S BLK

LCP 103P WHI

EXL 142 ORG DPK

PF 133 WHI

PF 133 ORG

PF 133 BLK

CCP 133 BLK

CCP 153 BLK

- LCP 102 BLK 10
- LCP 102 BLK DPK 10
- LCP 102 BLU 10
- LCP 102 ORG 10
- LCP 102 ORG DPK 10
- TWO PIN 10 AMP PLUG AND SOCKET
- LCP 103 WHI 10
- LCP 103 WHI DPK 10
- LCP 103 BLK 10
- LCP 103 BLK DPK 10
- THREE PIN 10 AMP PLUG AND SOCKET

This range of connectors provides a safe and easy method of extending power cables and electrical tools and appliances. With rubber cover and polypropylene inserts with integral cable grips. Retaining lugs prevent accidental disconnection.

Two pin versions are only for use with double insulated Class 2 appliances.

Three pin versions must be used with earthed appliances.

DIMENSIONS:
40 x 25 x 80mm
BS.5733/A: 1995

- LCP 102P BLK 10
- LCP 102P BLU 10
- LCP 102P ORG 10
- LCP 102P ORG DPK 10
- 10 AMP PLUG TWO PIN
- LCP 102S BLK 10
- LCP 102S BLU 10
- LCP 102S ORG 10
- 10 AMP SOCKET TWO PIN
- LCP 103P WHI 10
- LCP 103P BLK 10
- 10 AMP PLUG THREE PIN
- LCP 103S WHI 10
- LCP 103S BLK 10
- 10 AMP SOCKET THREE PIN

BS.5733/A: 1995

- EXL 142 ORG DPK 1
- 10 AMP TWO PIN WEATHER RESISTANT CONNECTOR SOCKET WITH 20 METRE CABLE

This product is supplied complete with 2 core <HAR> 1mm² PVC cable and a Duraplug rubber plug fitted with a 10 amp fuse (BS.1362). For use with double insulated Class 2 appliances.

Weather resistant to IPX4 the connector is manufactured from Nylon/PVC and features a retaining catch to prevent accidental disconnection.

BS.6991: 1990
BS.6500: 1994

- P 53 BLK 10
- 5 AMP
- PF 133 WHI 10
- PF 133 ORG 10
- PF 133 BLK 10
- FITTED WITH 13 AMP FUSE
- P 153 BLK 10
- 15 AMP

PF 133 With rubber cover and ABS/Polycarbonate base. Available with alternative fuse ratings to special order only. Approved by ASTA Licence no.99. BS.1363/A Pt.1: 1995

P 53 BLK Manufactured in rubber
P 153 BLK With rubber cover and ABS/Polycarbonate base.
BS.546: 1950

- CCP 53 BLK 1
- 5 AMP PLUG & SOCKET
- CCP 133 BLK 1
- 13 AMP PLUG & SOCKET
- CCP 153 BLK 1
- 15 AMP PLUG & SOCKET
- CCP 133P BLK 1
- SPARE 13 AMP PLUG

These splashproof couplers are a rugged means of connecting cables in industrial and commercial environments. Fitted with heavy duty cable clamps, tapered cable entry and fuse (13 amp version only).

DIMENSIONS:
Diameter x Length
CCP 53: 60 x 173mm
CCP 133: 65 x 182mm
CCP 153: 68 x 180mm
BS.5733
(BS.1363 Pin centres for 13 amp versions)
BS.5733
(BS.546 Pin centres for 5 and 15 amp versions)