


**T50R****111-95019**

T18S – T250XL



Available in a wide range of materials, these cable ties all feature internal serrations allowing for a positive hold onto cable, hose and pipe bundles. The design of the head guarantees a high tensile strength whilst allowing a very low insertion force, this, combined with the bent tail design of many of the ties, ensures a simple and quick installation. Whilst easily installed by hand, manual and pneumatic (for high volume applications) tensioning tools are available to ensure a consistent and safe installation.

For the routing, bundling and securing of cables, pipes and hoses.

**Base Data****Application Method**

Quick, simple fixing by hand or with HellermannTyton tensioning tools

**Colour**

Natural (NA)

**Package Content**

100

**Quantity (Sold Unit / EDP)**

100

**Quantity per**

Bag

**Recommended Application Tool**

MK3SP, MK3PNSP2, MK7P, MK7, MK7HT, MK20, MK6, MK6PN, MK9, MK9HT, MK21

**Logistic and Packaging****Carton Quantity**

7000

**EAN code**

4031026107844

**Quantity of Europallet**

126000

**Weight (kg) (Metric)**

1.3 kg

**Material and Specifications****Flammability**

UL94 V0

**Material**

Polyamide 6.6 V0 (PA66V0)

**Material Shortcut**

PA66V0

**Operating Temperature (Metric)**

-40 °C to +85 °C Continuous, (+105 °C for 500 h)

**Product Dimensions****Bundle Diameter max (Metric)**

50

**Bundle Diameter min (Metric)**

3.0

**Length L (Metric)**

200

**Minimum Tensile Strength (N)**

225

**Width W (Metric)**

4.6