

711147
↓ 59
60

multicomp

SIGNAL SECURITY CABLE

MAXIMUM OPERATING VOLTAGE	MAXIMUM CURRENT RATING PER CORE	MAXIMUM OPERATING TEMPERATURE	MAXIMUM CONDUCTOR RESISTANCE	NOMINAL RADIAL WALL THICKNESS OF OUTER SHEATH	NOMINAL OVERALL DIAMETER
50V rms.	1A	70°C	@ 20°C 92.4 Ω/KM	0.5MM	4 CORE 3.5MM 6 CORE 4.1MM 8 CORE 4.5MM 12 CORE 5.4MM

CORE COLOURS:

- 4 CORE RED, BLUE, YELLOW, BLACK.
- 6 CORE RED, BLUE, YELLOW, BLACK, WHITE, GREEN.
- 8 CORE RED, BLUE, YELLOW, BLACK, WHITE, GREEN, ORANGE, BROWN
- 12 CORE RED, BLUE, YELLOW, BLACK, WHITE, GREEN, ORANGE, BROWN, GREY, PINK, VIOLET, TURQUOISE.

A general purpose signal cable in 4, 6, 8 and 12 core configurations, ideal for use in security alarm installations. Seven strands of 0.2mm tinned annealed copper wire insulated with PVC to a minimum radial wall thickness of 0.15mm, overall sheathed in white PVC.