

			Core	
			Core - CPC	18nF / 100 m (Nominal)
			Screen - CPC	0.02nF / 100 m (Nominal)
		4 Core	Core - Core	nF / 100 m
			Core - CPC	nF / 100 m
	2.5 mm CSA		Screen - CPC.	nF / 100 m
		2 Core	Core - Core	nF / 100 m
			Core - CPC	nF / 100 m
			Screen - CPC	nF / 100 m
		4 Core	Core - Core	nF / 100 m
			Core - CPC	nF / 100 m
			Screen - CPC.	nF / 100 m
Bending	Radius		$r = 6 \times D$ (r = radius, (D = Diameter)	
Temperature	Operating		-20 to + 70 Deg. C.	
Voltage Drop	1.0mm CSA (DC or Single Phase AC)		44 mV / A / m	
	1.5mm CSA (DC or Single Phase AC)		29 mV / A / m	
	2.5 mm CSA (DC or Single Phase AC)		18 mV / A / m	
Current Rating	Cable Clipped (DC or Single Phase AC)	1.0mm	15 A	
		1.5 mm	19.5 A	
		2.5mm	27 A	
	Enclosed (DC or Single Phase AC)	1.0mm	13A	
		1.5 mm	16.5 A	
		2.5mm	23 A	
Warranty	Period		20 Years from Date of Manufacture	
	Identification		Date of Manufacture Marked On Cable	

Print Page & Close Window

Close Window