



Model No.	POS.1	POS.2	POS.3
	1MS1	ON	NONE
Term. Comm.	2-3		2-1
SCHEMATIC			

SWITCH FUNCTION

PANEL MOUNTING

P.C. MOUNTING

克重=250±50

RATING :

R : 0.4 Volt-Amps(VA) max. @20V max.(AC or DC)
 Q : 2Amps @250VAC
 5Amps @120 VAC or 28 VDC

SPECIFICATIONS
ELECTRICAL LIFE: 40,000 make-and-break cycles at full load.
CONTACT RESISTANCE: 10m Ω max. initial @ 2-4VDC
 100mA for both silver and gold plated contacts.
INSULATION RESISTANCE: 1,000M Ω min.
DIELECTRIC STRENGTH: 1,000 V RMS@sea level.
OPERATING TEMPERATURE: -30 ° C to 85 ° C.

MATERIALS
CASE: Dially phthalate (DAP) (UL94v-0).
ACTUATOR: Brass,chrome plated.
BUSHING: Brass,nickel plated.
HOUSING: Stainless Steel.
TERMINAL/CONTACT: Silver or gold plated.
SWITCH SUPPORT: Brass , Tin plated.

符號	原尺寸	修改後尺寸	變更日期
1 (A)			
2 (B)			
3 (C)			
4 (D)			
5 (E)			

SCALE (比例) :	3 : 2
TOLERANCE (公差) :	0.00 mm ± 0.25mm
ANGULAR :	± 2.54 mm
FILE NAME :	1MSP0330

德利威電子股份有限公司 DAILYWELL ELECTRONICS CO.,LTD.		TITLE	Miniature Toggle Switches			SIZE	A4
		DWG NO.	1MS1T2B4M7RE			UNIT	inch
REV.	A	DATA	JAN - 16 - 2003	SHEET	1 of 1	mm	
CHECKED BY	審核	Jack	DRAWN BY	製圖	BLUE		