



PG5 Disconnect Plugs

Terminal Blocks Accessories

Features and Benefits

Allow disconnect function when associated with the ZS4-SP and ZS4-SP-R1 terminal blocks.

Main Technical Data

	IEC	cULus - CSA	Ex e
Rated current	18 A	20 A	
Rated voltage	Standard use 400 V	150 V	
Impulse withstand voltage	6000 V		
Protection	IP 20	NEMA 1	

Mounting Instructions


Plug In

Tool
Torque

Material Specifications	Insulating material	Polyamide	
	Flammability	V0	
	NF F 16 101	I2F2	
Ambient temperature min/max	Service IEC 60068-2-1	-55 +110 °C	-67 +230 F
	Storage	-55 +110 °C	-67 +230 F
	Installing	-5 +40 °C	-23 +104 F

Ordering Details

PG5 Disconnect Plugs

Description	Type	Order Code	Pack ^(incl) pieces	Weight g (1 pce)
Equipped with linking bar	Orange  PG5-R1	1SNK 900 402 R0000	20	3.45

PG5 Accessories

Description	Type	Order Code	Pack ^(incl) pieces	Weight g (1 pce)
1 Blank card	White <input type="checkbox"/>	MC512	1SNK 140 000 R0000	22 0.06
Universal wire markers holder	Grey <input type="checkbox"/>	UMH	1SNK 900 611 R0000	10 0.20
Self adhesive strip	White <input type="checkbox"/>	SAT5	1SNK 900 614 R0000	5 6.00

PG5 Mounting Instructions

