

IF Series



- Regulated Single Output
- Industry Standard Pinout
- SIP or DIP Package
- Low Ripple & Noise
- 1000 VDC Isolation
- Optional 3000 VDC Isolation
- MTBF >2 Mhrs

Specification

Input

- Input Voltage Range • Nominal $\pm 10\%$
- Input Reflected Ripple • 20 mA rms through 12 μ H inductor, 5 Hz to 20 MHz
- Input Reverse Voltage Protection • None

Output

- Output Voltage • See table
- Minimum Load • None⁽⁴⁾
- Line Regulation • $\pm 0.5\%$ max
- Load Regulation • $\pm 0.5\%$ max
- Setpoint Accuracy • $\pm 2\%$ max
- Ripple & Noise • 50 mV pk-pk max, 20 MHz BW
- Temperature Coefficient • 0.02%/°C
- Short Circuit Protection • 1 sec
- Maximum Capacitive Load • 470 μ F

General

- Efficiency • See table
- Isolation Voltage • 1000 VDC standard, 3000 VDC option - see note 2
- Resistance • 1000 M Ω min
- Isolation Capacitance • 60 pF typical
- Switching Frequency • 50 kHz typical
- MTBF • >2 Mhrs

Environmental

- Operating Temperature • -40 to +85 °C (no derating)
- Storage Temperature • -40 to +125 °C
- Case Temperature • +100 °C max
- Cooling • Free-air convection

Notes

1. For DIP package, replace suffix 'S' with suffix 'D'.
2. For 3000 VDC isolation, add suffix '-H'.
3. All dimensions in inches (mm).
4. Operation at no load will not damage unit but it may not meet all specifications.

Input Voltage	Output Voltage	Output Current	Efficiency	Model Number ^(1,2)
5 V	3.3 V	333 mA	57%	IF0503S
	5.0 V	200 mA	65%	IF0505S
	9.0 V	111 mA	65%	IF0509S
	12.0 V	84 mA	68%	IF0512S
	15.0 V	67 mA	68%	IF0515S
12 V	3.3 V	333 mA	57%	IF1203S
	5.0 V	200 mA	63%	IF1205S
	9.0 V	111 mA	66%	IF1209S
	12.0 V	84 mA	68%	IF1212S
	15.0 V	67 mA	70%	IF1215S
24 V	3.3 V	333 mA	60%	IF2403S
	5.0 V	200 mA	65%	IF2405S
	9.0 V	111 mA	68%	IF2409S
	12.0 V	84 mA	68%	IF2412S
	15.0 V	67 mA	68%	IF2415S

Mechanical Details

