ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

3421650

DCP # REV DESCRIPTION DRAWN DATE CHECKD DATE APPRVD DATE NOT released			REVISIONS	00: No	DOC. NO. SPC-FODS .	• Effect	he: 12/21/	118 + DC	Effective: 12/21/98 + DCP No: 880
NOT released	-	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
			NOT released						



Excellent kit for bench meter - Straight sheath plug fits most popular bench DMM's. Leads are highly flexible silicone jacketed with safety sheath plugs. Rated to

EN61010-2-031 specifications.
Probes, leads & aligator clips - 1,000V CATII P2, 12A
Probe sprung hooks - 500V CATI P2, 3A

Spade lugs - 42V - 1,000V w/Safe User

FUR REFERENCE PURPOSES ONLY.						SPECIFIED,	UNLESS DIHERWISE	AL FATINDERS AND TECHNICAL INCOMMEND HOTEN ARE BREED LYON INFORMATION ALL FATINDERS AND TECHNICATE AND RELIABLE. BRACE CONTINUES OF IMPERIOR LOCATIONS OF IMPERIOR LOCATIONS, THE LACE SHAPE LOCATIONS AND LOCATIONS
ALLKOVED DI:		A PROCESS DV.	CHECKED BY:	2 7 2 7	Jeff McVicker	DRAWN BY:	NTON CONTAINED HEREN ARE BIGGE RATE AND RELIABLE BRACE CONDITION ID LIMBLETY WHATBORNEY IN CONNECTI IN LIMBLETY WHATBORNEY IN CONNECTI	
	באור. באורי	DATE.		DATE:		1/29/99	DATE:	UPON INFERNATION UP OF UPE ARE PRODUCT FOR THE ON THERETHE
SCALE: NTS			A 76	SIZE DWG. NO.		DRAWING TITLE: General Purpose DMM Kit,		
U.O.M.: INCHES [mm]		76-103						
SHEET: 1 OF 1			84N2145.dwg	ELECTRONIC FILE		DMM Kīt, Straight Plugs		9
-				7				

SPC-FD05,DWG